

SRF1020-SRF10150

Isolated 10.0AMP. Schottky Barrier Rectifiers




Features

- ✧ For surface mounted application
- ✧ Low power loss, high efficiency
- ✧ High current capability, low VF
- ✧ High reliability
- ✧ Epitaxial construction
- ✧ Guard-ring for transient protection

Mechanical Data

- ✧ Cases: ITO-220AB molded plastic
- ✧ Epoxy: UL 94V-0 rate flame retardant
- ✧ Polarity: As marked
- ✧ High temperature soldering guaranteed:
260°C/10 seconds .25", (6.35mm) from case.
- ✧ Weight: 2.24 grams
- ✧ Mounting torque: 5 in – 1bs. max.



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Rating at 25 °C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Type Number	Symbol	SRF 1020	SRF 1030	SRF 1040	SRF 1050	SRF 1060	SRF 1090	SRF 10100	SRF 10150	Units	
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	20	30	40	50	60	100	100	150	V	
Maximum RMS Voltage	V_{RMS}	14	21	28	35	42	70	70	105	V	
Maximum DC Blocking Voltage	V_{DC}	20	30	40	50	60	100	100	150	V	
Maximum Average Forward Rectified Current See Fig. 1	$I_{(AV)}$	10								A	
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	120								A	
Maximum Instantaneous Forward Voltage @5.0A	V_F	0.55			0.70		0.90		1.00	V	
Maximum D.C. Reverse Current @ $T_c=25^\circ\text{C}$ at Rated DC Blocking Voltage @ $T_c=100^\circ\text{C}$	I_R	0.5					0.1				mA mA
		15			10		5.0				
Typical Junction Capacitance (Note 2)	C_j	300								pF	
Typical Thermal Resistance (Note 1)	$R_{\theta JC}$	3.5					4.0				°C/W
Operating Junction Temperature Range	T_J	-65 to +125					-65 to +150				°C
Storage Temperature Range	T_{STG}	-65 to +150									°C

Notes: 1. Mounted on Heatsink Size of 2" x 3" x 0.25" Al-Plate.
2. Measured at 1MHz and Applied Reverse Voltage of 4.0V D.C.

SRF1020-SRF10150

Isolated 10.0AMP. Schottky Barrier Rectifiers

RATINGS AND CHARACTERISTIC CURVES (SRF1020 THRU SRF10150)

FIG.1- FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT PER LEG




FIG.3- TYPICAL FORWARD CHARACTERISTICS PER LEG




FIG.4- TYPICAL REVERSE CHARACTERISTICS PER LEG




FIG.5- TYPICAL JUNCTION CAPACITANCE PER LEG




FIG.6- TYPICAL TRANSIENT THERMAL IMPEDANCE PER LEG

