

CMLD6263A
CMLD6263C
CMLD6263S

**SURFACE MOUNT
DUAL PAIR, HIGH VOLTAGE
SILICON SCHOTTKY DIODES**

PICOmini™



SOT-563 CASE

Central™
Semiconductor Corp.

www.centrasemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CMLD6263 Series incorporates two pair, high voltage, low V_F Silicon Diodes in a space saving SOT-563 surface mount package. These diodes are designed for fast switching applications requiring a low forward voltage drop.

MARKING CODES:

CMLD6263A: 63A

CMLD6263C: 63C

CMLD6263S: 63S

FEATURES:

- High Voltage (70V)
- Low Forward Voltage
- Various Dual Pair Configurations

MAXIMUM RATINGS: ($T_A=25^\circ\text{C}$)

	SYMBOL		UNITS
Peak Repetitive Reverse Voltage	V_{RRM}	70	V
Continuous Forward Current	I_F	15	mA
Peak Forward Surge Current, $t_p=1.0\text{s}$	I_{FSM}	50	mA
Power Dissipation	P_D	250	mW
Operating and Storage Junction Temperature	T_J, T_{stg}	-65 to +150	$^\circ\text{C}$
Thermal Resistance	θ_{JA}	500	$^\circ\text{C/W}$

ELECTRICAL CHARACTERISTICS PER DIODE: ($T_A=25^\circ\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
I_R	$V_R=50\text{V}$		98	200	nA
BV_R	$I_R=10\mu\text{A}$	70			V
V_F	$I_F=1.0\text{mA}$		395	410	mV
C_T	$V_R=0, f=1.0\text{MHz}$			2.0	pF
t_{rr}	$I_R=I_F=10\text{mA}, I_{rr}=1.0\text{mA}, R_L=100\Omega$			5.0	ns


R2 (18-January 2010)

CMLD6263A
 CMLD6263C
 CMLD6263S

**SURFACE MOUNT
 DUAL PAIR, HIGH VOLTAGE
 SILICON SCHOTTKY DIODES**




SOT-563 CASE - MECHANICAL OUTLINE



SYMBOL	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.004	0.007	0.10	0.18
B	0.008		0.20	
C	0.022	0.024	0.56	0.60
D	0.059	0.067	1.50	1.70
E	0.020		0.50	
F	0.061	0.067	1.55	1.70
G	0.047		1.20	
H	0.006	0.012	0.15	0.30

SOT-563 (REV: R0)


PIN CONFIGURATIONS



**CMLD6263A
 COMMON ANODE**

- LEAD CODE:**
- 1) Cathode D2
 - 2) Anode D2, D4
 - 3) Cathode D4
 - 4) Cathode D3
 - 5) Anode D1, D3
 - 6) Cathode D1


MARKING CODE: 63A



**CMLD6263C
 COMMON CATHODE**

- LEAD CODE:**
- 1) Anode D1
 - 2) Anode D2
 - 3) Cathode D3, D4
 - 4) Anode D4
 - 5) Anode D3
 - 6) Cathode D1, D2

MARKING CODE: 63C



**CMLD6263S
 IN SERIES**

- LEAD CODE:**
- 1) Cathode D2
 - 2) Anode D3
 - 3) Cathode D4
 - 4) Cathode D3, Anode D4
 - 5) Anode D1
 - 6) Cathode D1, Anode D2

MARKING CODE: 63S

R2 (18-January 2010)