

TMX W328

SAW Front-End Filter – GSM Rx – RF
Specification (Rev-1)

■ Technical overview	P01
■ Configuration	P01
■ Typical Response	P02
■ Package Drawing	P02

TMX W328

SAW Bandpass Filter – GSM Rx - RF Specification (Rev 1)


April 15th, 2005

Electrical Parameters	Unit	Minimum	Typical ⁽¹⁾	Maximum
Source Impedance (single ended)	Ω	-	50 ⁽²⁾	-
Load Impedance (single ended)	Ω	-	50 ⁽²⁾	-
Center Frequency fo	MHz	-	942.5	-
Absolute Attenuation				
From 0 MHz to 880 MHz	dB	45	60	-
From 880 MHz to 905 MHz	dB	35	40	-
From 905 MHz to 915 MHz	dB	15	20	-
From 980 MHz to 982 MHz	dB	20	25	-
From 982 MHz to 1005 MHz	dB	23	26	-
From 1005 MHz to 1025 MHz	dB	30	38	-
From 1025 MHz to 1035 MHz	dB	35	40	-
From 1035 MHz to 1760 MHz	dB	40	50	-
From 1760 MHz to 2500 MHz	dB	30	40	-
Insertion Loss within 925 MHz – 960 MHz	dB	-	3.8	4.5
Passband Width	dB	-	35	-
Package type & size				
Length x Width	mm ²	-	3.0 x 3.0	-
Height	mm	-	1.3	1.5
Pin Out				
Input	2	Output	5	
Case Ground	1, 3, 4, 6	To Be Grounded	1, 3, 4, 6	

Notes :

- (1) Typical values are nominal performances at room temperature
- (2) No External matching circuit is required (see drawing hereunder)

50 Ω / 50 Ω Configuration



Maximum Ratings


Rating		Unit	Value
Operating Temperature Range	T _A	-20 to +70	°C
Storage Temperature Range	T _{stg}	-40 to +85	°C
DC Voltage	V _{DC}	10	V
Input Power		10	dBm

TMX W328

SAW Bandpass Filter – GSM Rx - RF
 Specification (Rev 1)

April 15th, 2005

TYPICAL S21 RESPONSE



PACKAGE DRAWING

