

# SURFACE-MOUNT CHIP BEAD ARRAY



## ACBA SERIES

### FEATURES:

- Array construction
- Avoid crosstalk

### OPTIONS:

- Tape & Reel is standard

### APPLICATIONS:

- Wireless application
- Networking System

### STANDARD SPECIFICATIONS:

Part Number	Z ( $\Omega$ ) $\pm 25\%$	Freq MHz	R <sub>DC</sub> $\Omega$ Max	I <sub>RATE</sub> Max mA
<b>1206 Series</b>				
ACBA-1206-30	30	100	0.20	500
ACBA-1206-60	60	100	0.25	400
ACBA-1206-120	120	100	0.30	350
ACBA-1206-150	150	100	0.35	250
ACBA-1206-220	220	100	0.35	250
ACBA-1206-300	300	100	0.40	250
ACBA-1206-470	470	100	0.50	200
ACBA-1206-600	600	100	0.50	200
ACBA-1206-1000	1000	100	0.75	150

Length (L)	0.126 $\pm$ 0.008 (3,20 $\pm$ 0,20)	Termination (D1)	0.016 $\pm$ 0.006 (0,40 $\pm$ 0,15)
Width (W)	0.063 $\pm$ 0.008 (1,60 $\pm$ 0,20)	Termination (D2)	0.008 $\pm$ 0.004 (0,20 $\pm$ 0,10)
Thickness (T)	0.035 $\pm$ 0.008 (0,90 $\pm$ 0,20)	Distance (D3)	0.031 $\pm$ 0.004 (0,80 $\pm$ 0,10)

• Operating Temperature: -40°C to +125°C

Note: All specifications subject to change without notice.

### PHYSICAL CHARACTERISTICS:

