

Clip, 5 x 20 mm, Version 3



250 VAC

**Description**

- Through hole mounting



References[General Product Information](#)**Weblinks**[Approvals](#), [RoHS](#), [CHINA-RoHS](#), [e-Store](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#)**Technical Data**

Fuse-Link	5 x 20 mm
Mounting	PCB
Terminal	Solder THT
Rated Voltage	250 VAC
Rated Current	6.3A
Degree of Protection	IP 00
Material: Terminals	see variants
Unit Weight (Socket/Cap)	0.37 g
Storage Conditions	0°C to 60°C, max. 70% r.h.
Product Marking	none

Soldering Methods	Wave
Solderability	235°C / 2 sec acc. to IEC 60068-2-20, Test Ta, method 1
Resistance to Soldering Heat	260°C / 10 sec acc. to IEC 60068-2-20, Test Tb, method 1A

Dimensions

Length 5.8 mm

**Drilling Diagrams****Variants**[Distributor-Stock-Check](#) | [SCHURTER-Stock-Check](#) | [e-Store](#)

Clip	Terminal	Material: Terminals	Order Number
●	Straight	Tin-Plated Bronze	7181.5001

Packaging Unit

Bulk (100 pcs.)