

SDS915

Switching Diode

Features

• SMD package : SOT-23

• Low forward voltage : V_F=0.9V(Typ.)

 \bullet Fast reverse recovery time : $t_{rr}{=}1.6~\mbox{\sc ns}\mbox{(Typ.)}$


• Small total capacitance : $C_T=2.2 pF(Typ.)$

Ordering Information

Type No.	Marking	Package Code	
SDS915	C5E	SOT-23	

Outline Dimensions

unit: mm



KSD-2002-002

SDS915

Absolute maximum ratings

Ta=25°C

Characteristic	Symbol	Rating	Unit
Peak reverse voltage	V_{RM}	85	V
Reverse voltage	V_R	80	V
Peak forward current	I_{FM}	300	mA
Average forward current	I _O	100	mA
Peak forward surge current(10ms)	I_{FSM}	2	Α
Power dissipation	P _D	150	mW
Junction temperature	T _j	150	°C
Storage temperature range	T _{stg}	-55 ~ 150	°C


Electrical Characteristics


Ta=25°C


Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Forward voltage	V _{F(1)}	$I_{\text{F}} = 1 \text{ mA}$	-	0.6	-	
	V _{F(2)}	$I_F = 10 \text{ mA}$	-	0.7	-	V
	V _{F(3)}	I _F =100 mA	-	0.9	1.2	
Reverse current	I_{R}	V _R =80V	-	-	0.5	μA
Total capacitance	C _T	$V_R=0$, $f=1$ MHz	-	2.2	4.0	рF
Reverse recovery time	t _{rr}	I _F =10 ^{mA} (Fig. 5)	-	1.6	4.0	ns

KSD-2002-002 2

Electrical Characteristic Curves











Fig. 5 Reverse recovery time(trr) test circuit



KSD-2002-002 3

The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).

Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..

Specifications mentioned in this publication are subject to change without notice.

KSD-2002-002