

This document was generated on 06/01/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Status:AOverview:veDescription:7.3	351500600 Ctive <u>rsablade</u> 30mm (.287") Pitch Wire-to-Wire VersaBlade™ Hybrid Receptacle Housing, without bunting Ears, 6 Circuits, Polyester UL94V-0, Natural	
Documents: Drawing (PDF)	RoHS Certificate of Compliance (PDF)	
Agency Certification		Serie
CSA	LR19980	image - Reference only
TUV	R72090206	
UL	E29179	EU RoHS China RoHS
		ELV and RoHS
General		Compliant
Product Family	Crimp Housings	REACH SVHC
Series	<u>35150</u>	Not Reviewed
Comments	Polarized to Mating Part, Positive Lock	Halogen-Free
Overview	versablade	Status
Product Name	VersaBlade™	Not Reviewed
Physical		Need more information on product environmental compliance?
Circuits (maximum)	6	environmental compliance?
Color - Resin	Natural	Email productcompliance@molex.com
Flammability	94V-0	For a multiple part number RoHS Certificate
Gender	Male	Compliance, click here
Glow-Wire Compliant	No	
Keying to Mating Part	None	Please visit the <u>Contact Us</u> section for any
Lock to Mating Part	Yes	non-product compliance questions.
Material - Resin	Polyester	
Number of Rows	2	
Packaging Type	Bag	
Panel Mount	No	Search Parts in this Series
Pitch - Mating Interface (ir		<u>35150</u> Series
Pitch - Mating Interface (m		
Polarized to Mating Part	Yes	Mates With
Stackable	No	35151-061* Plug Housings
Temperature Range - Ope	erating -40°C to +120°C	
Material Info		Use With VersaBlade™ Crimp Terminals, <u>35745</u> , <u>35746</u> , <u>35747</u>

This document was generated on 06/01/2010 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

