


BZX384-C2V4 THRU BZX384-C75**ZENER DIODES****SOD-323**

Dimensions are in inches and (millimeters)

FEATURES

- ◆ Silicon Planar Power Zener Diodes
- ◆ The Zener voltages are graded according to the international E 24 standard. Standard Zener voltage tolerance is $\pm 5\%$. Replace "C" with "B" for $\pm 2\%$ tolerance. Other voltage tolerances and other Zener voltages are available upon request.

**MECHANICAL DATA**

Case: SOD-323 Plastic Package

Weight: approx. 0.004 g

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

| | SYMBOL | VALUE | UNIT |
|--|------------------|-------------------|------|
| Zener Current | I _{ZM} | 250 | mA |
| Power Dissipation at T _{amb} = 25°C | P _{tot} | 200 ¹⁾ | mW |
| Junction Temperature | T _j | 175 | °C |
| Storage Temperature Range | T _s | - 65 to +175 | °C |

NOTES:

(1) Device on fiberglass substrate, see layout.

| | SYMBOL | MIN. | TYP. | MAX. | UNIT |
|---|-------------------|------|------|-------------------|-------|
| Thermal Resistance Junction to Ambient Air | R _{thJA} | - | - | 650 ¹⁾ | K/W |
| Forward Voltage at I _F = 10 mA | - | - | - | 0.9 | Volts |

NOTES:

(1) Valid provided that electrodes are kept at ambient temperature

BZX384-C2V4 THRU BZX384-C75

ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

| Type | Marking | Zener Voltage ⁽¹⁾ at I _{ZT1} | Dynamic Resistance at I _{ZT1} | Temp. Coeffi- cient of Zener Voltage at I _{ZT1} | Test Current I _{ZT1} (mA) | Dynamic Resistance at I _{ZT2} | Test Current I _{ZT2} (mA) | Reverse Leakage Current | |
|-------------|---------|---|--|---|--|---|--|----------------------------|--------------------------|
| | | V _Z (V) | r _{zj} (Ω) | α _{VZ} (10 ⁻⁴ /K) | | r _{zj} (Ω) | | I _R (μA) | at V _R (V) |
| BZX384-C2V4 | W1 | 2.20 ... 2.60 | 70 (≤100) | -3.5 ... 0.0 | 5 | 275 | 1.0 | 50.0 | 1.0 |
| BZX384-C2V7 | W2 | 2.50 ... 2.90 | 75 (≤100) | -9.0 ... -4.0 | 5 | 300 (≤600) | 1.0 | 20.0 | 1.0 |
| BZX384-C3 | W3 | 2.80 ... 3.20 | 80 (≤95) | -9.0 ... -3.0 | 5 | 325 (≤600) | 1.0 | 10.0 | 1.0 |
| BZX384-C3V3 | W4 | 3.10 ... 3.50 | 85 (≤95) | -8.0 ... -3.0 | 5 | 350 (≤600) | 1.0 | 5.00 | 1.0 |
| BZX384-C3V6 | W5 | 3.40 ... 3.80 | 85 (≤90) | -8.0 ... -3.0 | 5 | 375 (≤600) | 1.0 | 5.00 | 1.0 |
| BZX384-C3V9 | W6 | 3.70 ... 4.10 | 85 (≤90) | -7.0 ... -3.0 | 5 | 400 (≤600) | 1.0 | 3.00 | 1.0 |
| BZX384-C4V3 | W7 | 4.00 ... 4.60 | 80 (≤90) | -6.0 ... -1.0 | 5 | 410 (≤600) | 1.0 | 3.00 | 1.0 |
| BZX384-C4V7 | W8 | 4.40 ... 5.00 | 50 (≤80) | -5.0 ... +2.0 | 5 | 425 (≤500) | 1.0 | 3.00 | 2.0 |
| BZX384-C5V1 | W9 | 4.80 ... 5.40 | 40 (≤60) | -3.0 ... +4.0 | 5 | 400 (≤480) | 1.0 | 2.00 | 2.0 |
| BZX384-C5V6 | WA | 5.20 ... 6.00 | 15 (≤40) | -2.0 ... +6.0 | 5 | 80 (≤400) | 1.0 | 1.00 | 2.0 |
| BZX384-C6V2 | WB | 5.80 ... 6.60 | 6.0 (≤10) | -1.0 ... +7.0 | 5 | 40 (≤150) | 1.0 | 3.00 | 4.0 |
| BZX384-C6V8 | WC | 6.40 ... 7.20 | 6.0 (≤15) | +2.0 ... +7.0 | 5 | 30 (≤80) | 1.0 | 2.00 | 4.0 |
| BZX384-C7V5 | WD | 7.00 ... 7.90 | 6.0 (≤15) | +3.0 ... +7.0 | 5 | 30 (≤80) | 1.0 | 1.00 | 5.0 |
| BZX384-C8V2 | WE | 7.70 ... 8.70 | 6.0 (≤15) | +4.0 ... +7.0 | 5 | 40 (≤80) | 1.0 | 0.70 | 5.0 |
| BZX384-C9V1 | WF | 8.50 ... 9.60 | 6.0 (≤15) | +5.0 ... +8.0 | 5 | 40 (≤100) | 1.0 | 0.50 | 6.0 |
| BZX384-C10 | WG | 9.40 ... 10.6 | 8.0 (≤20) | +5.0 ... +8.0 | 5 | 50 (≤150) | 1.0 | 0.20 | 7.0 |
| BZX384-C11 | WH | 10.4 ... 11.6 | 10 (≤20) | +5.0 ... +9.0 | 5 | 50 (≤150) | 1.0 | 0.10 | 8.0 |
| BZX384-C12 | WI | 11.4 ... 12.7 | 10 (≤25) | +6.0 ... +9.0 | 5 | 50 (≤150) | 1.0 | 0.10 | 8.0 |
| BZX384-C13 | WK | 12.4 ... 14.1 | 10 (≤30) | +7.0 ... +9.0 | 5 | 50 (≤170) | 1.0 | 0.10 | 8.0 |
| BZX384-C15 | WL | 13.8 ... 15.6 | 10 (≤30) | +7.0 ... +9.0 | 5 | 50 (≤200) | 1.0 | 0.05 | 0.7 V _{Znom.} |
| BZX384-C16 | WM | 15.3 ... 17.1 | 10 (≤40) | +8.0 ... +9.5 | 5 | 50 (≤200) | 1.0 | 0.05 | 0.7 V _{Znom.} |
| BZX384-C18 | WN | 16.8 ... 19.1 | 10 (≤45) | +8.0 ... +9.5 | 5 | 50 (≤225) | 1.0 | 0.05 | 0.7 V _{Znom.} |
| BZX384-C20 | WO | 18.8 ... 21.2 | 15 (≤55) | +8.0 ... +10 | 5 | 60 (≤225) | 1.0 | 0.05 | 0.7 V _{Znom.} |
| BZX384-C22 | WP | 20.8 ... 23.3 | 20 (≤55) | +8.0 ... +10 | 5 | 60 (≤250) | 1.0 | 0.05 | 0.7 V _{Znom.} |
| BZX384-C24 | WR | 22.8 ... 25.6 | 25 (≤70) | +8.0 ... +10 | 5 | 60 (≤250) | 1.0 | 0.05 | 0.7 V _{Znom.} |
| BZX384-C27 | WS | 25.1 ... 28.9 | 25 (≤80) | +8.0 ... +10 | 2 | 65 (≤300) | 0.5 | 0.05 | 0.7 V _{Znom.} |
| BZX384-C30 | WT | 28.0 ... 32.0 | 30 (≤80) | +8.0 ... +10 | 2 | 70 (≤300) | 0.5 | 0.05 | 0.7 V _{Znom.} |
| BZX384-C33 | WU | 31.0 ... 35.0 | 35 (≤80) | +8.0 ... +10 | 2 | 75 (≤325) | 0.5 | 0.05 | 0.7 V _{Znom.} |
| BZX384-C36 | WW | 34.0 ... 38.0 | 35 (≤90) | +8.0 ... +10 | 2 | 80 (≤350) | 0.5 | 0.05 | 0.7 V _{Znom.} |
| BZX384-C39 | WX | 37.0 ... 41.0 | 40 (≤130) | +10.0 ... +12 | 2 | 80 (≤350) | 0.5 | 0.05 | 0.7 V _{Znom.} |
| BZX384-C43 | WY | 40.0 ... 46.0 | 45 (≤150) | +10.0 ... +12 | 2 | 85 (≤375) | 0.5 | 0.05 | 0.7 V _{Znom.} |
| BZX384-C47 | WZ | 44.0 ... 50.0 | 50 (≤170) | +10.0 ... +12 | 2 | 85 (≤375) | 0.5 | 0.05 | 0.7 V _{Znom.} |
| BZX384-C51 | X1 | 48.0 ... 54.0 | 60 (≤180) | +10.0 ... +12 | 2 | 85 (≤400) | 0.5 | 0.05 | 0.7 V _{Znom.} |
| BZX384-C56 | X2 | 52.0 ... 60.0 | 70 (≤200) | +9.0 ... +11 | 2 | 100 (≤425) | 0.5 | 0.05 | 0.7 V _{Znom.} |
| BZX384-C62 | X3 | 58.0 ... 66.0 | 80 (≤215) | +9.0 ... +12 | 2 | 100 (≤450) | 0.5 | 0.05 | 0.7 V _{Znom.} |
| BZX384-C68 | X4 | 64.0 ... 72.0 | 90 (≤240) | +10.0 ... +12 | 2 | 150 (≤475) | 0.5 | 0.05 | 0.7 V _{Znom.} |
| BZX384-C75 | X5 | 70.0 ... 79.0 | 95 (≤255) | +10.0 ... +12 | 2 | 170 (≤500) | 0.5 | 0.05 | 0.7 V _{Znom.} |


NOTES:

(1) Measured with pulses t_p = 5 ms

RATINGS AND CHARACTERISTICS CURVES BZX384-C2V4 THRU BZX384-C75


Breakdown characteristics

$T_j = \text{constant (pulsed)}$



Breakdown characteristics


$T_j = \text{constant (pulsed)}$




RATINGS AND CHARACTERISTICS CURVES BZX384-C2V4 THRU BZX384-C75

Breakdown characteristics

$T_j = \text{constant (pulsed)}$




Forward characteristics



Admissible power dissipation versus ambient temperature


For conditions, see footnote in table "Absolute Maximum Ratings"




RATINGS AND CHARACTERISTICS CURVES BZX384-C2V4 THRU BZX384-C75

Pulse thermal resistance versus pulse duration


For conditions, see footnote in table "Absolute Maximum Ratings"




Dynamic resistance versus Zener current



Capacitance versus Zener voltage




Dynamic resistance versus Zener current




RATINGS AND CHARACTERISTICS CURVES BZX384-C2V4 THRU BZX384-C75

Dynamic resistance versus Zener current




Thermal differential resistance versus Zener voltage


For conditions, see footnote in table "Absolute Maximum Ratings"



Dynamic resistance versus Zener voltage




Temperature dependence of Zener voltage versus Zener voltage




RATINGS AND CHARACTERISTICS CURVES BZX384-C2V4 THRU BZX384-C75


Change of Zener voltage versus junction temperature




Temperature dependence of Zener voltage versus Zener voltage



Change of Zener voltage versus junction temperature



Change of Zener voltage from turn-on up to the point of thermal equilibrium versus Zener voltage



RATINGS AND CHARACTERISTICS CURVES BZX384-C2V4 THRU BZX384-C75

Change of Zener voltage from turn-on
up to the point of thermal equilibrium
versus Zener voltage

