CRYSTAL OSCILLATOR LOW-JITTER SAW OSCILLATOR

EG - 2021 / 2001CA series

•Frequency range
•Supply voltage

•Output
•Function
•Thickness

: 62.5 MHz to 250 MHz
: 2.5V/ EG-2021CA
3.3V/ EG-2001CA
: CMOS
• CMOS
: Output enable(OE)

•Very low jitter and low phase noise by SAW unit.



Specifications (characteristics)


ltem		Symbol	Specifications			Remarks	
			EG-2021CA		EG-2001CA	Remarks	
Output frequency range		fo	62.500 MHz to 170.000MHz	170.001MHz to 250.000MHz	106.250 MHz to 170.000 MHz		
Supply voltage		Vcc	2.5 V± 0.125 V		3.3 V± 0.3 V		
	Storage temperature	T_stg	-40 °C to +100 °C			Store as bare product after unpacking	
range	Operating temperature	T_use	P: 0 °C to +70 °C R: -5 °C to +85 °C		P: 0 °C to +70° C		
Frequency tolerance		f_tol	G: ± 50 × 10 ⁻⁶ H: ± 100 × 10 ⁻⁶		Z: $\pm 50 \times 10^{-6}$ Y, H: $\pm 100 \times 10^{-6}$	P:0 °C to 70 °C,R:-5 °C to +85 °C *1	
Current consumption		lcc	25 mA Max.	30 mA Max.	50 mA Max.	No load condition, Max. frequency range	
Disable current		l_dis	600 μA Max.		10 μA Max.	OE=GND	
Symmetry		SYM	45 % to 55 %	40 % to 60 %	45 % to 55 %	CMOS load:50 % Vcc level, L_CMOS= Max.	
High output voltage		Voн	Vcc-0.35 V Min.		Vcc-0.4 V Min.	loh = -8 mA	
Low output voltage		Vol	0.35 V Max.		0.4 V Max.	lol = 8 mA	
Output load condition		L_CMOS	15 pF Max.			Max. frequency and Max. supply voltage range	
High input voltage		Vih	70 % Vcc Min.			OE terminal	
Low input voltage		VIL	30 % Vcc Max.		OE terminal		
Rise time / Fall time		t _r / t _f	2 ns Max.			CMOS load:20 % Vcc to 80 % Vcc level	
Start-up time		t_str	10 ms Max.			Time at minimum supply voltage to be 0 s	
		t DJ	0.2 ps Typ.			Deterministic Jitter	
Jitter *2		t RJ	3 ps Typ.			Random Jitter	
		t rms	3 ps Typ.			σ (RMS of total distribution)	
		t _{p-p}	25 ps Typ.			Peak to Peak	
		tacc	4 ps Typ.			Accumulated Jitter(σ) n=2 to 50000 cycles	
Phase Jitter		t PJ	0.05 × 10 ⁻³ Ul Typ. 1 ps Max.			Offset frequency: 12 kHz to 20 MHz	
Frequency aging*3		f_aging			+25 °C, First year, Vcc=2.5 V,3.3 V		


- *1 As per below table
- *2 Based on DTS-2075 Digital timing system made from WAVECREST with jitter analysis software VISI6.
- *3 Except:CHPA,CHRA,PCH

Model	EG-2021CA				
Model	Details of frequency tolerance	A *4	N *5		
	HP: ±100×10 ⁻⁶ (0°C to +70°C)	CHPA	CHPN		
Frequency	HR: ±100×10 ⁻⁶ (-5°C to +85°C)	CHRA	CHRN		
tolerance	GP: ±50×10 ⁻⁶ (0°C to +70°C)	_	CGPN		
	GR: +50×10 ⁻⁶ (-5°C to +85°C)	_	CGRN*7		

EG-2001CA				
Output mode		P:Symmetry 50 ±5 %		
	H: ±100×10 ⁻⁶ (0°C to +70°C) *4	PCH		
Frequency	Y: ±100×10 ⁶ (0°C to +70°C) *5	PCY		
tolerance	Z: ±50×10 ⁻⁶ (0°C to +70°C) *6	PCZ		

- ⁴4 This includes initial frequency tolerance, temperature variation, supply voltage variation, load variation, reflow drift, and aging(+25 °C,10 years).
- *5 This includes initial frequency tolerance, temperature variation, supply voltage variation, load variation, and reflow drift.(except aging)
- *6 This includes initial frequency tolerance, and temperature variation.(except reflow drift, supply voltage variation, load variation and aging)
- *7 Please contact us for inquiries.





http://www.epsontoyocom.co.jp

"QMEMS" EPSON TOYOCOM

In order to meet customer needs in a rapidly advancing digital, broadband and ubiquitous society, we are committed to offering products that are one step a head of the market and a rank above the rest in quality. To achieve our goals, we follow a "3D (three device) strategy" designed to drive both horizontal and vertical growth. We will to grow our three device categories of "Timing Devices", "Sensing Devices" and "Optical Devices", and expand vertical growth through a combination of products from these categories.

A Quartz MEMS is any high added value quartz device that exploits the characteristics of quartz crystal material but that is produced using MEMS (micro-electro-mechanical system) processing technology.

Market needs are advancing faster than previously imagined toward smaller, more stable crystal products, but we will stay ahead of the curve by rolling out products that exceed market speed and quality requirements. We want to further accelerate the 3D strategy by QMEMS.

Quartz devices have become crucial in the network environment where products are increasingly intended for broadband, ubiquitous applications and where various types of terminals can transfer information almost immediately via LAN and WAN on a global scale. Epson Toyocom Corporation addresses every single aspect within a network environment. The new corporation offers "Digital Convergence" solutions to problems arising with products for consumer use, such as, core network systems and automotive systems.



PROMOTION OF ENVIRONMENTAL MANAGEMENT SYSTEM CONFORMING TO INTERNATIONAL STANDARDS

At Epson Toyocom, all environmental initiatives operate under the Plan-Do-Check-Action(PDCA) cycle designed to achieve continuous improvements. The environmental management system (EMS) operates under the ISO 14001 environmental management standard.

ISO 14000 is an international standard for environmental management that was established by the International Standards Organization in 1996 against the background of growing concern regarding global warming, destruction of the ozone laver and global deforestation

All of our major manufacturing and non-manufacturing sites, in Japan and overseas, completed the acquisition of ISO 14001 certification. In the future, new group companies will be expected to acquire the certification around the third year of operations.

WORKING FOR HIGH QUALITY

In order provide high quality and reliable products and services than meet customer needs,

Epson Toyocom made early efforts towards obtaining ISO9000 series certification and has acquired ISO9001 for all business establishments in Japan and abroad. We have also acquired ISO/TS 16949 certification that is requested strongly by major automotive manufacturers as standard.

QS-9000 is an enhanced standard for quality assurance systems formulated by leading U.S. automobile manufacturers based on the international ISO 9000 series.

ISO/TS 16949 is a global standard based on QS-9000, a severe standard corresponding to the requirements from the automobile industry.

► Explanation of the mark that are using it for the catalog

Free	▶ Pb free. ▶ Complies with EU RoHS directive.
Rotts	 ▶ Pb free terminal designed. Contains Pb in products exempted by RoHS directive. (Contains Pb in sealing glass, high melting temperature type solder or other.) ▶ Complies with EU RoHS directive.
For Automotive	► The products have been designed for high reliability applications such as Automotive.

Notice

- •This material is subject to change without notice.
- Any part of this material may not be reproduced or duplicated in any form or any means without the written permission of Epson Toyocom.
- •The information, applied circuitry, programming, usage, etc., written in this material is intended for reference only. Epson Toyocom does not assume any liability for the occurrence of infringing on any patent or copyright of a third party. This material does not authorize the licensing for any patent or intellectual copyrights.
- •Any product described in this material may contain technology or the subject relating to strategic products under the control of the Foreign Exchange and Foreign Trade Law of Japan and may require an export license from the Ministry of International Trade and Industry or other approval from another government agency.
- You are requested not to use the products (and any technical information furnished, if any) for the development and/or manufacture of weapon of mass destruction or for other military purposes. You are also requested that you would not make the products available to any third party who may use the products for such prohibited purposes.
- •These products are intended for general use in electronic equipment. When using them in specific applications that require extremely high reliability, such as the applications stated below, you must obtain permission from Epson Toyocom in advance.

 / Space equipment (artificial satellites, rockets, etc.) / Transportation vehicles and related (automobiles, aircraft, trains, vessels, etc.)

 / Medical instruments to sustain life / Submarine transmitters / Power stations and related / Fire work equipment and security equipment / traffic control equipment / and others requiring equivalent reliability.
- In this new crystal master for Epson Toyocom, product codes and markings will remain as previously identified prior to the merger.
 Due to the on-going strategy of gradual unification of part numbers, please review product codes and markings, as they will change during the course of the coming months.

We apologize for the inconvenience, but we will eventually have a unified part numbering system for Epson Toyocom that will be user friendly.