

PHEMT GaAs IC High Linearity Positive Control SPDT Switch DC-2 GHz



AS205-322

Features

- High Linearity (50 dBm IP3 @ 0.9 GHz) @ 3 V
- Low Insertion Loss (0.35 dB @ 0.9 GHz)
- +3 V Operation
- Ultra Miniature MLP 2 x 1 mm 5 Lead Package
- PHEMT Process

Description

The AS205-322 is a PHEMT GaAs FET IC high linearity SPDT switch in a MLP 2 x 1 mm 5 lead plastic package. This switch has been designed for use where extremely high linearity, low insertion loss and ultra miniature package size are required. It can be controlled with positive, negative or a combination of both voltages. Some standard implementations include antenna changeover, T/R and diversity switching over 2 W. The AS205-322 switch can be used in many analog and digital wireless communication systems including cellular, GSM and DECT applications.

Electrical Specifications at 25°C (0, +3 V)

Parameter ¹	Frequency ²	Min.	Typ.	Max.	Unit
Insertion Loss ³	DC-0.5 GHz DC-1.0 GHz DC-2.0 GHz		0.35 0.35 0.55	0.40 0.50 0.70	dB
Isolation	DC-0.5 GHz DC-1.0 GHz DC-2.0 GHz	20 15 10	23 18 13		dB
VSWR ⁴	DC-1.0 GHz DC-2.0 GHz		1.3:1 1.3:1	1.5:1 1.5:1	dB

Operating Characteristics at 25°C (0, +3 V)


Parameter	Condition	Frequency	Min.	Typ.	Max.	Unit
Switching Characteristics ⁵	Rise, Fall (10/90% or 90/10% RF) On, Off (50% CTL to 90/10% RF) Video Feedthru			60 100 50		ns ns mV
Input Power for 1 dB Compression		0.9 GHz		+33		dBm
Intermodulation Intercept Point (IP3)	For Two-tone Input Power +17 dBm	0.9 GHz		+50		dBm
Control Voltages	$V_{Low} = 0$ to 0.2 V @ 20 μ A Max. $V_{High} = +3$ V @ 100 μ A Max. to +5 V @ 200 μ A Max.					

1. All measurements made in a 50 Ω system, unless otherwise specified.


2. DC = 300 kHz.

3. Insertion loss changes by 0.003 dB/°C.


MLP 2 x 1 mm 5 Lead




Typical Performance Data (0, +3 V)



Insertion Loss vs. Frequency



Isolation vs. Frequency



VSWR vs. Frequency

Truth Table


V ₁	V ₂	J ₁ -J ₂	J ₁ -J ₃
0	V _{High}	Isolation	Insertion Loss
V _{High}	0	Insertion Loss	Isolation

V_{High} = +3 to +5 V.

Absolute Maximum Ratings

Characteristic	Value
RF Input Power	6 W Max. > 900 MHz 0/+7 V Control
Control Voltage	-0.2 V, +7 V
Operating Temperature	-40°C to +85°C
Storage Temperature	-65°C to +150°C
θ _{JC}	25°C/W

Pin Out



DC blocking capacitors (C_{BL}) must be supplied externally.
C_{BL} = 100 pF for operating frequency >500 MHz.

www.DataSheet.in