

Product SKU:	C2100.21.01
Product Description:	Hook-Up Wire, UL 1015, CSA TEW, Gauge Size (AWG): 24, Conductor/Strands: 7/32, Jacket: Premium Grade PVC, Temperature Range: -20°C to +105°C - Black - 1000 Ft. Spool
Product Category:	Electronics - Hook-Up Wire - UL 1015, CSA TEW - STRANDED CONDUCTORS - Black

188

Product Construction:	
Conductor:	• 24 thru 10 AWG
	• Fully-annealed, tinned copper per ASTM B-33
	• Solid or stranded
Insulation:	• Color Code: See chart below
	Premium grade color-coded PVC
	• Temperature range: $-20\hat{A}^{\circ}C$ to $+105\hat{A}^{\circ}C$
Product Specification:	
Conductor Size (AWG):	• 24
Conductor/Strands:	• 7/32
No. of Pairs:	• 1
Jacket Color:	• Black
Nominal Insulation Thickness (in):	• 0.032
Nominal Insulation Thickness (mm):	• 0.81
Nominal Outside Diameter (in):	• 0.088
Nominal Outside Diameter (mm):	• 2.23

Standard Packaging: • 1000' Spool

Standard Package Quantity:	• 1
UPC #:	• 079407767618
Put-up:	• 1000
SCC-14:	• 50079407767611
Cube:	• 277.0596
Weight Per Unit of Measure:	• .0046
ColorOption:	• Black
Product Information:	
Applications:	• Internal wiring of electrical and electronic equipment
	• Internal wiring of panels and meters
	• Point-to-point wiring
	• Suggested voltage rating: 600 Volts
Compliances:	• CSA Type TEW
	• Designed to Meet UL VW-1 Vertical Wire Flame Test
	• UL Style 1015 - 105°C, 600V
Packaging:	• 10,000 foot (3048m) Reels
	• 1000' (305 m) Spools
	• Other put-ups available- consult Customer Service
Reference Charts	
Color Code Chart	
Technical Specifications	
Unit Conversion Factors	
Cable Design Equations - Balanced Pair	
In sull discuss of Isseles (Duran suti-	

- Insulation and Jacket Properties
- Temperature Conversion Chart
- Decimal and Unit Conversion Factors
- Cable Design Equations Braid Shield
- AWG Conductor Chart
- Conduit Capacity Chart Downloaded from Electronic components distributor

Cable Design Equations - Coaxial Cable Engineering Prefixes Coax Connector Cross Reference Glossary







