

This document was generated on 04/14/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0010321061		\frown	
Status:	Active		ff a	
		POX™ Wire-to-Board Header, Vertical, with Friction Lock, 6		
	tion PS-5197-001 (PDF) tion PS-5197-003 (PDF)	Product Specification PS-5197-004 (PDF) Product Specification PS-5197-005 (PDF) Product Specification PS-5281-002 (PDF) RoHS Certificate of Compliance (PDF)	Series image - Reference only	
Agency Certif	ication			
CSA TUV UL	ication	LR19980 R72090224 E29179	EU RoHS ELV and RoHS Compliant REACH SVHC	
General Product Family Series Application		PCB Headers <u>5281</u> Wire-to-Board	Contains SVHC: No Halogen-Free Status Not Reviewed	
Product Name		SPOX™	Need more information on product	
Physical			environmental compliance?	
Breakaway		No	Email productcompliance@molex.com	
Circuits (Loaded)		6	For a multiple part number RoHS Certificate	
Circuits (maximum)		6	Compliance, <u>click here</u>	
Color - Resin		Natural		
Durability (mating cycles max)		30	Please visit the <u>Contact Us</u> section for any	
First Mate / Last Break		No	non-product compliance questions.	
Flammability		94V-2		
Glow-Wire Compliant		No		
Guide to Mating Part		No		
Keying to Mating Part		None	Search Parts in this Series	
Lock to Mating Part		Yes	<u>5281</u> Series	
Material - Metal		Brass		
Material - Plating Mating		Tin	Mates With	
Material - Plating Termination		Tin	<u>5197</u> SPOX [™] Crimp Terminal Housing	
Material - Resin		Nylon	,	
Number of Rows		1		
Orientation		Vertical		
PC Tail Length (in)		0.142 In		
PC Tail Length (mm)		3.60 mm		
PCB Locator		No		
PCB Retention		None		
PCB Thickness Recommended (in)		0.062 ln		
PCB Thickness Recommended (mm)		1.60 mm		
Packaging Type Pitch - Mating Interface (in)		Bag 0.200 In		
Pitch - Mating Interface (in) Pitch - Mating Interface (mm)		5.08 mm		
Plating min: Mating (µin)		200		
Plating min: Mating (µm)		5		
Plating min: Termination (µin)		200		
Plating min: Termination (µm)		5		
Polarized to PCB		No		
Shrouded		Partial		
Stackable		A Lo Hon		

No

Stackable

Surface Mount Compatible (SMC) Temperature Range - Operating Termination Interface: Style	No -40°C to +105°C Through Hole			
Electrical				
Current - Maximum per Contact Voltage - Maximum	7A 250V			
Material Info				
Old Part Number	5281-06A			
Reference - Drawing Numbers				
Product Specification	PS-5197-001, PS-5197-003, PS-5197-004, PS-5197-005, PS-5281-002, RPS-5197-001, RPS-5281-001			
Sales Drawing	SD-5281-NA			

This document was generated on 04/14/2010 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

