




Telecommunication COMMON MODE CHOKE Transformers

DT35-2111T
DT35-2112T
DT35-2113T
DT35-2114T



DIMENSIONS IN mm

A	B	C	D	E	F	G
10.5 MAX.	2.5 MIN.	8.5 MAX.	10.5 MAX.	5.0 ± 0.3	2.5 ± 0.3	

ELECTRICAL CHARACTERISTICS				
	DT35-2111T	DT35-2112T	DT35-2113T	DT35-2114T
T.R	(N1:N2): 1:1 ± 2% @10KHz 0.1V	(N1:N2): 1:1 ± 2% @10KHz 0.1V	(N1:N2): 1:1 ± 2% @10KHz 0.1V	(N1:N2): 1:1 ± 1% @10KHz 0.1V
L	PRI: 5mH ± 10% PRI: 5mH ± 20% 160mA @10KHz 0.1V	PRI: 5mH ± 10% PRI: 5mH ± 20% 160mA @10KHz 0.1V	PRI: 3.5mH ± 10% PRI: 3.5mH ± 20% 160mA @10KHz 0.1V	PRI: 0.5mH ± 5% SEC: 0.5mH ± 5% @10KHz 0.1V
L.K	-----	180uH ± 10% @100KHz 1V	150uH ± 10% @100KHz 1V	-----
C	50pF Max. @100KHz 1V	50pF Max. @100KHz 1V	50pF Max. @100KHz 1V	
D.C.R	N1: 18 Ω ± 15% N2: 18 Ω ± 15%	N1: 16.5 Ω ± 15% N2: 20 Ω ± 15%	N1: 13.7 Ω ± 15% N2: 16.5 Ω ± 15%	N1: 1.7 Ω ± Max. N2: 1.7 Ω ± Max.
HI-POT	850 VAC 1 SEC	850 VAC 1 SEC	850 VAC 1 SEC	600 VAC 60 SEC
SCHEMATIC	1	1	1	2

DELTA ELECTRONICS, INC.

(TAOYUAN PLANT CPBG) 31-1, SHIEN PAN ROAD, KUEI SAN INDUSTRIAL ZONE, TAOYUAN SHIEN, TAIWAN, R.O.C.

TEL: 886-3-3626301 FAX: 886-3-3618901

http://www.deltaww.com