

# PPC

## PPC-7407

Socket 478 P4/P4-M/  
Celeron® 17" Panel PC

### Features and Benefits:

- High performance for multimedia solution
- Modularized panel and main case
- Switchable 12.1", 15" or 17" panel
- 1 x HDD (standard)
- 1 x FDD (slim)
- 1 x CD-ROM (slim)
- I/O port highlights:
  - VGA
  - 4 serials, +5V or +12V seletable
  - 1 parallel
  - 2 USB
  - 1 keyboard
  - 1 mouse
  - 1 10/100/1000Mbps LAN,
  - 8 DI/ 8DO
  - line-in/-out/mic
- Industry level of durability
- Spill proof water-resistant design

- 
- 



No. 24, Lane 365, Yang Guang St., Nei Hu District, Taipei 114, Taiwan, R.O.C.

Tel: +886-2-8751-1111

Fax: +886-2-8751-1199

Email: sales@protech.com.tw

http://www.protech.com.tw

Intel®  
Communications.

Alliance  
Affiliate Member  
BRONZE

ISO CERTIFIED  
9001 14001


# PPC-7407

Socket 478 Pentium® 4 17" Panel PC


17" Panel Front View



12.1" / 15" / 17" Modularizing View



Connector Description



## Specification

### Systems

<b>CPU Support</b>	Intel® Pentium® 4/ Pentium® 4-M/ Celeron® Up to 2.8GHz
<b>Memory Support</b>	1 x DIMM, DDR333 memory up to 1GB max.
<b>Front Bazel</b>	Aluminum
<b>Open Frame</b>	Yes
<b>IP65/NEMA4</b>	Yes
<b>Power Supply</b>	AC 200W power supply
<b>O.S. Support</b>	Win 98SE/2000/XP, Linux 8.0/9.0
<b>Dimension (WxHxD)</b>	440 x 344 x 107 mm (17.32" x 13.54" x 4.21")
<b>System Weight</b>	13 kg (28.66lb)
<b>VESA Mounting Support</b>	N/A
<b>Certificate</b>	CE/FCC/LVD/ULx

### I/O Ports

<b>USB</b>	2 x USB2.0
<b>KB/Mouse</b>	2
<b>Audio</b>	Line in/Line out/MIC in
<b>Paralle</b>	1 x parallel port (SPP/EPP/ECP) Yes
<b>Serial Port</b>	4 x COMs (pin 9 support +5V or +12V), COM2 for RS232/422/485

<b>Digital I/O</b>	8 DI / 8 DO
<b>LAN</b>	10/100/1000 Mbps
<b>VGA</b>	1600 x 1200 max.
<b>Brightness Control</b>	VR on rear panel
<b>Drive Bay</b>	1 x 3.5" HDD, 1 x slim CD, 1 x slim FDD, 1 x DOC (build-in riser card)
<b>Expansion Slot</b>	1 x PCI + 1 x ISA or 3 x PCI + 3 x ISA

### Display

<b>LCD</b>	17" SXGA TFT LCD
<b>Touch Screen</b>	Analog resistive (USB interface)

### Ordering

<b>PPC-7407</b>	panel PC with 17" LCD, S478 P-4 CPU board, resistive touchscreen, 200W AC power supply
<b>PPC-7400-CFKIT</b>	IDE CF card
<b>PPC-7400-1P1I</b>	1 x PCI + 1 x ISA riser card for PPC740X
<b>PPC-7400-3P3I</b>	3 x PCI + 3 x ISA riser card for PPC740X

All of trademarks and brand names are the property of their owners. Trademark "Protech" is the property of Protech Systems Co., Ltd. All information contained in this document is subject to change without any prior notice. This catalog is copyrighted in Jan. 2005.