

This document was generated on 05/26/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0678005001 Status: Active

Overview: serial ata products

1.27mm (.050") Pitch Serial ATA High Speed Header, Vertical, Surface Mount, with **Description:**

Locking Latch, 7 Circuits, Gold (Au) Flash, for 1.60mm (.063") PCB, with PCB Locator

Pegs, Lead-free

Documents: 3D Model

RoHS Certificate of Compliance (PDF)

Drawing (PDF)

Agency Certification

LR 19980 CSA UL E29179

General

PCB Headers Product Family Series 67800

Board-to-Board. Wire-to-Board Application

Staggered Solder Pin|Metal Post Length 2.65mm (.104") Comments

No

Overview serial ata products

Serial ATA **Product Name**


Physical

Stackable

Breakaway No Circuits (Loaded) 7 Circuits (maximum) 7 Color - Resin Black Durability (mating cycles max) 50 First Mate / Last Break Yes Flammability 94V-0 Glow-Wire Compliant No Guide to Mating Part No Keying to Mating Part Yes Lock to Mating Part Yes Material - Metal Brass Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic

Number of Rows Orientation Vertical **PCB** Locator Yes **PCB** Retention Yes Packaging Type Tray 0.050 In Pitch - Mating Interface (in) Pitch - Mating Interface (mm) 1.27 mm Pitch - Term. Interface (in) 0.050 In Pitch - Term. Interface (mm) 1.27 mm Plating min: Mating (µin) Plating min: Mating (µm) 0.05 Plating min: Termination (µin) 75 Plating min: Termination (µm) 1.9 Polarized to Mating Part Yes Polarized to PCB Yes Shrouded Fully



China RoHS

EU RoHS ELV and RoHS Compliant **REACH SVHC** Not Reviewed Halogen-Free

Status

Halogen-Free

Need more information on product environmental compliance?

Email productcompliance@molex.com For a multiple part number RoHS Certificate of Compliance, click here

Please visit the Contact Us section for any non-product compliance questions.

Search Parts in this Series

67800 Series

Temperature Range - Operating -35°C to +85°C Termination Interface: Style Surface Mount

Electrical

Current - Maximum per Contact 1.5A Voltage - Maximum 15V DC

Solder Process Data

Lead-free Process Capability Reflow Capable (SMT only)

Material Info

Reference - Drawing Numbers

Packaging Specification PK-67800-001 Sales Drawing SD-67800-005

This document was generated on 05/26/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

