

This document was generated on 04/09/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Documents: <u>3D Model</u> Drawing (PDF)	Product Specification PS-99020-0011 (PDF) RoHS Certificate of Compliance (PDF)	
Agency Certification		Serie
CSA	LR19980	image - Reference only
UL	E29179	
. .		EU RoHS China RoHS
General		ELV and RoHS
Product Family	Ribbon Cable / Wire Trap Connectors	Compliant
Series	<u>90327</u>	REACH SVHC
Comments	Low Profile	Contains SVHC: No
Component Type	Housing	Halogen-Free
Glow-Wire Compliant	No	<u>Status</u>
Product Name	Picoflex®	Not Reviewed
-		Need more information on product
Physical		environmental compliance?
Circuits (Loaded)	26	
Color - Resin	Natural	Email productcompliance@molex.com
Durability (mating cycles max)	100	For a multiple part number RoHS Certificate
Entry Angle	90° Angle	Compliance, <u>click here</u>
Flammability	94V-0	Please visit the Contact Us section for any
Lock to Mating Part	Yes	
Material - Metal	Phosphor Bronze	non-product compliance questions.
Material - Plating Mating	Gold	
Material - Plating Termination	Tin	
Material - Resin	Polyester	
Number of Rows	2	Search Parts in this Series
PCB Retention	_ None	<u>90327</u> Series
Packaging Type	Bag	
Pitch - Mating Interface (in)	0.050 ln	Mates With
Pitch - Mating Interface (mm)	1.27 mm	Low Profile Vertical <u>90325</u> , Low Profile
Polarized to Mating Part	Yes	Right Angle 90800 , 90715 , 90814 , 9077
Stackable	No	Vertical
Surface Mount Compatible (SMC		
Temperature Range - Operating		
Termination Interface: Style	IDT or Pierce	Application Tooling FAQ
,		Tooling specifications and manuals are
Wire Insulation Diameter	1.00mm (.039") max.	found by selecting the products below.
Wire Size AWG	26, 28 Dibban Cabla	Crimp Height Specifications are then
Wire/Cable Type	Ribbon Cable	contained in the Application Tooling
Electrical		Specification document.
	1 24	Global
Current - Maximum per Contact	1.2A	Description Product #
Voltage - Maximum	250V	Arbor Press Fixture 0690201902
Material Info		Extrator Tool <u>0621006000</u> for Picoflex™
Reference - Drawing Num	bers	Connectors
Product Specification	PS-99020-0011	Semi-Automatic 0691271001
Sales Drawing	SDA 00227	Bench Press

Product Specification Sales Drawing

SDA-90327

| <u>FAQ</u>

Description	Product #
Arbor Press Fixture	0690201902
Extrator Tool	<u>0621006000</u>
for Picoflex [™]	
Connectors	
Semi-Automatic	<u>0691271001</u>
Bench Press	

PB14 for 90327

Connectors, 4 to 26 Circuit Extraction Tool 0690081070 (Plastic) for 90327 Connector, 4-26 Circuit Handtool for <u>0690081090</u> 90327, 90584 and 91577 Picoflex® Connectors, 4-26 Circuit Arbor Press Fixture 0690201908 for 91577 Picoflex® Connectors

This document was generated on 04/09/2010 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

