CERTI-CRIMP II SAHT

onlinecomponents.com

Standard Straight Action Hand Tool Design Widely used in the Aircraft and Military industries

Features:

Fixed dies Straight action jaw closure Ratchet mechanism ensures complete crimp cycle Emergency only ratchet release Terminal/wire positioning aids & Ins. adjustment on most tools Ergonomic non-slip handles Approximate weight 0.59 kg (1.3 lbs) Revised:

Part Number	Description	mm ² (AWG) or other
91572-1	AMP CT 2.0 Receptacle	0.12 - 0.4 (26-22)
91576-1	AMP DYNAMIC D-2	0.08 - 0.22 (28-24)
91595-1	AMP DYNAMIC D-2	0.4 - 1.0 (22-18)
91558-1	AMP DYNAMIC D-3	0.6 - 1.5 (20-16)
91559-1	AMP DYNAMIC D-3	0.2 - 0.6 (24-20)
91503-1	AMPLIMITE HD-20	0.08 - 0.6 (28-20) Ins. Ø0.76-1.52mm
91513-1	AMPLIMITE HD-20	0.4 - 1.0 (22-18) No Ins. Crimp
91548-1	AMPLIMITE HD-20	0.08 - 0.6 (28-20) No Ins. Crimp
91549-1	AMPLIMITE HD-20	0.08 - 0.22 (28-24) Ins. Ø0.76-1.52mm
91520-1	AMPLIMITE HD-22	0.08 - 0.4 (28-22) Ins. Ø0.76-1.27mm
91537-1	AMPMODU II FFC	0.15 - 0.4 (26-22)
91516-1	AMPMODU IV	0.05 - 0.6 (30-20)
91517-1	AMPMODU IV, V	0.15 - 0.4 (26-22) Ins. Ø1.02-1.52mm
91512-1	Commercial MATE-N-LOK	0.2 - 1.0 (24-18) Ins. Ø1.52-2.54mm
91501-1	Micro MATE-N-LOK	0.2 - 0.6 (24-20) Ins. Ø0.89-1.53mm
91502-1	Micro MATE-N-LOK	0.05 - 0.12 (30-26) Ins. Ø0.89-1.53mm
91522-1	Mini-Universal MATE-N-LOK	0.4 - 1.0 (22-18) Ins. Ø1.5-2.39mm
91529-1	Mini-Universal MATE-N-LOK	0.15 - 0.4 (26-22) Ins. Ø1.19-1.75mm
91536-1	Mini-Universal MATE-N-LOK "F" Ins. Crimp	0.5 - 1.42 (22-16) Ins. Ø2.0-3.2mm
91594-1	Mini-Universal MATE-N-LOK "O/L" Ins. Crimp	0.5 - 1.42 (22-16) Ins. Ø2.0-3.2mm
91577-1	MULTILOCK 040	0.4 - 0.6 (22-20)
91505-1	TYPE III+	0.2 - 1.42 (24-16) Ins. Ø1.14-2.54mm

Only the most popular options are listed here, please use our online search by terminal PN to find the right tool for your application, and contact us where information is unclear or missing - there may well be something available for your requirement.

July 2008

Image representative of type only

CERTI-CRIMP II SAHT - Short Mencetheonents.com

Ideal for working in confined spaces Widely used in the Aircraft and Military industries

Features:

Fixed dies Straight action jaw closure Ratchet mechanism ensures complete crimp cycle Emergency only ratchet release Terminal/wire positioning aids & Ins. adjustment on most tools Ergonomic non-slip handles Approximate weight 0.5 kg (1.1 lbs)



Part Number	Description	mm ² (AWG) or other
1901600-2	PIDG STRATO-THERM Terminals & Splices	1.0 - 1.5 (18-16)
1901611-2	PIDG STRATO-THERM Terminals & Splices	0.2 - 0.6 (24-20)
Only the mos	t popular options are listed here, please use our online search by terminal PN to find the right tool where information is unclear or missing - there may well be something available for your	

CERTI-CRIMP II SAHT - Long Handle

Low handle force for ease of operation Widely used in the Aircraft and Military industries

Features:

Fixed dies Straight action jaw closure Ratchet mechanism ensures complete crimp cycle Emergency only ratchet release Terminal/wire positioning aids & Ins. adjustment on most tools Ergonomic non-slip handles Approximate weight 0.59 kg (1.3 lbs) Image representative of type only



Part Number	Description	mm² (AWG) or other
1901600-1	PIDG STRATO-THERM Terminals & Splices	1.0 - 1.5 (18-16)
1901611-1	PIDG STRATO-THERM Terminals & Splices	0.2 - 0.6 (24-20)
		the second se

Image representative of type only

July 2008

CERTI-CRIMP II SAHT - Head Auge (Deputation)

Head only for use with Power Assist options

Features:

Fixed Dies Straight action jaw closure Ratchet mechanism ensures complete crimp cycle Emergency only ratchet release Terminal/wire positioning aids & Ins. adjustment on most tools

Use with: 1213805-[] Battery Tool Kit 1213860-[] Adapter, Electric Terminator

Part Number	Description	mm ² (AWG) or other
1-1901600-2	PIDG STRATO-THERM Terminals & Splices	1.0 - 1.5 (18-16)
1-1901611-1	PIDG STRATO-THERM Terminals & Splices	0.2 - 0.6 (24-20)
Only the most	popular options are listed here, please use our online search by terminal PN to find the right where information is unclear or missing - there may well be something available for	

CERTI-CRIMP II SA Battery Tool Kit

Convert your existing Hand Tools into Powered! 1213805-2 - Kit only without Head 1213805-5 - Kit only without Head (GB Power Plug)

Features:

Heads can be removed from Hand Tools, or are also available as a [-3] option. Example 91500-1 CERTI-CRIMP II SAHT; handles can be

removed and the head used with this kit. Alternatively 91500-3 (head only) is also available.

Over 100 crimps per charge Compact - only 360mm (14") long and weighs 1.57kg (3.48lbs)

The Tool Kit is supplied in a durable plastic carry case and includes: Battery Tool with the relevant CERTI-CRIMP II SAHT Adapter Battery Charger 230 v Two Batteries

for more information, please see the Power Assist section

Adapter - CERTI-CRIMP II to Electric Terminator


1213860-1 - Adapter only

Features:

For use with Electric Terminators (1673677-2 or 1490076-2) and any CERTI-CRIMP II SAHT Head.

Heads can be removed from Hand Tools, or are also available as a [-3] option.

Example 91500-1 CERTI-CRIMP II SAHT; the head can be removed from the handles and used along with this adapter on the Electric Terminator . Alternatively 91500-3 (head only) is also available.







Double Action Hand Tool onlinecomponents.com

Note: The approvals shown against the tools listed are only applicable when using terminals and wires recommended for the relevant industry. Widely used in Aircraft and Military applications

Image representative of type only

July 2008

Features:

Fixed dies Ratchet mechanism ensures complete crimp cycle Emergency only ratchet release Terminal/wire positioning aids & Ins. adjustment on many tools Ergonomic non-slip handles Approximate weight 0.54 kg (1.2 lbs)



Part Number	Description	mm ² (AWG) or other
45216	PIDG Closed End Splice	1.0 - 1.5 (18-16)
90009-8	Special GB Railways PIDG FASTON Tool Qualifications: LUL RSE 024 pt6 & EE6161	1.5 - 2.5 (16-14)
90035-3	Special GB Railways PIDG FASTON Tool Qualifications: LUL RSE 024 pt6 & EE6161	0.4 - 1.0 (22-18)
482930-1	Special French tool for PIDG FASTON 2.8 (.110) with crimp orientation at 90° Marks the applied product with a one dot indent code.	0.15 - 0.4 (26-22)
46121	Standard Tool for PIDG Terminals & Splices; PLASTI-GRIP Butt Splices Qualifications: Mil-T-7928; LUL RSE 024 pt6 & EE6161 Marks the applied product with a one dot indent code	0.15 - 0.4 (26-22)
47386	Standard Tool for PIDG & PLASTI-GRIP Terminals and PIDG Splices - GB Railways Qualifications: Mil-T-7928/7; LUL RSE 024 pt6 & EE6161 Marks the applied product with a one dot indent code.	0.4 - 1.5 (22-16) Ins. Ø3.18mm max
47386-5	French PIDG & PLASTI-GRIP Ring Tongue Tool - includes French Instuction Sheet Meets Mil-T-7928 - AMP specified level Marks the applied product with a one dot indent code.	0.4 - 1.5 (22-16)
47387	Standard Tool for PIDG & PLASTI-GRIP Terminals and Splices - GB Railways Qualifications: Mil-T-7928; LUL RSE 024 pt6 & EE6161 Marks the applied product with a two dot indent code.	1.25 - 2.0 (16-14) 0.6 - 1.5 (20-16) HD Ins. Ø3.8mm1 max
525690	Special GB Aerospace PIDG & PLASTI-GRIP Ring Tongue Tool. Equivalent to 47386 but has special retaining pins/rings to reduce the risk of tool parts falling off whilst building and maintaining aircraft.	0.6 - 1.0 (20-18)
525691	Special GB Aerospace PIDG & PLASTI-GRIP Ring Tongue Tool. Equivalent to 47387 but has special retaining pins/rings to reduce the risk of tool parts falling off whilst building and maintaining aircraft.	1.5 - 2.5 (16-14)
47386-4	GB Special for PIDG & PLASTI-GRIP Ring Tongue's & FASTON's Meets Mil-T-7928 - AMP specified level for Ringtongues only Marks the applied product with a one dot indent code.	0.4 - 1.5 (22-16)
47387-7	GB Special for PIDG & PLASTI-GRIP Ring Tongue's and FASTON's: Meets Mil-T-7928 - AMP specified level for Ring Tongues only Marks the applied product with a two dot indent code.	1.5 - 2.5 (16-14) 0.6 - 1.5 (20-16) HD
46447	SOLISTRAND High Temp Terminals and Splices	0.4 - 6.0 (22-10)
49592	Standard Tool for SOLISTRAND Terminals & Splices Qualifications: Mil-T-7928	2.5 - 4.0 (14-12)
49935	Standard Tool for SOLISTRAND Terminals and Splices Qualifications: Mil-T-7928; LUL RSE 024 pt6 & EE6161	0.4 - 6.0 (22-10)
69363	Standard tool for SOLISTRAND Terminals & Splices Qualifications: Mil-T-7928; LUL RSE 024 pt6 & EE6161	0.15 - 0.6 (26-20)
525693	Special tool for SOLISTRAND Terminals & Splices (GB) Qualifications: Mil-T-7928; LUL RSE 024 pt6 & EE6161 Equivalent to 49935 but has special retaining pins/rings to reduce the risk of tool parts falling off whilst building and maintaining aircraft.	0.4 - 6.0 (22-10)
46673	STRATO-THERM Uninsulated Terminals & Splices	0.4 - 1.5 (22-16)

Convert your existing Hand Tools into Powered! 1213804-2 - Kit only without Head 1213804-5 - Kit only without Head (GB Power Plug)

Features:

Example 47386 DAHT; handles can be removed and the head used with this kit.

Over 100 crimps per charge Compact - only 360mm (14") long and weighs 1.57kg (3.48lbs)

The Tool Kit is supplied in a durable plastic carry case and includes: Battery Tool with the relevant DAHT Adapter Battery Charger 230 v Two Batteries

for more information, please see the Power Assist section

Adapter - Double Action Hand Tool to 626 Pneumatic

1213563-1 - Adapter only

Features:

Heads can be removed from Hand Tools, example: the Handles from 47386 can be removed and the head used with this Adapter (includes cam).

Also required: Hand held power unit 189721-1 or Foot actuated Power Unit 189722-1

for more information, please see the Power Assist section

Image representative of type only





Image representative of type only

Revised:

C-Head SAHT

onlinecomponents.com

Revised: Ju

Image representative of type only

July 2008

69710-1 - Base Tool without Die-set Widely used in Aircraft and Military applications Can be used with all C-Head SAHT Dies

Features:

Interchangeable Dies Straight action jaw closure Ratchet mechanism ensures complete crimp cycle Emergency only ratchet release Approximate weight 0.86 kg (1.9 lbs)



C-Head SAHT - LD

1901260-1 Base Tool without Die-set A light duty alternative to 69710-1 Can be used with all C-Head SAHT Dies EXCEPT: - Die-set - C-Head SAHT - HD

- Through Splice applicatons

Features:

Interchangeable Dies Straight action jaw closure Ratchet mechanism ensures complete crimp cycle Emergency only ratchet release Ergonomic non-slip handles Approximate weight 0.5 kg (1.1 lbs)





Die-set - C-Head SAHT

onlinecomponents.com

A range of Die-sets for many premium crimp applications

Features:

Use in: Hand Tool Frame 69710-1 Hand Tool Frame 1901260-1 (see restrictions)

Battery Tool Kits: Open Head 1213840-[] Closed Head 1213819-[]

Adapters for C-Head Dies: Electric Terminator 1901556-1 Press SSC- 2FP 8-1481221-3

Image representative of type only

P

Part Number	Description	mm ² (AWG) or other
58212-1	AMPLIMITE	RG 142, 142A, 142B
576711	PIDG STRATO-THERM Terminals & Splices	0.2 - 0.4 (24-22)
576714	PIDG STRATO-THERM	1.5 (16)
576715	PIDG STRATO-THERM	1.0 (18)
576720	PIDG STRATO-THERM	0.5 (22)
47807-1	PIDG, PLASTI-GRIP Terminals & Splices	1.5 - 2.5 (16-14)
47806-2	PIDG, PLASTI-GRIP, Terminals & Splices	0.4 - 1.5 (22-16)
1-539634-9	Pin 50 ohm, size 8 kit	Gore Cable Type: GSC-03-81748-00

Only the most popular options are listed here, please use our online search by terminal PN to find the right tool for your application, and contact us where information is unclear or missing - there may well be something available for your requirement.


Die-set - C-Head SAHT - HD

A range of Heavy Duty Die-sets for many premium crimp applications

Features:

Use in: Hand Tool Frame 69710-1

Adapters for C-Head Dies: Electric Terminator 1901556-1 Press SSC- 2FP 8-1481221-3 Image representative of type only



Part Number	Description	mm ² (AWG) or other
59993-1	AMPLIMITE	8 (10)
576716	PIDG STRATO-THERM Terminals & Splices	2.5 (14)
576723	PIDG STRATO-THERM Terminals & Splices	6.0 (10)
576742	PIDG STRATO-THERM Terminals & Splices	4.0 (12)
69735	PIDG STRATO-THERM Terminals & Splices	4.0 - 6.0 (12-10)
47808-6	PIDG, PLASTI-GRIP Terminals & Splices	4.0 - 6.0 (12-10)
90140-1	TYPE XII Contact	6.0 - 10.0 (10-8)
90145-1	TYPE XII Contact	2.5 - 4.0 (14-12)
58380-1	Universal MATE-N-LOK	3.0 (12)
58380-2	Universal MATE-N-LOK	5.0 (10)

Only the most popular options are listed here, please use our online search by terminal PN to find the right tool for your application, and contact us where information is unclear or missing - there may well be something available for your requirement.

_

Revised:

C-Head SAHT Battery Tool Kitonlinecomponents.com

1213819-2 - CLOSED head 1213819-5 - CLOSED head (GB Power Plug) 1213840-2 - OPEN head 1213840-5 - OPEN head (GB Power Plug)

Features:

Over 100 crimps per charge Compact - only 360mm (14") long and weighs 1.57kg (3.48lbs)

The Tool Kit is supplied in a durable plastic carry case and includes: Battery Tool with the relevant C-Head SAHT Adapter Battery Charger 230 v Two Batteries

for more information, please see the Power Assist section

Adapter - C-Head SAHT to Bench Press SSC-2FP

8-1481221-3 - Adapter only

Features:

Adapts Bench Top Press SSC- 2FP (1481004-7 pictured) to take C-Head SAHT Dies

for more information on the Press and Press options, please see the Power Assist section



1901556-1 - Adapter only


Features:

Adapts the Electric Terminator to take C-Head SAHT Dies

for more information on the Press and Press options, please see the Power Assist section

Image representative of type only







Revised:

Heavy Head Hand Tool

onlinecomponents.com

Note: The specifications shown against the tools listed are only applicable when using terminals recommended for the relevant industry Widely used in Aircraft and Military applications

Features:

Fixed dies Straight action jaw closure Ratchet mechanism ensures complete crimp cycle Emergency only ratchet release Terminal/wire positioning aids & Ins. adjustment on most tools Approximate weight 0.95 kg (2.1 lbs)



Revised:

Part Number	Description	mm ² (AWG) or other
234170-1	AMP DYNAMIC D-5	1.5 - 2.5 (16-14)
234171-1	AMP DYNAMIC D-5	4.0 - 6.0 (12-10)
1366044-1	AMP DYNAMIC D-5 Receptacle	8.0 (10) Ins. Ø4.9-7.8mm
90246-1	Standard tool for PIDG FASTON	2.5 - 4.0 (14-12)
90276-2	Special GB Railways PIDG FASTON Tool Qualifications: LUL RSE 024 pt6 & EE6161	4.0 - 6.0 (12-10)
484364-1	PIDG STRATO-THERM Terminals & Splices	1.0 (18)
576782	Special GB Aerospace tool for thin-wall PIDG STRATO-THERM Terminals & Splices Qualified to BS 4G178	2.5 (14)
576783	Special GB Aerospace tool for thin-wall PIDG STRATO-THERM Terminals & Splices Qualified to BS 4G178	4.0 (12)
576784	Special GB Aerospace tool for thin-wall PIDG STRATO-THERM Terminals & Splices with PTFE or PEEK thin-wall Insulation Qualified to BS 4G178	6.0 (10)
576778	Special GB Aerospace tool for thin-wall PIDG STRATO-THERM Terminals & Splices Qualified to BS 4G178	0.2 - 0.4 (24-22)
576779	Special GB Aerospace tool for thin-wall PIDG STRATO-THERM Terminals & Splices Qualified to BS 4G178	0.5 (22)
576780	Special GB Aerospace tool for thin-wall PIDG STRATO-THERM Terminals & Splices Qualified to BS 4G178	1.0 (18)
576781	Special GB Aerospace tool for thin-wall PIDG STRATO-THERM Terminals & Splices Qualified to BS 4G178	1.5 (16)
59287-2	PIDG, PLASTI-GRIP Large Expansion Terminals & Splices	4.0 - 6.0 (12-10) (16-14) HD
525692	Special GB Aerospace PIDG & PLASTI-GRIP Ring Tongue Tool. Equivalent to 59239-4 but has special retaining pins/rings to reduce the risk of tool parts falling off whilst building and maintaining aircraft.	4.0 - 6.0 (12-10)
59239-4	Standard Tool for PIDG & PLASTI-GRIP Terminals and Splices - GB Railways Qualifications: Mil-T-7928; LUL RSE 024 pt6 & EE6161 Marks the applied product with a one dot indent code.	3.0 - 5.0 (12-10) 1.5 - 2.5 (16-14) HD Ins. Ø5.84mm max
69322-1	SOLISTRAND High Temp Parallel Splice	0.4 - 6.0 (22-10)
69355	SOLISTRAND Terminals & Splices	10.0 (8)
59461	STRATO-THERM Uninsulated Terminals & Splices with Insulation Support	4.0 - 6.0 (12-10) (16-14) HD
90382-2	TYPE XII Contact	1.5 - 4.0 (16-12)
90384-1	TYPE XII Contact	6.0 - 10.0 (10-8)

Only the most popular options are listed here, please use our online search by terminal PN to find the right tool for your application, and contact us where information is unclear or missing - there may well be something available for your requirement.

July 2008

Heavy Head Hand Tool Batter

Convert your existing Hand Tools into Powered! 1901235-2 - Kit only without head 1901235-5 - Kit only without head (GB Power Plug)

Features:

Heads can be removed from many Heavy Head Hand Tools, example: the Handles from 59239-4 can be removed and the head used with this kit. See Instruction sheet 409-10068 for a list of compatible tools

Over 100 crimps per charge Compact - only 360mm (14") long and weighs 1.57kg (3.48lbs)

The Tool Kit is supplied in a durable plastic carry case and includes: Battery Tool with Heavy Head Adapter Battery Charger 230 v Two Batteries

for more information, please see the Power Assist section




525432-1 - Adapter only

Features:

Heads can be removed from Hand Tools, example: the Handles from 59239-4 can be removed and the head used with this Adapter on the 626 Pneumatic system.

Also required: Adapter Holder with Ratchet 356304-1 or Adapter Holder without Ratchet 189928-1 and Hand held power unit 189721-1 or Foot actuated Power Unit 189722-1

Image representative of type only



S.C

Image representative of type only

CERTI-LOK

169400 Base Tool without Die-set

Features:

Interchangeable Dies Straight action jaw closure Ratchet mechanism ensures complete crimp cycle Easy access ratchet release Handle pressure adjustment with locking device Ergonomic non-slip handles Approximate weight 0.64 kg (1.4 lbs) rs



Revised:

Description	mm ² (AWG) or other
Complete tool for LOCKING CLIP	0.03 - 0.56 (32-20)
Die-set for PIDG, PLASTI-GRIP Terminals & Splices Use in Hand Tool Frame 169400 GB Railways PIDG & PLASTI-GRIP Tool (Signal only) Meets; Mil-T 7928 F, VG 88720, DIN 41611	0.6 - 6.0 (20-10)
Die-set for SOLISTRAND Terminals & Splices Use in Hand Tool Frame 169400	0.4 - 6.0 (22-10)
	Complete tool for LOCKING CLIP Die-set for PIDG, PLASTI-GRIP Terminals & Splices Use in Hand Tool Frame 169400 GB Railways PIDG & PLASTI-GRIP Tool (Signal only) Meets; Mil-T 7928 F, VG 88720, DIN 41611 Die-set for SOLISTRAND Terminals & Splices

Only the most popular options are listed here, please use our online search by terminal PN to find the right tool for your application, and contact us where information is unclear or missing - there may well be something available for your requirement.

Adapter - CERTI-LOK to Electric Terminator

169411 - Adapter only

Features:

Adapts the Electric Terminator to take CERTI-LOK Dies

for more information on the Press and Press options, please see the Power Assist section





A unique tool that applies terminals from special small reels

Features:

Terminal feeding and cutting device Straight action jaw closure Ratchet mechanism ensures complete crimp cycle Easy access ratchet release Handle pressure adjustment with locking device Egonomic non-slip handles



Revised:

Part Number	Description	mm ² (AWG) or other
169424-1	AMPLIMITE HD-20	0.08 - 0.56 (28-20) Ins. Ø0.76-1.52mm
734643-1	AMPLIVAR	
734203-1	AMPMODU IV	0.12 - 0.14 (26)
734204-1	AMPMODU IV	0.2 -0.56 (24-20)
734870-1	MICRO MATCH COSI contact	0.2 - 0.6 (24-20)
734870-2	MICRO MATCH COSI contact	0.08 - 0.2 (28-24)
539608-1	MODU II	0.02 - 0.20 (32-24)
734216-1	TYPE III+	0.2 - 1.5 (24-16) Ins. Ø1.1-2.5mm

Only the most popular options are listed here, please use our online search by terminal PN to find the right tool for your application, and contact us where information is unclear or missing - there may well be something available for your requirement.

PEZ 100

539717-1 - Base Tool without Die-set 1579000-1 - Base Tool without Die-set Long Handles

Features:

Interchangeable Dies Flap type terminal locator Straight action jaw closure Ratchet mechanism ensures complete crimp cycle Easy access ratchet release Handle pressure adjustment with locking device Egonomic non-slip handles



Part Number	Description	mm ² (AWG) or other
1579002-6	PIDG STRATO-THERM	0.2 - 0.4 (24-22)
1579002-7	PIDG STRATO-THERM	1.0 - 2.5 (18-14)
7-1579001-2	POSITIVE-LOK	0.35 - 0.75 (24-18)
7-1579001-3	POSITIVE-LOK	0.5 - 0.75 (22-20)
7-1579001-4	Die-set for Ring Tongue (similar to DIN 46225)	1.0 - 2.5 (18-14) Ins. Ø2 1-3 1mm

Only the most popular options are listed here, please use our online search by terminal PN to find the right tool for your application, and contact us where information is unclear or missing - there may well be something available for your requirement.

July 2008

ERGOCRIMP

539635-1 Base Tool without Die-set

Note: This tool is not compatible with SDE Dies

Features:

Interchangeable Dies Virtually a straight action jaw closure Ratchet mechanism ensures complete crimp cycle Easy access ratchet release Handle pressure adjustment with locking device Egonomic non-slip handles Approximate weight 0.59 kg (1.3 lbs)

Spare parts Kit 539635-2 (excluding main spring) Main Spring PN 1579005-1

Part Number	Description	mm ² (AWG) or other
9-1579004-6	MCON 2.8 Receptacle	0.2 - 0.35 (24-22) Ins. Ø1.15-1.4mm
9-1579004-8	MCON 2.8 Receptacle	1.5 - 2.5 (16-14) Ins. Ø2.2-3.0mm
9-1579004-9	MCON 2.8 Receptacle	4.0 (12)

onlinecomponents.com

Only the most popular options are listed here, please use our online search by terminal PN to find the right tool for your application, and contact us where information is unclear or missing - there may well be something available for your requirement.

Die-set - ERGOCRIMP


Widely used in the Automotive industry

Features:

Use in: Hand Tool Frame 539635-1

1285003-1 - Head for the 626 Pneumatic System 1579000-7 - Adapter for Bench Top Press SSC- 2FP (1481004-7) for more information please see the Power Assist section Image representative of type only





Part Number	Description	mm ² (AWG) or other
4-1579001-1	AMP MCP 1.2-LL	1.0 - 1.5 (18-16)
4-1579001-2	AMP MCP 1.2-LL	0.5 - 0.75 (22-20)
4-1579001-3	AMP MCP 1.2-LL	0.25 - 0.35 (24-22)
4-1579001-4	AMP MCP 1.2-LL	0.14 - 0.22 (26-24)
4-1579001-5	AMP MCP 1.2-LL (SWS)	1.0 - 1.5 (18-16)
4-1579001-6	AMP MCP 1.2-LL (SWS)	0.75 - 1.0 (20-16)
4-1579001-7	AMP MCP 1.2-LL (SWS)	0.2 - 0.35 (24-22)
4-1579001-8	AMP MCP 1.2-LL (SWS)	0.14 - 0.22 (26-24)
539950-2	AMP MCP 1.5k; AMP MCP 1.5k (SWS)	0.2 - 1.0 (24-18)
539691-2	PIDG, PLASTI-GRIP - All Types	0.4 - 6.0 (22-10)
6-1579001-6	SOLARLOK	1.5 - 6.0 (16-10)
6-1579001-7	SOLARLOK	4.0 - 6.0 (12-10)
539662-2	SOLISTRAND Terminals & Splices	0.3 - 6.6 (24-10)

Only the most popular options are listed here, please use our online search by terminal PN to find the right tool for your application, and contact us where information is unclear or missing - there may well be something available for your requirement.

MP

Revised:

Tetra-Crimp Hand Tool 58078-3 - Base Tool without Die-set

Features:

Interchangeable Dies Ratchet mechanism ensures complete crimp cycle Tamper proof ratchet release setting Emergency ratchet release feature Terminal loactor / support and wire stop on many tools Approximate weight 0.64 kg (1.4 lbs) Egonomic non-slip handles

mineconne

Image representative of type only

Part Number	Description	mm ² (AWG) or other
59824-1	Complete Tool for PIDG, PLASTI-GRIP Terminals & Splices Meets UL requirements	0.4 - 6.0 (22-10)
58052-3	Die-set for ULTRA FAST Use In Hand Tool Frame 58078-3	0.15 - 0.4 (26-22)
90390-3	Die-set for ULTRA FAST (including Flag Terminals) Use In Hand Tool Frame 58078-3	0.4 - 1.0 (22-18)
90391-3	Die-set for ULTRA FAST (including Flag Terminals) Use In Hand Tool Frame 58078-3	1.5 - 2.5 (16-14)
58079-3	Die-set for ULTRA FAST PLUS Use In Hand Tool Frame 58078-3	0.4 - 1.0 (22-18)
58080-3	Die-set for ULTRA FAST PLUS Use In Hand Tool Frame 58078-3	1.5 - 2.5 (16-14)

Image representative of type only

A light weight and compact tool for many commercial applications

Features:

Fixed dies Straight action jaw closure Ratchet mechanism ensures complete crimp cycle Easy access ratchet release Handle pressure adjustment with locking device Easy terminal positioning with 'Flap Locator' (some tools) Egonomic non-slip handles Approximate weight 0.46 kg (1.0 lbs)



Part Number	Description	mm ² (AWG) or other
1579004-2	110 FASTIN-ON	0.5 - 1.5 (22-16)
169341-1	AMPLIMITE HD-20 (Spare Terminal Locator 4-539785-7)	0.03 - 0.56 (32-20) Ins. Ø0.5-1.5mm
734360-1	AMPLIMITE HD-22	0.08 - 0.4 (28-22)
169481-1	AMPMODU IV (Spare Terminal Locator 4-539785-8)	0.03 - 0.56 (32-20) Ins. Ø0.5-1.4mm
734202-1	Mini-Universal MATE-N-LOK	0.4 - 1.0 (22-18)
734218-1	MODULAR PLUG	4 Posn
734218-2	MODULAR PLUG	6 Posn
734218-3	MODULAR PLUG	8 Posn
734218-4	MODULAR PLUG	6 Posn off-set
539645-1	MQS Ø1.0mm	0.35 - 0.5 (24-22)
169994-1	POSITIVE-LOK 4.8 mm	0.2 - 0.6 (24-20)
169481-2	TANDEM-SPRING (Spare Terminal Locator 4-539785-9)	0.03 - 0.56 (32-22)
169480-1	TYPE 'F' Crimp-on Snap-in	0.05 - 1.5 (30-16)
169475-1	TYPE III+	0.03 - 0.56 (32-20)
169422-1	TYPE III+; CI-2 Socket	0.75 - 2.5 (20-14) Ins. Ø2.0-3.8mm
1579004-4	Wire End Ferrules	0.08 - 10.0 (28-8)

Modular Mini CERTI-LOK

Based on the Mini Certi-Lok tool 2-1579005-1 Short handle assembly 2-1579005-2 Long handle assembly

Features:

Heads with identical features to the Mini Certilok tool

Choice of two handle lengths: 2-1579005-1 Short Handle 2-1579005-2 long Handle

Interchangerbility via snap-in pins.



Image representative of type only

Part Number	Description	mm ² (AWG) or other
2-1579021-8	Head only for 4.2mm PE Series	0.15 - 1.0 (26-18)
1579001-8	Head only for FFC to MQS	0.35 - 0.5 (24-22)
5-1579001-8	Complete tool for MQS (SWS)	0.5 - 0.75 (22-20)
1579001-9	Head only for Pin/Socket Ø2.5	1.5 - 2.5 (16-14)
7-1579001-8	Head only for SOLARLOK	1.5 - 2.5 (16-14)
7-1579001-9	Head only for SOLARLOK	4.0 - 6.0 (12-10)
1-1579004-1	Complete tool for SOLARLOK with Long Handle assembly	1.5 - 2.5 (16-14)
1-1579004-2	Complete tool for SOLARLOK with Long Handle assembly	4.0 - 6.0 (12-10)

onlinecomponents.com

Only the most popular options are listed here, please use our online search by terminal PN to find the right tool for your application, and contact us where information is unclear or missing - there may well be something available for your requirement.

C-Frame Hand Tool

6-1419172-9 - Base Tool without Die-set

Features:

Interchangeable Dies Double action jaw closure Ratchet mechanism ensures complete crimp cycle Easy access ratchet release Handle pressure adjustment with locking device Egonomic non-slip handles Approximate weight 0.55 kg (1.2 lbs) Image representative of type only



Part Number	Description	mm ² (AWG) or other
1583684-1	Die-set for ADK Series Back Shell Use in Hand Tool frame 6-1419172-9	6.0 mm Cable Dia Max
1583684-2	Die-set for ADK Series Back Shell Use in Hand Tool frame 6-1419172-9	7.5 mm Cable Dia Max
1583684-3	Die-set for ADK Series Back Shell Use in Hand Tool frame 6-1419172-9	8.5 mm Cable Dia Max
1583684-4	Die-set for ADK Series Back Shell Use in Hand Tool frame 6-1419172-9	9.5 mm Cable Dia Max
948761-2	Complete tool for HDE 20 Ferrule	9-15-25 WAY 8.2MM I/D
948761-1	Complete tool for HDE20 Ferrule	9-15-25 WAY 6.25MM I/D
948761-3	Complete tool for HDE20 Ferrule	9-15-25 WAY 9.5MM I/D

734566-1 Complete tool for N Series 50 & 70 ohm

Image representative of type only

D-Frame Tool

Features:

Fixed Die-sets Small and lightweight Ratchet mechanism ensures complete crimp cycle Easy access ratchet release Handle pressure adjustment with locking device Egonomic non-slip handles Approximate weight 0.55 kg (1.2 lbs)

Revised:

Part Number	Description	mm ² (AWG) or other
947488-1	Coax - BNC, TNC	Cable Dia 5 & 6mm
947679-1	HE 13 / 14 Crimp-on Snap-in	0.08 - 0.2 (28-24)
2-1579002-0	Wire Wire End Ferrrules (Square crimp form)	0.5 - 6.0 (22-10)
Only the mean	the second s	to final the statet to all feature equilibrities and equite at the

Only the most popular options are listed here, please use our online search by terminal PN to find the right tool for your application, and contact us where information is unclear or missing - there may well be something available for your requirement.

Trapezium Crimp Tool

Special Trapezium crimp tool for Wire End Ferrule applications

Features:

Ratchet mechanism ensures complete crimp cycle Easy access ratchet release Handle pressure adjustment with locking device Egonomic non-slip handles Image representative of type only



Part Number	Description	mm ² (AWG) or other
734641-2	Wire End Ferrules (trapezium crimp form)	0.14 - 6.0 (26-10)
734641-3	Wire End Ferrules (trapezium crimp form)	0.5 - 10 (22-6)
734641-4	Wire End Ferrules (trapezium crimp form)	10.0 - 16.0 (8-6)

Square Crimp Tool

onlinecomponents.com

Special Square crimp tool for Wire End Ferrule applications

Features:

Ratchet mechanism ensures complete crimp cycle Easy access ratchet release Handle pressure adjustment with locking device Egonomic non-slip handles



-

Revised:

Part Number	Description	mm ² (AWG) or other
539660-1	Wire Wire End Ferrrules (square crimp form)	0.08 - 6.0 (28-10)
539661-1	Wire Wire End Ferrrules (square crimp form)	0.75 - 10 (20-8)

Only the most popular options are listed here, please use our online search by terminal PN to find the right tool for your application, and contact us where information is unclear or missing - there may well be something available for your requirement.

Service Tool

734790-1 - Base Tool without Die-set

Features:

Interchangeable Dies Ratchet mechanism ensures complete crimp cycle Easy access ratchet release Handle pressure adjustment with locking device Egonomic non-slip handles Approximate weight 0.59 kg (1.3 lbs) Image representative of type only

Part Number	Description	mm ² (AWG) or other
1-1579004-5	Complete tool for FASTON; FASTIN-FASTON	0.1 - 6.0 (18-10)
2-1579021-3	Complete tool for FASTON; FASTIN-FASTON Use in Hand Tool 734790-1	0.5 - 6.0 (22-10)
734767-1	Micro TIMER I; Junior Power-TIMER 2.8 (SWS); CI-2 Use in Hand Tool 734790-1	0.5 - 2.5 (22-14)
1-1579004-4	Complete tool for PIDG, PLASTI-GRIP - All Types	0.5 - 6.0 (22-10)
2-1579021-2	Die-set for PIDG, PLASTI-GRIP - RBY all types Use in Hand Tool 734790-1	0.5 - 6.0 (22-10)
734768-1	Pin / Socket Ø1.5 (SWS) Use in Hand Tool 734790-1	0.5 - 2.5 (22-14)
1-1579004-6	Complete tool for SOLISTRAND Terminals & Splices	0.08 - 10.0 (28-8)
2-1579021-4	Die-set for SOLISTRAND Terminals & Splices Use in Hand Tool 734790-1	0.5 - 6.0 (22-10)
734658-1	Complete Tool for Wire End Ferrules	25.0 - 35.0 (4-2)
734658-2	Complete Tool for Wire End Ferrules	50 (1/0)
790081-2	Complete Tool for Wire End Ferrrules	6.0 - 16.0 (10-6)
1-1579004-7	Complete Tool for Wire End Ferrules DIN 46228	0.14 - 6.0 (26-10)
2-1579021-5	Die-set for Wire End Ferrules DIN 46228	0.14 - 6.0 (26-10)

1579021-5 Die-set for Wire End Ferrules DIN 46228 Use in Hand Tool 734790-1

Only the most popular options are listed here, please use our online search by terminal PN to find the right tool for your application, and contact us where information is unclear or missing - there may well be something available for your requirement.

July

July 2008

TERMI-POINT Hand Tool

Features:

Pneumatic options (pictured) Interchangeable Mandrels Terminals fed from Reel

I	mage representative of type only

Revised:



Part Number	Description	mm ² (AWG) or other
655032-1	Maxi TERMI-POINT	0.2 - 0.56 (24-20)
655136-3	STD TERMI-POINT	0.2 - 0.4 (24-22)
1-69411-3	Mandrel (red) for 69526-1 - Ins. Range Ø1.10 - 1.65 mm	0.2 (24)
1-69411-4	Mandrel (orange) for 69526-1 - Ins. Range Ø1.14 - 1.65 mm	0.4 (22)
1-69411-9	Mandrel (brown) for 69526-1 - Ins. Range Ø1.14 - 1.65 mm	0.15 (26)
69526-2	Hand Tool without Mandrel	0.08 - 0.4 (28-22)
69551-5	Mandrel (black) for 69526-1 - Ins. Range Ø1.14 - 1.65 mm	0.08 (28)
69551-6	Mandrel (brown) for 69526-1 - Ins. Range Ø0.56 - 1.14 mm	0.15 (26)
69551-8	Mandrel (orange) for 69526-1 - Ins. Range Ø0.87 - 1.23 mm	0.4 (22)
69551-9	Mandrel (red) for 69526-1 - Ins. Range Ø0.74 - 1.23 mm	0.2 (24)
69561	Mandrel (yellow) for 654182-1 - Ins. Range Ø1.17 - 1.65 mm	0.56 (22)
69561-1	Mandrel (yellow) for 654182-1 - Ins. Range Ø1.68 - 2.16 mm	0.56 (22)
69561-4	Mandrel (red) for 654182-1 - Ins. Range Ø1.17 - 1.65 mm	0.2 (24)
654182-1	Hand Tool without Mandrel	0.6 - 0.2 (20-24)
871087-1	Hand Tool (pneumatic) without Mandrel	0.6 - 0.2 (20-24)
871087-2	Hand Tool (pneumatic) without Mandrel	0.4 - 0.15 (22-26)
871295-1	Mandrel (yellow) for 871087-1 - Ins. Range Ø0.91 - 1.65 mm	0.56 (22)
871295-2	Mandrel (red) for 871087-1 - Ins. Range Ø0.86 - 1.65 mm	0.2 (24)
871295-3	Mandrel (orange) for 871087-2 - Ins. Range Ø0.91 - 1.65 mm	0.4 (22)
871295-4	Mandrel (red) for 871087-2 - Ins. Range Ø0.86 - 1.65 mm	0.2 (24)
871295-5	Mandrel (brown) for 871087-2 - Ins. Range Ø0.76 - 1.40 mm	0.15 (26)

Only the most popular options are listed here, please use our online search by terminal PN to find the right tool for your application, and contact us where information is unclear or missing - there may well be something available for your requirement.

6