



NOTES
 1. 適合ハウジング: 502380-****
 APPLICABLE HOUSING: 502380-****
 図示の斜線部の範囲は、接点部のため、傷、打痕、汚れなどを付けないようにして下さい。
 PLEASE DON'T DAMAGE, DON'T DENT, AND DON'T MAKE IT DIRTY, BECAUSE THE RANGE IN THE SHADED PORTION SHOWN IN FIGURE IS THE CONTACT AREA.

φ0.8-1.0mm	AWG#26-28	502381-0000	連続状 CHAIN
絶縁被覆外径範囲 INS. RANGE	適用電線範囲 WIRE RANGE	製品番号 MATERIAL NO.	端子形状 FORM
SCALE 20:1		DESIGN UNITS METRIC	THIRD ANGLE PROJECTION

1.25 W/B CONN. SINGLE PLUG TERMINAL -LEAD FREE-

MOLEX	MOLEX INCORPORATED	DOCUMENT NO. SD-502381-001	SHEET NO. 1 OF 1
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			

REVISED EC NO. J2008-0004 2007/10/29 DRAWN:ISHI CHK:K.ASAKAWA 2007/10/29 APPR:Y.IITO 2007/10/29	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY	
	10 UNDER	±0.2	DRAWN BY T.MIYAZAKI	DATE 2006/08/28
	10 OVER 30 UNDER	±0.25	CHECKED BY K.ASAKAWA	DATE 2006/08/28
	30 OVER	±0.3	APPROVED BY YO.IITO	DATE 2006/08/28
ANGULAR ±3 °		MATERIAL NO. SEE TABLE		SIZE A3
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				

部品 PART	材質 MATERIAL
ターミナル TERMINAL	銅合金 COPPER ALLOY
	溶めつき: 0.4 micro-meter MIN. リフロー処理(前めつき) REFLOW TREATMENT (PRE-PLATED)
	TIN
	ニッケルめつき(下地): 0.1 micro-meter MIN. リフロー処理(前めつき) NICKEL (UNDER PLATING) REFLOW TREATMENT (PRE-PLATED)

tb_frame_A3_1_ME_S
Rev. E 2006/04/15

EN-02JA(021)