



## T&B® Fittings

**T&B Catalog Number:** 5233  
**UPC Number:** 78621005233  
**Description:** 3/4" Straight steel liquidtight connector

**Status:** Active

### WEB\_USE

-T&B Product Line 012

### Features

- Ability to install quickly with low torque effort

### Application

- Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.

- To positively bond conduit to box or enclosure.

### General

-Material Steel

-Finish Electro Zinc Plated with Chromate Coating

### Dimension Information

-Dimension A (inches) 1 21/32

-Dimension B (inches) 1 5/8

-Dimension C (inches) 9/16

-Conduit Size (inches) 39876

### Specifications

-3dmodel Available on Website

### Accessories & Components

-Wiremesh Grips for Liquidtight Fittings WMG-LT3

### Packaging

-T&B Inner Pack 25

-Package in Units 50

-T&B Sold in UOM Each

-T&B Weight Per UOM 24.4 lbs. per 100

### Application Support

-Product Overview Available on Website

### Certifications

-RoHS Compliance Yes

### Certifications



File Nbr:

E 23018

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
 www.tnb.com

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email:techsupport@tnb.com