



NOTE:

- MATERIAL:  
HOUSING: HIGH TEMP PLASTIC, UL94-V0, BLACK  
TERMINAL: COPPER ALLOY, SQ=0.40±0.03MM
- FINISH:  
TERMINAL: GOLD AT CONTACT,  
G/F OVER 1um(40u") MIN Ni OVER ALL
- SPEC.:  
PRODUCT SPEC: GS-12-629  
PACKING SPEC: GS-14-1420
- THE HSG. WILL WITHSTAND EXPOSURE TO 260C PEAK TEMP. FOR 10 SEC. IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN.
- PRODUCT NUMBERING:  
20021121 - X 0 0 XX X X LF

LEAD FREE

PLATING:  
1: GOLD FLASH ALL OVER  
4: 0.25um(10u") GOLD AT CONTACT  
8: 0.76um(30u") GOLD AT CONTACT

PACKING  
D: TUBE+ CAP  
T: TUBE  
C: REEL+CAP(6,8,10,12,16,20P)

PIN COUNT  
04,06,08, 12, 14,.... 98,A0  
( 4 - 100 EVERY EVEN PIN )

POST OPTION  
0: W/O POST  
1: WITH POST

All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of FCI. Copyright FCI.



mat'l. code		tolerances unless otherwise specified		CUSTOMER COPY		FCI	
ltr	ecn no	dr	date	linear	.X ± 0.38	projection	www.fciconnect.com
A	T09-1117	S.LIN	09/15/09		.XX ± 0.25		title 1.27X1.27MM BTB,HEADER UNSTROUDED, SMT
B	T10-0013	S.LIN	01/22/10		.XXX ± 0.10		
C	T11-0022	S.LIN	11-04-26	angles	0° ± 2°		
				dr	STERLING LIN 09/15/09		product family 585 size  dwg no 20021121
				engr	STERLING LIN 09/15/09		
				chr	GARY HSIEH 09/15/09		
				appd	JOSEPH HSIA 09/15/09		
sheet index	revision sheet	C	1			scale	A4

ACAD PDM: Rev:C 3 STATUS Released cage code Printed: Apr 27, 2011 4