


5.00mm (.197") Pitch SPOX™ Header 5287-NA Vertical



Circuits	Order No.	Lead-free
2	10-63-3023	Yes
3	10-63-3033	
4	10-63-3043	
5	10-63-3053	
6	10-63-3063	

Features and Benefits

- Sizes 2 to 6 circuits
- Polarization through varied center spacing between circuits 1 and 2

Reference Information

Packaging: Bag
 UL File No.: E29179
 CSA File No.: LR19980
 Mates With: 5199-N housings
 Designed In: Millimeters


Electrical

Voltage: 250V
 Current: 7.0A
 Contact Resistance: 10 milliohms max.
 Dielectric Withstanding Voltage: 1500V AC/1 min.
 Insulation Resistance: 1000 Megohms min.

Physical

Housing: 6/6 nylon, UL 94V-2
 Contact: Brass, 1.14mm (.045") square
 Plating: Tin
 Operating Temperature: -40 to +105°C

5.00mm (.197") Pitch SPOX™ Header 5289-NA Vertical Friction Lock



Circuits	Order No.	Lead-free
2	10-31-2028	Yes
3	10-31-2038	
4	10-31-2048	
5	10-31-2058	
6	10-31-2068	

Features and Benefits

- Sizes 2 to 6 circuits
- Locking ramp
- Polarization through varied center spacing between circuits 1 and 2
- Plating options available (contact Molex)

Reference Information

Packaging: Bag
 UL File No.: E29179
 CSA File No.: LR19980
 Mates With: 5199-N housings
 Designed In: Millimeters

Electrical

Voltage: 250V
 Current: 7.0A
 Contact Resistance: 10 milliohms max.
 Dielectric Withstanding Voltage: 1500V AC/1 min.
 Insulation Resistance: 1000 Megohms min.

Physical

Housing: 6/6 nylon, UL 94V-2
 Contact: Brass, 1.14mm (.045") square
 Plating: Tin
 Operating Temperature: -40 to +105°C

D

3.00 to 7.92mm (.118 to .312") Pitch PCB and Wire Connectors