

**(2,54mm) .100"**  
**SSW, SSQ SERIES**

# THROUGH-HOLE .025" SQ POST SOCKET

## SPECIFICATIONS

For complete specifications see [www.samtec.com?SSW](http://www.samtec.com?SSW) or [www.samtec.com?SSQ](http://www.samtec.com?SSQ)


**Insulator Material:**  
 Black Liquid Crystal Polymer (-S & -D) or Black High Temperature Thermoplastic (-T)  
**Contact Material:**  
 Phosphor Bronze  
**Plating:**  
 Au or Sn over 50µ" (1.27µm) Ni  
**Operating Temp Range:**  
 -55°C to +125°C with Gold  
 -55°C to +105°C with Tin  
**Contact Resistance:**  
 10 mΩ max  
**Insertion Depth:**  
 (3,68mm) .145" to (6,35mm) .250"  
**Insertion Force:**  
 (Single contact only) (-S plating)  
 Standard= 6oz (1,67N) avg (0,64mm) .025" SQ pin);  
 SSW Low Insertion Force= 3oz (0,83N) avg  
 SSQ Low Insertion Force= 3.3oz (0,92N) avg  
**Normal Force:**  
 Standard= 125grams (4.4N)  
**Withdrawal Force:**  
 (Single contact only) (-S plating)  
 Standard= 5oz (1,39N) avg (0,64mm) .025" SQ pin);  
 SSW Low Insertion Force= 2.6oz (0,72N) avg  
 SSQ Low Insertion Force= 2.9oz (0,81N) avg  
**Max Cycles:**  
 100 with 10µ" (0,25µm) Au  
**Voltage Rating:**  
 550 VAC mated with TSW  
**RoHS Compliant:**  
 Yes  
**Lead-Free Solderable:**  
 Yes



**Mates With:**  
 TSW, MTSW, MTLW,  
 LCW, EW, ZW, TSS,  
 ZSS, TSM, TSSH, HTSS



<b>TYPE STRIP</b>	<b>PIN CENTERS</b>	<b>NO. PINS PER ROW</b>
<b>SSW = Solder Tail</b>	<b>-1 = (2,54mm) .100" Centers</b>	
<b>SSQ = Square Tail</b>		




CURRENT RATING		
AMBIENT TEMP	TSW mated with SSQ	TSW mated with SSW
20°C	7.6A	6.9A
40°C	6.9A	6.1A
60°C	5.9A	5.3A
95°C	3.9A	3.5A
6 POSITIONS (2x3) POWERED		

**Note:**  
 Some lengths, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)



### LEAD STYLE

### PLATING OPTION

### ROW OPTION

### TAIL OPTION

### OTHER OPTION

**-F**

= Gold flash on contact, Matte Tin on tail

**-L**

= 10µ" (0,25µm) Gold on contact, Matte Tin on tail

**-G**

= 20µ" (0,51µm) Gold on contact, Gold flash on tail

**-T**

= Matte Tin (-T N/A on LIF contacts)

**Note:** Other Gold plating options available. Contact Samtec.

**-S**

= Single Row

**-P**

= Single Row (Notched to mate with LCW) 36 pins max

**-D**

= Double Row

**-T**

= Triple Row

**-Q**

= Double Row .200" (5,08mm) row space (Outer rows filled only)

**-RA**

= Right Angle (Leave blank for straight pin version)

**-N**

= Notch (5, 7, 8, 10, 12, 13, 15, 17, 20, 25, 32 & 36 positions only) (-D & SSW only) (Mates to TSS, ZSS and HTSS only)

**-LL**

= Locking Lead

Two leads per strip crimped in opposite directions on or near centerline. Available on tails from (2,29mm) .090" to (7,87mm) .310" only. N/A with single row 1 or 2 positions.

**- "XXX"**


= Polarized (Specify "XXX" as position number)

## Straight Pin Versions (Specify "LEAD STYLE" from chart)

LEAD STYLE		SINGLE DOUBLE OR TRIPLE A
Standard Insertion Force	Low Insertion Force*	
-01	-21	(2,64) .104
-02	-22	(4,93) .194
-03	-23	(10,00) .394
-04	-24	(14,83) .584
-06**	N/A	(3,15) .124

\* LIF N/A with Tin Plating


\*\*Style -06 N/A with SSW



## Right Angle Versions (Specify "LEAD STYLE" from chart)

LEAD STYLE		SINGLE	DOUBLE	TRIPLE
Standard Insertion Force	Low Insertion Force*	(-S & -P) A	(-D) A	(-T & -Q) A
-02	-22	(2,54) .100	(2,54) .100	(2,54) .100
-03	-23	(7,62) .300	(7,62) .300	N/A
-04	-24	(12,45) .490	N/A	N/A

\*LIF N/A with Tin Plating



Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 SAMTEC SILICON VALLEY • Tel: 408-395-5900 SAMTEC SOUTHERN CALIFORNIA • Tel: 1-800-726-8329  
 SAMTEC AMERICA LATINA COMERCIO EXTERIOR LTDA • Tel: (+55 31) 3786 3227 SAMTEC UNITED KINGDOM • Tel: 44 01236 739292 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0  
 SAMTEC FRANCE • Tel: 33 01 60 95 06 60 SAMTEC ITALY • Tel: 39 039 6890337 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 SAMTEC BENELUX • Tel: 44 01236 739292  
 SAMTEC ISRAEL • Tel: 972-3-7526600 SAMTEC INDIA • Tel: +91-80-3272 1612 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 SAMTEC JAPAN • Tel: 045-475-1385 SAMTEC CHINA • Tel: 86-21-6083 3766  
 SAMTEC TAIWAN • Tel: 886-2-2709-6109 SAMTEC HONG KONG • Tel: 852-26904858 SAMTEC KOREA • Tel: 82-31-717-5685 SAMTEC ANZ • Tel: 613 9580 0683