

Clip, 6.3x32 mm, 32 A, BeCu

onlinecomponents.com  
THE ONLINE DISTRIBUTOR OF ELECTRONIC COMPONENTS

600 VAC/DC · 32 A (UL)

**Description**

- BeCu Clip up to 32 A Application

**Standards**- UL 4248-1 / UL E 39328  
- CSA 22.2 no. 4248-1**Applications**- Industrial electronic  
- Photovoltaic**References****Weblinks**



pdf, html, General Product Information, Approvals, RoHS, CHINA-RoHS, e-Store, SCHURTER-Stock-Check, Distributor-Stock-Check

**Technical Data**

Fuse-Link	6.3 x 32 mm	Soldering Methods	Wave
Mounting	PCB	Solderability	235 °C / 2 sec acc. to IEC 60068-2-20, Test Ta, method 1
Terminal	Solder THT	Resistance to Soldering Heat	260 °C / 10 sec acc. to IEC 60068-2-20, Test Tb, method 1A
Rated Voltage	600 VAC/DC		
Rated Current	32 A (UL)		
Admissible Ambient Air Temp.	-55 °C to 125 °C		
Material: Terminals	BeCu		
Storage Conditions	0 °C to 60 °C, max. 70% r.h.		

**Abmessungen**

8.2 mm



Drilling diagram

**Variants**

Clip	Material: Terminals	Order Number
●	Tin-plated Beryllium-Copper	8040.0001
●	Silver-plated Beryllium-Copper	8040.0003

**Packaging Unit**

Bulk (1000 pcs.)