



ALUMINUM ELECTROLYTIC CAPACITORS

UX series Chip Type, Higher Capacitance Range



- Chip type, higher capacitance in larger case sizes.
- Designed for surface mounting on high density PC board.
- Applicable to automatic mounting machine fed with carrier tape.
- Compliant to the RoHS directive (2002/95/EC).




Specifications


Item	Performance Characteristics																			
Category Temperature Range	-55 to +105°C (6.3 to 100V), -40 to +105°C (160 to 400V)																			
Rated Voltage Range	6.3 to 400V																			
Rated Capacitance Range	1 to 1000μF																			
Capacitance Tolerance	±20% at 120Hz, 20°C																			
Leakage Current	Rated voltage (V)						6.3 to 100				160 to 400									
	Leakage Current						After 1 minute's application of rated voltage, leakage current is not more than 0.03CV (μA), I = 0.04CV+100 (μA) max.(1 minute's)													
Tangent of loss angle (tan δ)	Measurement frequency : 120Hz, Temperature : 20°C																			
	Rated voltage (V)	6.3	10	16	25	35	50	63	100	160	200	250	400							
	tan δ (MAX.)	0.22	0.19	0.16	0.14	0.12	0.10	0.10	0.08	0.20	0.20	0.20	0.25							
Stability at Low Temperature	Measurement frequency: 120Hz																			
	Rated voltage (V)		6.3	10	16	25	35	50	63	100	160	200	250	400						
	Impedance ratio Z-55°C / Z+20°C	4	4	3	3	3	2	3	4	—	—	—	—							
	ZT / Z20 (MAX.)	Z-40°C / Z+20°C	—	—	—	—	—	—	—	6	6	6	10							
Endurance	The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 2000 hours (160 to 400V : 3000hours) at 105°C.						Capacitance change							Within ±20% of the initial capacitance value						
							tan δ							200% or less than the initial specified value						
Shelf Life	After storing the capacitors under no load at 105°C for 1000 hours and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they shall meet the specified values for the endurance characteristics listed above.						Leakage current							Less than or equal to the initial specified value						
Resistance to soldering heat	The capacitors are kept on a hot plate for 30 seconds, which is maintained at 250°C. The capacitors shall meet the characteristic requirements listed at right when they are removed from the plate and restored to 20°C.						Capacitance change							Within ±10% of the initial capacitance value						
							tan δ							Less than or equal to the initial specified value						
Marking							Leakage current							Less than or equal to the initial specified value						
	Black print on the case top.																			

Chip Type


(φ6.3, φ8 × 6.2)



(φ8 × 10, φ10 × 10)



Type numbering system (Example : 10V 100μF)



φD × L	(mm)			
A	6.3 × 7.7	8 × 6.2	8 × 10	10 × 10
B	2.4	3.3	2.9	3.2
C	6.6	8.3	8.3	10.3
E	2.2	2.3	3.1	4.5
L	7.7	6.2	10	10
H	0.5 to 0.8	0.5 to 0.8	0.8 to 1.1	0.8 to 1.1

● Dimension table in next page.

■ Dimensions

Cap. (μF)	Code	V		6.3		10		16		25		35		50		63		100		
		0J	1A	1C	1E	1V	1H	1J	2A											
4.7	4R7																		8×6.2	42
10	100																8×6.2	51	8×10	75
22	220													○ 8×6.2	67(64)	8×10	108	■ 10×10	150(121)	
33	330											○ 8×6.2	76(75)	8×10	133	■ 10×10	185(179)	10×10	180	
47	470									○ 8×6.2	79(78)	8×10	124	■ 10×10	180(167)	10×10	220	10×10	230	
100	101			8×6.2	90	○ 8×10	148(111)	8×10	181	■ 10×10	304(283)	10×10	310	10×10	320					
220	221	○ 8×10	161(121)	8×10	173	■ 10×10	330(307)	■ 10×10	351(283)	10×10	450									
330	331	8×10	288	■ 10×10	318(296)	■ 10×10	441(410)	10×10	372											
470	471	■ 10×10	340(316)	■ 10×10	351(326)	10×10	489													
680	681	10×10	408	10×10	392															
1000	102	10×10	495																Case size φD × L (mm)	Rated ripple

Cap. (μF)	Code	V		160		200		250		400	
		2C	2D	2E	2G						
1	010									8×10	25
1.8	1R8									8×10	26
2.2	2R2									8×10	27
3.3	3R3			8×10	31	8×10	31	10×10	38		
3.9	3R9			8×10	34	8×10	34	10×10	39		
4.7	4R7			8×10	37	8×10	37	10×10	40		
6.8	6R8			8×10	44	8×10	44				
10	100	8×10	57	10×10	64	10×10	64				
18	180	10×10	64								

Rated ripple current (mA rms) at 105°C 120Hz

Size φ6.3 × 7.7 is available for capacitors marked. "○" / Size φ8 × 10 is available for capacitors marked. "■"

※ In this case, □ will be put at 12th digit of type numbering system.

● Frequency coefficient of rated ripple current

Cap. (μF)	Frequency	50 Hz	120 Hz	300 Hz	1 kHz	10 kHz or more
1 to 47		0.80	1.00	1.15	1.40	1.67
100 to 1000		0.85	1.00	1.08	1.20	1.30

- Taping specifications are given in page 23.
- Recommended land size, soldering by reflow are given in page 18, 19.
- Please select UJ(p.112) series if high C/V products are required.
- Please refer to page 3 for the minimum order quantity.