

- Home
- Quick Links
- Cross reference
- RoHS/LF P/N Search
- Industry Standards
- Alphabetical List
- Documentation
- 3D model search
- Customer drawing search
- Free search
- Search by category
- Services
- E-Services
- Distributor list

Start > Search=10061399-101LF\* > 10061399-101LF

**10061399-101LF**

**10061399-101LF - AIRMAX® : 4-Pair, 96 -position, 2 mm pitch, 8 column, Right Angle Header I/O**



ACTIVE

RoHS Compliant

[Distributor Stock](#)

[Print Datasheet](#)

- FCI Brings You More**
- [Contact our sales/technical support](#)
  - [Sample request](#)
  - [Price request](#)

- [Customer drawing](#)
- [Environmental Compliance Report](#)

[Specifications](#) | [Download document](#)

Dimensional	General	Physical
<b>Dimensional</b>		
Pitch (Slot - min)		20 mm
Spacing (Column)		2 mm
<b>General</b>		
Number of contacts		96
Orientation		Right Angle
Product Series		AirMax VS
Style		Signal Receptacle 2 mm
Termination Style		Press-Fit
Number of columns		8
Number of differential pairs (per column)		4
<b>Physical</b>		
Material (Contact)		Copper Alloy
Material (Housing)		Hi-Temp Thermo Plastic
Plating (Contact)		Au over Ni