

This document was generated on 04/30/2012

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 50-84-2020
Status: Active

Overview: MLX™ Power Connectors

Description: 2.13mm Diameter MLX™ Pin and Socket Receptacle, 2 Circuits

Documents:

3D Model Product Specification PS-42022-0001 (PDF)
Drawing (PDF) RoHS Certificate of Compliance (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family Crimp Housings

Series <u>42022</u>

Application Power, Wire-to-Wire

Comments Glow Wire Equivalent Part Number <u>366440002</u>. Current

Nο

- Maximum per contact 20A if used with 36663 and

36664 terminal

MolexKits Yes

Overview MLXTM Power Connectors

Product Name MLXTM

Physical

Circuits (maximum) 2 Circuits Detail Color - Resin Natural Flammability 94V-2 Gender Female Glow-Wire Compliant No Keying to Mating Part None Lock to Mating Part Yes Material - Resin Nylon Number of Rows Packaging Type Carton Panel Mount Yes Pitch - Mating Interface 6.35mm Polarized to Mating Part Yes

Temperature Range - Operating -55°C to +105°C

Electrical

Stackable

Current - Maximum per Contact 20A

Material Info

Old Part Number 42022-2A

Reference - Drawing Numbers

Product Specification PS-42022-0001

Sales Drawing SD-36644-001, SD-42022-**

Series image - Reference only

EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Contains SVHC: No
Low-Halogen Status
Low-Halogen



Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

42022 Series

Mates With

42021 MLX™ Power Crimp Housing Plug

Use With

MLX Crimp Terminal <u>42023</u>, <u>42024</u>

This document was generated on 04/30/2012

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION