


### FEATURES

- $I_{T(RMS)} = 8A$
- $V_{DRM} = 200V$  to  $800V$
- High surge current capability

### DESCRIPTION

The S08xxxH series of SCRs uses a high performance MESA GLASS PNP technology. These parts are intended for general purpose applications.




### ABSOLUTE RATINGS (limiting values)

Symbol	Parameter		Value	Unit
$I_{T(RMS)}$	RMS on-state current (180° conduction angle)	$T_c = 95^\circ C$	8	A
$I_{T(AV)}$	Average on-state current (180° conduction angle)	$T_c = 95^\circ C$	5.1	A
$I_{TSM}$	Non repetitive surge peak on-state current ( $T_j$ initial = $25^\circ C$ )	$t_p = 8.3$ ms	88	A
		$t_p = 10$ ms	80	
$I^2t$	$I^2t$ Value for fusing	$t_p = 10$ ms	32	$A^2s$
$di/dt$	Critical rate of rise of on-state current $I_G = 100$ mA $di_G/dt = 1$ A/ $\mu s$ .		100	A/ $\mu s$
$T_{stg}$ $T_j$	Storage and operating junction temperature range		- 40, + 150 - 40, + 125	$^\circ C$
TI	Maximum lead temperature for soldering during 10s at 4.5mm from case		260	$^\circ C$


Symbol	Parameter	Voltage				Unit
		B	D	M	N	
$V_{DRM}$ $V_{RRM}$	Repetitive peak off-state voltage $T_j = 125^\circ C$	200	400	600	800	V




**Fig.1 :** Maximum average power dissipation versus average on-state current.




**Fig.2 :** Correlation between maximum average power dissipation and maximum allowable temperature (Tamb and Tcase) for different thermal resistances heatsink + contact.




**Fig.3 :** Average on-state current versus case temperature.




**Fig.4 :** Relative variation of thermal impedance versus pulse duration.



**Fig.5 :** Relative variation of gate trigger current and holding current versus junction temperature.




**Fig.6 :** Non repetitive surge peak on-state current versus number of cycles.




## S08xxxH

**Fig.7 :** Non repetitive surge peak on-state current for a sinusoidal pulse with width :  $t_p \leq 10\text{ms}$ , and corresponding value of  $I^2t$ .



**Fig.8 :** On-state characteristics (maximum values).



**PACKAGE MECHANICAL DATA**  
TO220 Non-insulated (Plastic)

REF.	DIMENSIONS					
	Millimeters			Inches		
	Typ.	Min.	Max.	Typ.	Min.	Max.
A			10.3			0.406
B		6.3	6.5	0.248	0.256	
C			9.1			0.358
D		12.7			0.500	
F			4.2			0.165
G			3.0			0.118
H		4.5	4.7		0.177	0.185
I		3.53	3.66		0.139	0.144
J		1.2	1.3		0.047	0.051
L			0.9			0.035
M	2.7			0.106		
N			5.3			0.209
N1	2.54			0.100		
O		1.2	1.4		0.047	0.055
P			1.15			0.045

Marking : type number  
Weight : 1.8 g

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1995 SGS-THOMSON Microelectronics - All rights reserved.

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands  
Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A.