



Monolithic N-Channel JFET Duals

SST404
SST406

U401
U404

U406

PRODUCT SUMMARY					
Part Number	$V_{GS(off)}$ (V)	$V_{(BR)GSS}$ Min (V)	g_{fs} Min (mS)	I_G Typ (pA)	$ V_{GS1} - V_{GS2} $ Max (mV)
U401	-0.5 to -2.5	-40	1	-2	5
SST/U404	-0.5 to -2.5	-40	1	-2	15
SST/U406	-0.5 to -2.5	-40	1	-2	40

FEATURES

- Monolithic Design
- High Slew Rate
- Low Offset/Drift Voltage
- Low Gate Leakage: 2 pA
- Low Noise
- High CMRR: 102 dB

BENEFITS

- Tight Differential Match vs. Current
- Improved Op Amp Speed, Settling Time Accuracy
- Minimum Input Error/Trimming Requirement
- Insignificant Signal Loss/Error Voltage
- High System Sensitivity
- Minimum Error with Large Input Signal

APPLICATIONS

- Wideband Differential Amps
- High-Speed, Temp-Compensated, Single-Ended Input Amps
- High-Speed Comparators
- Impedance Converters



DESCRIPTION

The SST/U401 series of high-performance monolithic dual JFETs features extremely low noise, tight offset voltage and low drift over temperature specifications, and is targeted for use in a wide range of precision instrumentation applications. This series has a wide selection of offset and drift specifications with the U401 featuring a 5-mV offset and 10- μ V/ $^{\circ}$ C drift.

The U series, hermetically sealed TO-71 package is available

with full military processing (see Military Information). The SST series SO-8 package provides ease of manufacturing, and the symmetrical pinout prevents improper orientation. The SO-8 package is available with tape-and-reel options for compatibility with automatic assembly methods (see Packaging Information).

For similar high-gain products in TO-78 packaging, see the 2N5911/5912 data sheet.



ABSOLUTE MAXIMUM RATINGS

Gate-Drain, Gate-Source Voltage	-40 V
Gate Current	10 mA
Lead Temperature ($1/16$ " from case for 10 sec.)	300 $^{\circ}$ C
Storage Temperature :	U Prefix -65 to 200 $^{\circ}$ C
	SST Prefix -55 to 150 $^{\circ}$ C

Operating Junction Temperature	-55 to 150 $^{\circ}$ C
Power Dissipation :	Per Side ^a 300 mW
	Total ^b 500 mW

- Notes
- Derate 2.4 mW/ $^{\circ}$ C above 25 $^{\circ}$ C
 - Derate 4 mW/ $^{\circ}$ C above 25 $^{\circ}$ C

For applications information see AN106.



SPECIFICATIONS (T _A = 25°C UNLESS OTHERWISE NOTED)										
Parameter	Symbol	Test Conditions	Typ ^a	Limits						Unit
				U401		SST/U404		SST/U406		
				Min	Max	Min	Max	Min	Max	
Static										
Gate-Source Breakdown Voltage	V _{(BR)GSS}	I _G = -1 μA, V _{DS} = 0 V	-58	-40		-40		-40		V
	V _{(BR)G1 - G2}	I _G = ±1 μA, V _{DS} = 0 V, V _{GS} = 0 V	±45	±30		±30		±30		
Gate-Source Cutoff Voltage	V _{GS(off)}	V _{DS} = 15 V, I _D = 1 nA	-1.5	-0.5	-2.5	-0.5	-2.5	-0.5	-2.5	
Saturation Drain Current ^b	I _{DSS}	V _{DS} = 10 V, V _{GS} = 0 V	3.5	0.5	10	0.5	10	0.5	10	mA
Gate Reverse Current	I _{GSS}	V _{GS} = -30 V, V _{DS} = 0 V	-2		-25		-25		-25	pA
		T _A = 125°C	-1							nA
Gate Operating Current	I _G	V _{DG} = 15 V, I _D = 200 μA	-2		-15		-15		-15	pA
		T _A = 125°C	-0.8		-10		-10		-10	nA
Drain-Source On-Resistance	r _{DS(on)}	V _{GS} = 0 V, I _D = 0.1 mA	250							Ω
Gate-Source Voltage	V _{GS}	V _{DG} = 15 V, I _D = 200 μA	-1		-2.3		-2.3		-2.3	V
Gate-Source Forward Voltage	V _{GS(F)}	I _G = 1 mA, V _{DS} = 0 V	0.7							
Dynamic										
Common-Source Forward Transconductance	g _{fs}	V _{DS} = 15 V, I _D = 200 μA f = 1 kHz	1.5	1	2	1	2	1	2	mS
Common-Source Output Conductance	g _{os}		1.3		2		2		2	μS
Common-Source Forward Transconductance	g _{fs}	V _{DS} = 10 V, V _{GS} = 0 V f = 1 kHz	4	2	7	2	7	2	7	mS
Common-Source Output Conductance	g _{os}		5		30		30		30	μS
Common-Source Input Capacitance	C _{iss}	V _{DS} = 15 V, I _D = 200 μA f = 1 MHz	4		8		8		8	pF
Common-Source Reverse Transfer Capacitance	C _{rss}		1.5		3		3		3	
Equivalent Input Noise Voltage	e _n	V _{DS} = 15 V, I _D = 200 μA f = 10 Hz	10		20		20		20	nV/ √Hz
Matching										
Differential Gate-Source Voltage	V _{GS1} - V _{GS2}	V _{DG} = 10 V, I _D = 200 μA			5		15		40	mV
Gate-Source Voltage Differential Change with Temperature	$\frac{\Delta V_{GS1} - V_{GS2} }{\Delta T}$	V _{DG} = 10 V I _D = 200 μA T _A = -55 to 125°C	SST404	20						μV/°C
			SST406	40						
			All U		10		25		80	
Common Mode Rejection Ratio	CMRR	V _{DG} = 10 to 20 V, I _D = 200 μA	102	95		95				dB


Notes

- a. Typical values are for DESIGN AID ONLY, not guaranteed nor subject to production testing.
- b. Pulse test: PW ≤ 300 μs duty cycle ≤ 3%.


NR9

TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)


Drain Current and Transconductance vs. Gate-Source Cutoff Voltage




Gate Leakage Current




Output Characteristics




Output Characteristics









Output Characteristics



Output Characteristics




TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)




TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)


Common-Source Input Capacitance vs. Gate-Source Voltage




Common-Source Reverse Feedback Capacitance vs. Gate-Source Voltage




Output Conductance vs. Drain Current




Equivalent Input Noise Voltage vs. Frequency



Common-Source Forward Transconductance vs. Drain Current



On-Resistance and Output Conductance vs. Gate-Source Cutoff Voltage





Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.