



REV	CNN	6	CNN DESCRIPTION	Date	7	Check in
06	-		TABLE ADDED	17/02/2010		Shaun Barron
06	-		TABLE ADDED	18/02/2010		Shaun Barron

A standard 4mm plug, with a rigid, screw on acetal body which comes in a range of colours for easy identification.
 This range of product caters for a broad range of test instrumentation and speaker applications.
 The plug pin comes with a solder bucket for secure cable fixing.

Part	550	
Insulant	Acetal-LG chemical LUCCEL N127-LD/DN127-LD	Acetal C27021 R
Socket	Brass BS 2874 silver plated	
Spring		
Amps	10A	
Nominal working Voltage	50V	
Contact Resistance	10mΩ	
Maximum Temperature		
RTI	+ 110°C	
Minimum temperature	- 20°C	
Recommended Temperature	10A @55°C	
Voltage Breakdown	5000v	
Conductor size	1.5mm ²	
Colours	550-0100	Black
	550-0200	Blue
	550-0300	Brown
	550-0400	Green
	550-0500	Red
	550-0600	White
	550-0700	Yellow

Dimensions



STANDARD 4mm PLUG – SOLDER BUCKET

Tel No. +44(0)1724 273200 Website www.dem-uk.com

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF
 ALPHA 3 MANUFACTURING.
 ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF
 ALPHA 3 MANUFACTURING IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:
 DIMENSIONS ARE IN MILLIMETRES
 LINEAR TOLERANCE:
 NO DECIMAL PLACES ±0.5mm
 1 DECIMAL PLACE ±0.25mm
 2 DECIMAL PLACES ±0.125mm
 ANGULAR TOLERANCE: ±1°



DEM Manufacturing, Deltron Emcon House
 Hargreaves Way, Sowcliffe Ind. Park,
 Scunthorpe, North Lincolnshire, DN15 8RF, UK

FINISH	-	DEBURR AND BREAK SHARP EDGES	DRAWN BY	SPB	TITLE	GENERAL SPECIFICATION
			APPROVED BY	W/C	550 SERIES	
			IF IN DOUBT ASK DO NOT SCALE DRAWING	THIRD ANGLE PROJECTION	4mm PLUG	
MATERIAL	-			SHEET 1 OF 1	DRAWING NO.	550 SERIES
				SCALE 1:1	ISSUE	06
				A4	Release	