



CEM9433



AUGUST 1999

5

P-Channel Enhancement Mode Field Effect Transistor

FEATURES

- -20V , -5.4A , $R_{DS(ON)}=65m\Omega$ @ $V_{GS}=-4.5V$.
 $R_{DS(ON)}=100m\Omega$ @ $V_{GS}=-2.5V$.
- Super high dense cell design for extremely low $R_{DS(ON)}$.
- High power and current handing capability.
- Surface Mount Package.



ABSOLUTE MAXIMUM RATINGS ($T_A=25^\circ C$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	-20	V
Gate-Source Voltage	V_{GS}	± 12	V
Drain Current-Continuous ^a @ $T_J=125^\circ C$ -Pulsed ^b	I_D	± 5.4	A
	I_{DM}	± 20	A
Drain-Source Diode Forward Current ^a	I_S	-2.6	A
Maximum Power Dissipation ^a	P_D	2.5	W
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 150	$^\circ C$

THERMAL CHARACTERISTICS

Thermal Resistance, Junction-to-Ambient ^a	$R_{\theta JA}$	50	$^\circ C/W$
--	-----------------	----	--------------

CEM9433

ELECTRICAL CHARACTERISTICS (TA=25°C unless otherwise noted)

5

Parameter	Symbol	Condition	Min	Typ ^c	Max	Unit
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BVDSS	V _{GS} =0V, I _D =-250μA	-20			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =-16V, V _{GS} =0V		-1		μA
Gate-Body Leakage	I _{GSS}	V _{GS} =±12V, V _{DS} =0V		±100		nA
ON CHARACTERISTICS^b						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =-250μA	-0.6			V
Drain-Source On-State Resistance	R _{D(S(ON))}	V _{GS} =-4.5V, I _D =-5.2A		50	65	mΩ
		V _{GS} =-2.5V, I _D =-4.5A		80	100	mΩ
On-State Drain Current	I _{D(ON)}	V _{DS} =-5V, V _{GS} =-4.5V	-20			A
Forward Transconductance	g _F	V _{DS} =-9V, I _D =-5.1A		15		S
DYNAMIC CHARACTERISTICS^c						
Input Capacitance	C _{iss}	V _{DS} =-10V, V _{GS} =0V f=1.0MHz		1430		pF
Output Capacitance	C _{oss}			800		pF
Reverse Transfer Capacitance	C _{rss}			325		pF
SWITCHING CHARACTERISTICS^c						
Turn-On Delay Time	t _{D(ON)}	V _D =-6V, I _D =-1A, V _{GEN} =-4.5V, R _{GEN} =6Ω		20	28	ns
Rise Time	t _r			21	30	ns
Turn-Off Delay Time	t _{D(OFF)}			76	106	ns
Fall Time	t _f			56	78	ns
Total Gate Charge	Q _g			19.4	25	nC
Gate-Source Charge	Q _{gs}	V _{DS} =-6V, I _D =-5.1A, V _{GS} =-4.5V		3		nC
Gate-Drain Charge	Q _{gd}			5		nC

CEM9433

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ ^c	Max	Unit
DRAIN-SOURCE DIODE CHARACTERISTICS ^b						
Diode Forward Voltage	V_{SD}	$V_{GS} = 0V, I_S = -2.6A$		-0.9	-1.2	V

5

Notes

- a. Surface Mounted on FR4 Board, $t \leq 10\text{ sec}$.
- b. Pulse Test: Pulse Width $\leq 300 \mu\text{s}$, Duty Cycle $\leq 2\%$.
- c. Guaranteed by design, not subject to production testing.




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance




Figure 4. On-Resistance Variation with Drain Current and Temperature

CEM9433

5




Figure 5. Gate Threshold Variation with Temperature




Figure 7. Transconductance Variation with Drain Current




Figure 6. Breakdown Voltage Variation with Temperature




Figure 8. Body Diode Forward Voltage Variation with Source Current




Figure 9. Gate Charge




Figure 10. Maximum Safe Operating Area

CEM9433

5




Figure 11. Switching Test Circuit




Figure 12. Switching Waveforms




Figure 13. Normalized Thermal Transient Impedance Curve