## **Industrial Power Connectors**

online catalog







## Searches

Part Information | Specifications | Line Drawings








Distributors

Contact Us

**Technical Support** 

Amphenol Corporation






**Description:** Stamped single contact, high current, male

Family: C146 Contacts



General Standard Value	
Standard	Value
	1,0 - 2.0 mm
	1,8 - 2,8 mm
	2,5 - 3.5 mm
	2,5 + 0.5 mm
	3,5 + 0.5 mm
	3,5 + 0.5 mm
IEC 60512-2 Test 2 a	≤ 5 m Ω
IEC 60512-9 Test 22 a	≥ 2 p F
IEC 60512-0 Test 22 a	> 3,2 p F
120 000 12-3 103t 22 a	<u>-</u> 5,2 p i
IEC 60512-6 Test 11 j	+ 125 ° C
IEC 60512-6 Test 11 j	-40 ° C
IEC 60512-5 Test 9 a	≥ 500 mating cycles
	Cu Zn (brass)
	Cu Sn (Tin Bronze)
	Ag
	IEC 60512-2 Test 2 a IEC 60512-9 Test 22 a IEC 60512-9 Test 22 a IEC 60512-6 Test 11 j IEC 60512-6 Test 11 j





© Amphenol-Tuchel Electronics 2004 / Legal Disclaimer / Data Protection / Imprint