



- NOTES:**
- HOUSING MATERIAL: GLASS FILLED LIQUID CRYSTAL POLYMER, UL94V-0, COLOR: BLACK
TERMINAL MATERIAL: MODIFIED TIN/BRASS ALLOY
 - FINISH: A = .000200/(0.00051) MIN. TIN OVER .000050/(0.0013) MIN. NICKEL PLATE.
B = .000015/(0.00038) MINIMUM GOLD IN SELECTIVE AREA,
.000060/(0.00152) MINIMUM TIN/LEAD (90/10) ON PCB TAILS,
BOTH OVER .000050/(0.00127) MINIMUM NICKEL PLATE.
C = .000030/(0.00076) MINIMUM GOLD IN SELECTIVE AREA,
.000060/(0.00152) MINIMUM TIN/LEAD (90/10) ON PCB TAILS,
BOTH OVER .000050/(0.00127) MINIMUM NICKEL PLATE.
 - PRODUCT SPECIFICATION: PS-43045
 - TRAY PACKAGED: SEE MOLEX DRAWING PK-70873-0314
 - MATES WITH MICRO FIT (3.0) RECEPTACLE SERIES 43025
 - HEADER INSTALLATION REQUIRES A MINIMUM FORCE OF 24LBS/(107 N)
PER CIRCUIT DISTRIBUTED EQUALLY ACROSS THE ENTIRE SURFACE.
 - .010/.025 OFFSETS ARE PRESENT ON ALL PARTS MANUFACTURED AFTER 11/1/2007,
AND ON PARTS PRIOR TO 11/1/2007 THAT CONTAIN A GREEN DOT ON THE PRIMARY
SHIPPING CARTON LABEL.
 - THIS PART CONFORMS TO CLASS B REQUIREMENTS OF COSMETIC SPECIFICATION
PS-45499-002.

ADD .097 DIM. NOTE 8 IEC NO: UCP2008-0324 2007/12/19 DRAWN BY: BURLESON 2007/12/20 CHKD: SMOUSEK 2007/12/20 APPR: SMITH 2007/12/20 HZ REV	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED): 4 PLACES ± .005 ± .005 3 PLACES ± .005 ± .010 2 PLACES ± .025 ± .014 1 PLACE ± 0.36 ± .005 ANGULAR ± 1/2°	DIMENSION STYLE IN/MM DRAWN BY: BURLESON DATE: 2001/08/30 CHECKED BY: MUELLER DATE: 2001/08/30 APPROVED BY: MARGULIS DATE: 2001/08/30	SCALE: --- DESIGN UNITS: METRIC THIRD ANGLE PROJECTION
	MICRO FIT HEADER VERTICAL COMPLIANT PIN TRAY PACKED			
	MOLEX INCORPORATED			
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO. SEE CHART DOCUMENT NO. SD-44914-001	

SHEET NO. 1 OF 1