

FK-MCP 1,5/10-ST-3,81 BK

Order No.: 1967142

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1967142>Plug component, Nominal current: 8 A, Rated voltage (III/2): 160 V,
Pitch: 3.81 mm, Color: black**Commercial data**

GTIN (EAN)	4017918917791
Note	Made-to-order
sales group	E101
Pack	50 pcs.
Customs tariff	85366990
Weight/Piece	0.00959 KG

Product notesWEEE/RoHS-compliant since:
02/13/2003

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Certificates / Approvals

Certification

CB, CSA, CUL, GOST, UL, VDE-PZI

CSA

Nominal voltage U_N	300 V
Nominal current I_N	8 A
AWG/kcmil	28-16

CUL

Nominal voltage U_N	300 V
Nominal current I_N	8 A
AWG/kcmil	28-16

UL

Nominal voltage U_N	300 V
Nominal current I_N	8 A
AWG/kcmil	28-16

Accessories

Item	Designation	Description
------	-------------	-------------

Marking

1051993	B-STIFT	Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm
0804109	SK 3,81/2,8:FORTL.ZAHLEN	Marker card, printed horizontally, self-adhesive, 10-section marker strip, 14 identical decades marked 1-10, 11-20 etc. up to 91-(99)100, sufficient for 140 terminal blocks
0805056	SK 3,81/2,8:SO	Marker card, special printing, self-adhesive, labeled acc. to customer requirements, 14 identical marker strips per card, max. 25-position labeling per strip, color: White
0803883	SK U/2,8 WH:UNBEDRUCKT	Unprinted marker cards, DIN A4 format, pitch as desired, self-adhesive, with 50 stamped marker strips, 185 mm strip length, can be labeled with the CMS system or manually with the M-PEN

Tools

1205037	SZS 0,4X2,5	Screwdriver, bladed, matches all screw terminal blocks up to 1.5 mm ² connection cross section, blade: 0.4 x 2.5 mm
---------	-------------	--

Additional products

Item	Designation	Description
------	-------------	-------------

General

1897885	EMC 1,5/10-G-3,81	Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Pitch: 3.81 mm, Color: green, Metal surface: Sn, Assembly: Press-in
1860728	EMCV 1,5/10-G-3,81	Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Pitch: 3.81 mm, Color: green, Metal surface: Sn, Assembly: Press-in
1857964	IMC 1,5/10-ST-3,81	Plug component, Nominal current: 8 A, Rated voltage (III/2): 160 V, Pitch: 3.81 mm, Color: green, Metal surface: Sn
1803358	MC 1,5/10-G-3,81	Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Pitch: 3.81 mm, Color: green, Metal surface: Sn, Assembly: Soldering

1908842	MC 1,5/10-G-3,81 THT	Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Pitch: 3.81 mm, Color: black, Metal surface: Sn, Assembly: SMD/THT/THR, User information and design recommendations on through hole reflow technology can be found at: http://www.combicon.com
1830033	MCD 1,5/10-G-3,81	Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Pitch: 3.81 mm, Color: green, Metal surface: Sn, Assembly: Soldering, In combination with MCV plug components, both an MCVW and an MCVR plug must be used.
1843156	MCD 1,5/10-G1-3,81	Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Pitch: 3.81 mm, Color: green, Metal surface: Sn, Assembly: Soldering, In combination with MCV plug components, both an MCVW and an MCVR plug must be used.
1830486	MCDV 1,5/10-G-3,81	Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Pitch: 3.81 mm, Color: green, Metal surface: Sn, Assembly: Soldering, In combination with MCV plug components, both an MCVW and an MCVR plug must be used.
1847819	MCDV 1,5/10-G1-3,81	Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Pitch: 3.81 mm, Color: green, Metal surface: Sn, Assembly: Soldering, In combination with MCV plug components, both an MCVW and an MCVR plug must be used.
1861808	MCO 1,5/10-GL-3,81	Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Pitch: 3.81 mm, Color: green, Metal surface: Sn, Assembly: Soldering
1861727	MCO 1,5/10-GR-3,81	Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Pitch: 3.81 mm, Color: green, Metal surface: Sn, Assembly: Soldering
1803507	MCV 1,5/10-G-3,81	Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Pitch: 3.81 mm, Color: green, Metal surface: Sn, Assembly: Soldering
1837515	MCVDU 1,5/10-G-3,81	Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Pitch: 3.81 mm, Color: green, Metal surface: Sn, Assembly: Soldering
1832811	MCVK 1,5/10-G-3,81	Plug component, Nominal current: 8 A, Rated voltage (III/2): 160 V, Pitch: 3.81 mm, Color: green, Metal surface: Sn, Assembly: DIN rail
1827350	SMC 1,5/10-G-3,81	Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Pitch: 3.81 mm, Color: green, Metal surface: Sn, Assembly: Soldering

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;