



Description:

Statfree DLR EPA Kits meets the working surface requirements of EN61340-5-1. This material is a dual purpose rubber matting material. The two layer construction allows it to be used as a dissipative or a conductive matting product. The soft dissipative layer makes an excellent table mat, ideal for use in soldering and assembly areas. This rubber material has superior resistance to heat, abrasion, chemicals, and is easy to clean and maintain. Statfree DLR material will not melt and does not burn when coming into contact with hot metal parts or soldering debris. It is amine, chloride, sulfide, alumina, and magnesia free.

Specifications:

Construction:	Dual layer Static Dissipative rubber
Material Thickness:	2mm (± 5%)
Colour:	Blue
Texture:	Slight emboss
Weight:	2.7kg/m ²
Hardness:	75 ± 5 Shore A
Rp-p Colour Layer:	10E6 - 10E8 ohms tested per IEC 61340-2-3
Rp-p Black Layer:	<10E5 ohms tested per IEC 61340-2-3
Rg Colour Layer:	10E6 - 10E8 ohms tested per IEC 61340-2-3
Rg Black Layer:	<10E5 ohms tested per IEC 61340-2-3

Grounding: This material must be properly grounded for optimum electrical performance.

<u>Cleaning:</u> Use only ESD mat cleaner such as Reztore [™] Surface & Mat Cleaner to clean and extend mat useful life. Do not use cleaners contaiing silicone as silicone will create an insulative film on the surface. Do not use solvent based cleaners as solvents will dry out matting and may cause curling.

Special manufactured items are not returnable for credit

EN 61340-5-1 paragraph 5.2.2 Working surfaces and storage racks "All working surfaces and storage racks on which unprotected ESDS may be placed shall be capable of being connected to EPA ground and shall have a point-to-point resistance and resistance to EPA ground in accordance with table 1 (Rp greater or equal to 1 x 10E4, less than or equal to 1 x 10E9 ohms, and Rg greater or equal to 7.5 x 10E5 to less than or equal to 1 x 10E9 ohms)."



Tolerances are ± 5mm unless specified



EPA KIT, STATFREE DLR MATERIAL, BLUE, 1.2M x 0.6M

VERMASON UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH,	DRAWING NUMBER	DATE
HERTFORDSHIRE, SG6 2TD, UNITED KINGDOM PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440 AIL: Service@Vermason.co.uk, INTERNET: Vermason.co.uk	VER-28217	August 2010