

300 IP TORX PLUS® torque-indicator



Application: TORX PLUS® socket screws
Pre-set torque: 0.6 Nm-3.0 Nm (0.4 ft.lb.-3.0 ft.lb.), fixed pre-sets
Accuracy: ±10 %
Blade: Hexagonal, 4 mm, reduced diameter tip
Design: Black Point
Handle: Kraftform with non-roll feature, multi-component

| Code | Nm | ft. lb. | mm | mm | mm | mm | | | |
|-------------|-------|---------|-----|----|-----|----|-----|------------|---|
| 05028040001 | 6 IP | 0.6 | 0.4 | 4 | 3.5 | 65 | 105 | 2 9/16" | 1 |
| 05028041001 | 7 IP | 0.9 | 0.7 | 4 | 3.5 | 65 | 105 | 2 9/16" | 1 |
| 05028042001 | 8 IP | 1.2 | 0.9 | 4 | 3.5 | 65 | 105 | 2 9/16" | 1 |
| 05028043001 | 9 IP | 1.4 | 1.0 | 4 | 3.5 | 65 | 105 | 2 9/16" | 1 |
| 05028044001 | 10 IP | 2.0 | 1.5 | 4 | 3.8 | 65 | 105 | 2 9/16" | 1 |
| 05028045001 | 15 IP | 3.0 | 2.2 | 4 | 3.8 | 65 | 105 | 2 9/16" | 1 |