

Angular Feed-Through Spring Clamp



	AS4/3			AS4/4			AS6/3		
Terminal Width	6 mm			6 mm			8 mm		
Height x Length	42 x 61.5 mm			42 x 61.5 mm			42 x 74 mm		
Stripping Length	14 mm			14 mm			15 mm		
Insulation Material	Polyamide 6.6			Polyamide 6.6			Polyamide 6.6		
Type of Connection	3 spring clamps & 2 slots for interconnection			4 spring clamp connection			3 spring clamps & 2 slots for interconnection		
Approvals	UL ^①			UL ^①			UL ^①		
Wire Range	22-10 AWG	0.5-4 sq.mm.	22-10 AWG	22-10 AWG	0.5-4 sq.mm.	22-10 AWG	22-8 AWG	0.5-6 sq.mm.	22-8 AWG
Voltage Rating	600V	800 V	600 V	600V	800 V	600 V	600V	800 V	600 V
Current Rating	35 A	32 A	35 A	35 A	32 A	35 A	50 A	41 A	50 A
Other Approvals									

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Terminal Block	AS4/3	100	AS4/4	100	AS6/3	50
End Plate	EPAS4	50	EPAS4	50	EPAS6	50
Partition Plate						
DIN Rail for ordering information refer to page 72						
End Stop for ordering information refer to page 74	CA702	50	CA702	50	CA702	50
	CA802	50	CA802	50	CA802	50
Jumpers Adjacent	CA801/2	100			CA801/3	100
Jumpers Alternate	CA801/2-3	100			CA801/3-3	100
Push in type wire jumper	CA901/2	100			CA901/3	100
Step Down Jumper see page 78	CA901/4	100			CA901/4	100
	CA901/6	100			CA901/6	100
Marking Tags (KType)	MT6	100	MT6	100	MT8	100
	MT6F	10	MT6F	10	MT6F	10

① UL recognition in progress.