


# EMK33 Series

- MEMS Clock Oscillators
- LVCMOS Output
- +3.3V Supply Voltage
- Tri-State and Power Down Options
- 4 Pad Plastic SMD Package
- 30,000 G Shock Resistance
- RoHS Compliant (Pb-Free)



ECLIPTEK<sup>®</sup>  
CORPORATION



## ELECTRICAL SPECIFICATIONS

|   |   |   |
|---|---|---|
| <b>Nominal Frequency</b>                          |   | 1.000MHz to 125MHz  |
| <b>Operating Temperature Range</b>                |   | -40°C to +85°C  |
| <b>Storage Temperature Range</b>                  |   | -55°C to +125°C   |
| <b>Supply Voltage (V<sub>DD</sub>)</b>            |   | 3.3V <sub>DC</sub> ±10%   |
| <b>Input Current</b>                              | ≤ 25.000MHz   | 20mA Maximum  |
|   | > 25.000MHz   | 25mA Maximum  |
| <b>Frequency Tolerance / Stability</b>            | Inclusive of All Conditions: Calibration Tolerance at 25°C, Frequency Stability over the Operating Temperature Range, Supply Voltage Change, Output Load Change, 1st Year Aging at 25°C, 260°C Reflow, Shock, and Vibration |   |
| <b>Output Voltage Logic High (V<sub>OH</sub>)</b> | I <sub>OH</sub> = -8mA  | 90% of V <sub>DD</sub> Minimum  |
| <b>Output Voltage Logic Low (V<sub>OL</sub>)</b>  | I <sub>OL</sub> = +8mA  | 10% of V <sub>DD</sub> Maximum  |
| <b>Rise Time / Fall Time</b>                      | 20% to 80% of waveform  | 2nSeconds Maximum   |
| <b>Duty Cycle</b>                                 | at 50% of waveform  | 50 ±5(%)  |
| <b>Load Drive Capability</b>                      |   | 15pF Maximum  |
| <b>Output Control Function</b>                    |   | Tri-State or Power Down   |
| <b>Output Control Input Voltage</b>               | V <sub>IH</sub> of 70% of V <sub>DD</sub> Minimum or No Connection  | Enables Output  |
|   | V <sub>IL</sub> of 30% of V <sub>DD</sub> Maximum   | Disables Output: High Impedance State for Tri-state, Logic Low for Power Down |
| <b>Standby Current</b>                            |   | 50µA Maximum  |
| <b>Peak to Peak Jitter (tPK)</b>                  | 1.000MHz to 12.287999MHz  | 500pSec Maximum, 200pSec Typical  |
|   | 12.288MHz to 125.000MHz   | 250pSec Maximum, 100pSec Typical  |
| <b>Aging</b>                                      | First Year at 25°C  | ±1ppm Maximum   |
| <b>Start Up Time</b>                              |   | 50mSec Maximum  |

| MANUFACTURER   | CATEGORY   | SERIES | PACKAGE | VOLTAGE | CLASS | REV. DATE |
|----------------|------------|--------|---------|---------|-------|-----------|
| ECLIPTEK CORP. | OSCILLATOR | EMK33  | PLASTIC | 3.3V    | 055K  | 04/10     |

## PART NUMBERING GUIDE

### EMK33 H 2 H - 50.000M TR

**FREQUENCY TOLERANCE & STABILITY/  
OPERATING TEMPERATURE RANGE**

G=±100ppm Maximum over -40°C to +85°C  
H=±50ppm Maximum over -40°C to +85°C

**DUTY CYCLE**

2=50% ±5%

**LOGIC CONTROL**


H=Tri-State (High Impedance)  
J=Power Down (Logic Low)

**AVAILABLE OPTIONS**


Blank=Bulk  
TR=Tape & Reel

**FREQUENCY**

**MECHANICAL DIMENSIONS**  
ALL DIMENSIONS IN MILLIMETERS





**SUGGESTED SOLDER PAD LAYOUT**  
ALL DIMENSIONS IN MILLIMETERS



Pin 1: Tri-State or Power Down    Pin 3: Output  
Pin 2: Case Ground                    Pin 4: Supply Voltage

Tolerances=±0.1

**TAPE AND REEL DIMENSIONS**  
ALL DIMENSIONS IN MILLIMETERS



|  |           |           |            |          |           |
|--|-----------|-----------|------------|----------|-----------|
|  | A         | B         | C          | D        | E         |
|  | 12.0 ±0.3 | 5.5 ±0.05 | 4.75 ±0.05 | 4.0 ±0.1 | 2.0 ±0.1  |
|  | F         | G         | H          | J        | K         |
|  | 4.0 ±0.2  | A0*       | 1.5 ±1/-0  | B0*      | 0.3 ±0.05 |
|  |           |           |            | L        |           |
|  |           |           |            |          | K0*       |

|      |         |        |          |           |            |
|------|---------|--------|----------|-----------|------------|
| REEL | M       | N      | O        | P         | Q          |
|      | 1.5 MIN | 50 MIN | 20.2 MIN | 13.0 ±0.2 | 40 MIN     |
|      | R       | S      | T        | U         | V          |
|      | 2.5 MIN | 10 MIN | 18.4 MAX | 180 MAX   | 12.4 +2/-0 |
|      |         |        |          |           | QTY/REEL   |
|      |         |        |          |           | 1,000      |

\*Compliant to EIA 481C

**ENVIRONMENTAL/MECHANICAL SPECIFICATIONS**

| Characteristic               | Specification  |
|------------------------------|--|
| ESD Susceptibility           | MIL-STD-883, Method 3015, Class 2, HBM: 2000V                      |
| Flammability                 | UL94-V0  |
| Mechanical Shock             | MIL-STD-883, Method 2002, Condition G, 30,000G                     |
| Moisture Resistance          | MIL-STD-883, Method 1004   |
| Moisture Sensitivity Level   | J-STD-020, MSL 1   |
| Resistance to Soldering Heat | MIL-STD-202, Method 210, Condition K                               |
| Resistance to Solvents       | MIL-STD-202, Method 215  |
| Solderability                | MIL-STD-883, Method 2003 (Four I/O Pads on bottom of package only) |
| Temperature Cycling          | MIL-STD-883, Method 1010, Condition B                              |
| Thermal Shock                | MIL-STD-883, Method 1011, Condition B                              |
| Vibration                    | MIL-STD-883, Method 2007, Condition A, 20G                         |

**MARKING SPECIFICATIONS**

Line 1: XXXX or XXXXX  
Ecliptek Manufacturing Lot Code

|                                |                        |                 |                    |                 |               |                    |
|--------------------------------|------------------------|-----------------|--------------------|-----------------|---------------|--------------------|
| MANUFACTURER<br>ECLIPTEK CORP. | CATEGORY<br>OSCILLATOR | SERIES<br>EMK33 | PACKAGE<br>PLASTIC | VOLTAGE<br>3.3V | CLASS<br>OS5K | REV. DATE<br>04/10 |
|--------------------------------|------------------------|-----------------|--------------------|-----------------|---------------|--------------------|