

200 mA low quiescent current
very low noise LDO


Datasheet – production data

Features

- Input voltage from 1.9 to 5.5 V
- Very low dropout voltage (100 mV typ. at 100 mA load)
- Low quiescent current (max. 100 μ A, 1 μ A in OFF mode)
- Very low noise
- Output voltage tolerance: $\pm 2.0\%$ @ 25 °C
- 200 mA guaranteed output current
- Wide range of fixed output voltages available on request: from 0.8 V to 3.5 V with 100 mV step
- Adjustable version: from 0.8 V to $V_{IN} - V_{drop}$
- Logic-controlled electronic shutdown
- Compatible with ceramic capacitor $C_{OUT} = 1 \mu F$
- Internal current and thermal limit
- Available in SOT23-5L, SOT323-5L and DFN6 (1.2 x 1.3 mm) packages
- Temperature range: -40 °C to 125 °C

Applications

- Mobile phones
- Personal digital assistants (PDAs)
- Cordless phones and similar battery-powered systems
- Digital still cameras



Description

The LDK120xx low drop voltage regulator provides 200 mA of maximum current from an input supply voltage in the range of 1.9 V to 5.5 V, with a typical dropout voltage of 100 mV.

It is stabilized with a ceramic capacitor on the output.

The very low drop voltage, low quiescent current and low noise features make it suitable for low power battery-powered applications.

An enable logic control function puts the LDK120xx in shutdown mode allowing a total current consumption lower than 1 μ A.

The device also includes a short-circuit constant current limiting and thermal protection.

Table 1. Device summary


Part numbers			
LDK120XX	LDK120XX12	LDK120XX28	LDK120XX33
LDK120XX08	LDK120XX15	LDK120XX30	LDK120XX35
LDK120XX10	LDK120XX18	LDK120XX31	
LDK120XX11	LDK120XX25	LDK120XX32	

Contents

1	Diagram	3
2	Pin configuration	4
3	Typical application	5
4	Maximum ratings	6
5	Electrical characteristics	7
6	Typical performance characteristics	9
7	Package mechanical data	14
8	Order codes	23
9	Revision history	24

1 Diagram

Figure 1. Block diagram



2 Pin configuration

Figure 2. Pin connection (top view)




Table 2. Pin description (SOT23-5L, SOT323-5L)

Pin		Symbol	Function
SOT23/ SOT323	DFN6		
1	6	IN	Input voltage of the LDO
2	2	GND	Common ground
3	4	EN	Enable pin logic input: Low = shutdown, High = active
4	3	BYP ⁽¹⁾ /ADJ	Bypass capacitor on fixed versions, Adjustable pin on ADJ versions
5	1	OUT	Output voltage of the LDO
-	5	N/C	Not connected. This pin should be connected to GND

1. Bypass capacitor for noise reduction on fixed version is optional, if not used the relevant pin must be left floating with no routing on the board.

3 Typical application

Figure 3. Typical application circuits for fixed version





Figure 4. Typical application circuits for adjustable version



4 Maximum ratings

Table 3. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{IN}	DC input voltage	- 0.3 to 6	V
V_{OUT}	DC output voltage	- 0.3 to $V_I + 0.3$	V
V_{EN}	Enable input voltage	- 0.3 to $V_I + 0.3$	V
$V_{BYP/ADJ}$	ADJ/Bypass pin voltage	2	V
I_{OUT}	Output current	Internally limited	mA
P_D	Power dissipation	Internally limited	mW
T_{STG}	Storage temperature range	- 65 to 150	°C
T_{OP}	Operating junction temperature range	- 40 to 125	°C

Note: *Absolute maximum ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied. All values are referred to GND.*

Table 4. Thermal data

Symbol	Parameter	SOT23-5L	SOT323-5L	DFN-6L	Unit
R_{thJA}	Thermal resistance junction-ambient	160	246	237	°C/W
R_{thJC}	Thermal resistance junction-case	68	134	104	°C/W

5 Electrical characteristics

$T_J = 25^\circ\text{C}$, $V_{IN} = V_{OUT(NOM)} + 1 \text{ V}$, $C_{IN} = C_{OUT} = 1 \mu\text{F}$, $I_{OUT} = 1 \text{ mA}$, $V_{EN} = V_{IN}$, unless otherwise specified.

Table 5. Electrical characteristics for LDK120xx

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
V_{IN}	Operating input voltage		1.9		5.5	V
V_{OUT}	V_{OUT} accuracy	$I_{OUT}=1 \text{ mA}$, $T_J=25^\circ\text{C}$	-2.0		2.0	%
		$I_{OUT}=1 \text{ mA}$, $-40^\circ\text{C} < T_J < 125^\circ\text{C}$	-3.0		3.0	%
ΔV_{OUT}	Static line regulation	$V_{OUT} + 1 \text{ V} \leq V_{IN} \leq 5.5 \text{ V}$, $I_{OUT}=1 \text{ mA}$		0.05		%/V
ΔV_{OUT}	Static load regulation	$I_{OUT} = 1 \text{ mA}$ to 200 mA		0.006		%/mA
V_{DROP}	Dropout voltage ⁽¹⁾	$I_{OUT} = 100 \text{ mA}$, $V_{OUT}=2.5 \text{ V}$		100		mV
		$I_{OUT} = 200 \text{ mA}$, $V_{OUT}=2.5 \text{ V}$ $40^\circ\text{C} < T_J < 125^\circ\text{C}$		150	300	
e_N	Output noise voltage	10 Hz to 100 kHz , $I_{OUT}=10 \text{ mA}$, $V_{OUT}=2.5 \text{ V}$, $C_{BYP}=10 \text{ nF}$		51		$\mu\text{V}_{\text{RMS}}/\text{V}$
SVR	Supply voltage rejection	$V_{IN}=V_{OUT(NOM)}+0.5 \text{ V} +/- V_{\text{RIPPLE}}$ $V_{\text{RIPPLE}}=0.1 \text{ V}$ Freq.=120 Hz to 10 kHz $I_{OUT}=10 \text{ mA}$		55		dB
I_Q	Quiescent current	$I_{OUT}=0 \text{ mA}$, $-40^\circ\text{C} < T_J < 125^\circ\text{C}$		30	60	μA
		$I_{OUT}=200 \text{ mA}$, $-40^\circ\text{C} < T_J < 125^\circ\text{C}$		50	100	
		V_{IN} input current in OFF mode: $V_{EN}=\text{GND}$			1	
I_{SC}	Short-circuit current	$R_L=0$		400		mA
V_{EN}	Enable input logic low	$V_{IN}=1.9 \text{ V}$ to 5.5 V , $-40^\circ\text{C} < T_J < 125^\circ\text{C}$			0.4	V
	Enable input logic high	$V_{IN}=1.9 \text{ V}$ to 5.5 V , $-40^\circ\text{C} < T_J < 125^\circ\text{C}$	1.2			
I_{EN}	Enable pin input current	$V_{SHDN}=V_{IN}$			100	nA
T_{SHDN}	Thermal shutdown			160		°C
	Hysteresis			20		
C_{OUT}	Output capacitor	Capacitance (see <i>Section 6: Typical performance characteristics</i>)	1		22	μF

1. Dropout voltage is the input-to-output voltage difference at which the output voltage is 100 mV below its nominal value.

$T_J = 25^\circ\text{C}$, $V_{IN} = V_{OUT(NOM)} + 1 \text{ V}$, $C_{IN} = C_{OUT} = 1 \mu\text{F}$, $I_{OUT} = 1 \text{ mA}$, $V_{EN} = V_{IN}$, unless otherwise specified.

Table 6. Electrical characteristics for LDK120

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
V_{IN}	Operating input voltage		1.9		5.5	V
V_{ADJ}	V_{ADJ} accuracy	$I_{OUT}=1 \text{ mA}$, $T_J=25^\circ\text{C}$	784	800	816	mV
		$I_{OUT}=1 \text{ mA}$, $-40^\circ\text{C} < T_J < 125^\circ\text{C}$	-3.0		3.0	%
ΔV_{OUT}	Static line regulation	$V_{OUT} + 1 \text{ V} \leq V_{IN} \leq 5.5 \text{ V}$, $I_{OUT}=1 \text{ mA}$		0.05		%/V
ΔV_{OUT}	Static load regulation	$I_{OUT}=1 \text{ mA}$ to 200 mA		0.006		%/mA
V_{DROP}	Dropout voltage ⁽¹⁾	$I_{OUT}=100 \text{ mA}$, $V_{OUT}=2.5 \text{ V}$		100		mV
		$I_{OUT}=200 \text{ mA}$, $V_{OUT}=2.5 \text{ V}$ $40^\circ\text{C} < T_J < 125^\circ\text{C}$		150	300	
e_N	Output noise voltage	10 Hz to 100 kHz , $I_{OUT}=10 \text{ mA}$		130		$\mu\text{V}_{RMS}/\text{V}$
I_{ADJ}	Adjust pin current				1	μA
SVR	Supply voltage rejection	$V_{IN}=V_{OUT(NOM)}+0.5 \text{ V} \pm V_{RIPPLE}$ $V_{RIPPLE}=0.1 \text{ V}$ Freq.= 120 Hz to 10 kHz $I_{OUT}=10 \text{ mA}$		55		dB
I_Q	Quiescent current	$I_{OUT}=0 \text{ mA}$, $-40^\circ\text{C} < T_J < 125^\circ\text{C}$		30	60	μA
		$I_{OUT}=200 \text{ mA}$, $-40^\circ\text{C} < T_J < 125^\circ\text{C}$		50	100	
		V_{IN} input current in OFF mode: $V_{EN}=\text{GND}$			1	
I_{SC}	Short-circuit current	$R_L=0$		400		mA
V_{EN}	Enable input logic low	$V_{IN}=1.9 \text{ V}$ to 5.5 V , $-40^\circ\text{C} < T_J < 125^\circ\text{C}$			0.4	V
	Enable input logic high	$V_{IN}=1.9 \text{ V}$ to 5.5 V , $-40^\circ\text{C} < T_J < 125^\circ\text{C}$	1.2			
I_{EN}	Enable pin input current	$V_{SHDN}=V_{IN}$			100	nA
T_{SHDN}	Thermal shutdown			160		$^\circ\text{C}$
	Hysteresis			20		
C_{OUT}	Output capacitor	Capacitance (see <i>Section 6: Typical performance characteristics</i>)	1		22	μF

1. Dropout voltage is the input-to-output voltage difference at which the output voltage is 100 mV below its nominal value.

6 Typical performance characteristics

$C_{IN} = C_{OUT} = 1 \mu F$, V_{EN} to V_{IN} , unless otherwise specified.

Figure 5. Output voltage vs. temp. for adjustable ($I_O = 1 \text{ mA}$)




Figure 6. Output voltage vs. temp. for adjustable version ($I_O = 200 \text{ mA}$)




Figure 7. Output voltage vs. temp. for fixed version ($I_O = 1 \text{ mA}$)




Figure 8. Output voltage vs. temp. for fixed version ($I_O = 200 \text{ mA}$)




Figure 9. Line regulation vs. temp. for adjustable version




Figure 10. Short-circuit current vs. temp. for adjustable version




Figure 11. Load regulation vs. temp. for adjustable version




Figure 12. Load regulation vs. temp. for fixed version




Figure 13. Enable pin thresholds vs. temp. ($V_{IN} = 1.9$ V)




Figure 14. Enable pin thresholds vs. temp. ($V_{IN} = 4$ V)




Figure 15. Quiescent current vs. temp. for adjustable version ($I_O = 0$ mA)




Figure 16. Quiescent current vs. temp. for adjustable version ($I_O = 200$ mA)




Figure 17. Quiescent current vs. temp. for fixed version ($I_O = 0 \text{ mA}$)




Figure 18. Quiescent current vs. temp. for fixed version ($I_O = 200 \text{ mA}$)




Figure 19. Shutdown current vs. temperature




Figure 20. SVR vs. frequency ($V_O = 2.5 \text{ V}$)




Figure 21. SVR vs. frequency ($V_O = V_{ADJ}$)




Figure 22. Output noise vs. frequency ($V_O = 3.3 \text{ V}$)




Figure 23. Output noise vs. frequency ($V_O = V_{ADJ}$)




Figure 24. Stability region vs. C_{OUT} (fixed)




Figure 25. Stability region vs C_{OUT} (adjust.)




Figure 26. Line transient ($V_{OUT} = V_{ADJ}$)




Figure 27. Line transient ($V_{OUT} = 3 \text{ V}$)




Figure 28. Load transient ($V_{OUT} = 3 \text{ V}$)







Figure 29. Load transient ($V_{OUT} = V_{ADJ}$)


$V_{OUT} = V_{ADJ}$, $V_{IN} = V_{EN} = 3.5$ V, $I_{OUT} = 1$ mA to 200 mA,
 $C_{OUT} = 1 \mu\text{F}$, $t_r = t_f = 5 \mu\text{s}$

Figure 30. Startup transient



$V_{OUT} = 3$ V, $V_{IN} = V_{EN} = 0$ to 4.2 V, $I_{OUT} = 1$ mA, $C_{IN} = C_{OUT} = 1 \mu\text{F}$, $t_r = t_f = 5 \mu\text{s}$

Figure 31. Enable transient ($V_{OUT} = V_{ADJ}$)

V_{OUT} @ 0.8 V, $V_{IN} = 1.9$, $V_{EN} = 0$ to V_{IN} , $I_{OUT} = 200$ mA,
 $C_{OUT} = 1 \mu\text{F}$, $t_r = t_f = 1 \mu\text{s}$

Figure 32. Enable transient ($V_{OUT} = 3$ V)

$V_{IN} = 4$ V, $V_{EN} = 0$ to V_{IN} , $I_{OUT} = 200$ mA, $C_{IN} = C_{OUT} = 1 \mu\text{F}$,
 $t_r = t_f = 1 \mu\text{s}$

Figure 33. Dropout voltage vs. temperature ($I_{OUT} = 100$ mA)**Figure 34. Dropout voltage vs. temperature ($I_{OUT} = 200$ mA)**

7 Package mechanical data

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: www.st.com. ECOPACK is an ST trademark.

Table 7. SOT23-5L mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	0.90		1.45
A1	0.00		0.15
A2	0.90		1.30
b	0.30		0.50
C	0.09		0.20
D	2.80		3.05
E	1.50		1.75
e		0.95	
H	2.60		3.00
L	0.30		0.60
θ	0°		10°



Figure 35. SOT23-5L drawing**Figure 36.** SOT23-5L footprint data (dimensions in mm)

Table 8. DFN6L (1.2 x 1.3 mm) mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	0.31	0.38	0.40
A1	0.00	0.02	0.05
b	0.15	0.18	0.25
c		0.05	
D		1.20	
E		1.30	
e		0.40	
L	0.475	0.525	0.575
L3	0.375	0.425	0.475


Figure 37. DFN6L (1.2 x 1.3 mm) drawing



Figure 38. DFN6L foot print data (dimensions in mm)

Table 9. SOT323-5L mechanical data


Dim.	mm		
	Min.	Typ.	Max.
A	0.80		1.10
A1	0.00		0.10
A2	0.80	0.90	1.00
b	0.15		0.30
C	0.10		0.22
D	1.80	2.00	2.20
E	1.80	2.10	2.40
E1	1.15	1.25	1.35
e		0.65	
e1		1.3	
L	0.26	0.36	0.46
θ	0°		8°

Figure 39. SOT323-5L drawing




Tape & Reel SOT23-xL MECHANICAL DATA

DIM.	mm.			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A			180			7.086
C	12.8	13.0	13.2	0.504	0.512	0.519
D	20.2			0.795		
N	60			2.362		
T			14.4			0.567
Ao	3.13	3.23	3.33	0.123	0.127	0.131
Bo	3.07	3.17	3.27	0.120	0.124	0.128
Ko	1.27	1.37	1.47	0.050	0.054	0.058
Po	3.9	4.0	4.1	0.153	0.157	0.161
P	3.9	4.0	4.1	0.153	0.157	0.161



Tape & Reel SOT323-xL MECHANICAL DATA

DIM.	mm.			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A	175	180	185	6.889	7.086	7.283
C	12.8	13	13.2	0.504	0.512	0.519
D	20.2			0.795		
N	59.5	60	60.5		2.362	
T			14.4			0.567
Ao		2.25			0.088	
Bo		2.7			0.106	
Ko		1.2			0.047	
Po	3.98	4	4.2	0.156	0.157	0.165
P	3.98	4	4.2	0.156	0.157	0.165



8 Order codes

Table 10. Order codes

Part numbers	Packages			Output voltages
	SOT323-5L	SOT23-5L	DFN6L	
LDK120XX	LDK120C-R	LDK120M-R	LDK120PU-R	ADJ
LDK120XX08	LDK120C08R	LDK120M08R	LDK120PU08R	0.8 V
LDK120XX10	LDK120C10R	LDK120M10R	LDK120PU10R	1.0 V
LDK120XX11	LDK120C11R	LDK120M11R		1.1 V
LDK120XX12	LDK120C12R	LDK120M12R		1.2 V
LDK120XX15	LDK120C15R	LDK120M15R		1.5 V
LDK120XX18	LDK120C18R	LDK120M18R		1.8 V
LDK120XX25	LDK120C25R	LDK120M25R		2.5 V
LDK120XX28	LDK120C28R	LDK120M28R		2.8 V
LDK120XX30	LDK120C30R	LDK120M30R	LDK120PU30R	3.0 V
LDK120XX31	LDK120C31R	LDK120M31R		3.1 V
LDK120XX32	LDK120C32R	LDK120M32R	LDK120PU32R	3.2 V
LDK120XX33	LDK120C33R	LDK120M33R		3.3 V
LDK120XX35	LDK120C35R			3.5 V

Table 11. Marking

Order codes	Packages	Output voltages	Marking
LDK120MxxR	SOT23-5L	xx V	Kxx
LDK120CxxR	SOT323-5L	xx V	Kxx
LDK120PUxxR	DFN-6L	xx V	xx
LDK120M-R	SOT23-5L	Adj	KAD
LDK120C-R	SOT323-5L	Adj	KAD
LDK120PU-R	DFN-6L	Adj	AD

9 Revision history

Table 12. Document revision history

Date	Revision	Changes
26-Nov-2012	1	Initial release
31-Jan-2013	2	Added new part number LDK120PU32R Updated <i>Table 10 on page 23</i>

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY TWO AUTHORIZED ST REPRESENTATIVES, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2013 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -
Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com

