

ESW205 and ESW208 Series

5 & 8 Port, Compact Industrial Ethernet Switches

Features

- ✓ **NEW** UL/cUL Class I Div 2 Groups A,B,C, and D
- ✓ Generic Standard for (Heavy) Industrial Environments - EN61000-6-2
- ✓ Shock, Vibration, Tested
- ✓ Operating Temperature
-10°C to 60°C (Standard)
-40°C to 75°C (-T models)
- ✓ ST or SC Single and Multi mode fiber Ports
- ✓ 10/100M, full/half duplex, MDI/MDI-X (Auto-negotiate)
- ✓ Supports IEEE 802.3, 802.3u, and 802.3x standards
- ✓ Industrial IP30 rated DIN rail case with 6 way Panel mount options
- ✓ Dual power inputs, 12 to 36 VDC and 10 to 24 VAC
- ✓ 2K MAC addresses

Functional Description

Designed to fit many applications, the ESW205 and ESW208 series are more than just an Ethernet switch with a great low pricing. They are plug-and-play industrial Ethernet Switches with an compact IP30 DIN rail case, 6 way mountable panel brackets, LEDs for Power, (Link / Speed / Activity for each port), 12 to 36 VDC and 10 to 24 VAC power inputs with removable terminal blocks. These switches are perfect for any applications that require special protection from hash environments.

Choose a switch with five or eight copper ports, or a combination of copper and fiber ports. Multi-mode fiber models extend range up to 2 km. Single-mode fiber models extend range up to 20 km. All models require an external power supply (sold separately).

The switch ships with 4 panel mount clips giving the user 6 different ways to panel mount the unit.



Ordering Information

Model Number	10/100 Copper	Multi-Mode Fiber	Single-mode Fiber
ESW205	5		
ESW205-MT	4	1 (ST)	
ESW205-MC	4	1 (SC)	
ESW205-ST	4		1 (ST)
ESW205-SC	4		1 (SC)
ESW208	8		
ESW208-2MT	6	2 (ST)	
ESW208-2MC	6	2 (SC)	
ESW208-2ST	6		2 (ST)
ESW208-2SC	6		2 (SC)
ESW208-4MT-T	4	4 (ST)	
ESW208-4MC-T	4	4 (SC)	
ESW208-4ST-T	4		4 (ST)
ESW208-4SC-T	4		4 (SC)
All Models available in wide temperature		Add -T to model number	

Accessory Items

MDR-20-24	DIN Rail Mount, 24 VDC, 1 A Power Supply
MDR-40-24	DIN Rail Mount, 24 VDC, 1.7 A Power Supply
DR19RMKT	Adjustable DIN Rail 19 Inch Rack Mount Kit
EIRSP1	Single Stage Surge Protector

www.bb-elec.com orders@bb-elec.com support@bb-elec.com

International Office: 707 Dayton Road PO Box 1040 Ottawa, IL 61350 USA 815-433-5100 Fax 433-5104
European Office: Westlink Commercial Park Oranmore Co. Galway Ireland +353 91 792444 Fax +353 91 792445



Specifications

Technology

Standards:	IEEE802.3, 802.3u, 802.3x
Processing Type:	Store and forward with IEEE802.3x full duplex, non-blocking flow control
Flow Control:	IEEE802.3x flow control, back pressure flow control
Packet buffer memory:	64K bytes
Address Table Size	2K MAC Addresses

Interface

RJ45 Ports:	10/100BaseT(X) auto negation, Full/Half duplex, auto MDI/MD-X
Fiber Ports:	100BaseFX, (multi-mode or single-mode with ST or SC connectors)
LED Indicators:	Power, (Link / Speed / Activity for each port)

Fiber Optics

Fiber Type	Distance	Wavelength	Transmit Power	Receive Sensitivity
Multi-mode	2 km	1310 nm	Neg. 23.5 to Neg. 14 dBm	≤ Neg. 35 dBm
Single-mode	20 km	1310 nm	Neg. 15 to Neg. 8 dBm	≤ Neg. 35 dBm

Power

Input Voltage 12 to 36 VDC and 10 to 24 VAC

Power Consumption 4.00 W Max

Input Connection Removable Terminal Block
Protection Reverse Polarity Protection

Mechanical

Enclosure IP30 DIN mount metal case

Dimensions (5 ports) H 112.4mm x W 30mm x D 75.2mm
(4.42 in x 1.18in x 2.96in)

Dimensions (8 ports)
8 copper,
6 copper/2 fiber ports, H 130mm x W 44mm x D 105mm
(5.1in X 1.73in x 4.13in)

Dimensions (8 ports)
4 copper/4 fiber ports H 130mm x W 46mm x D 105mm
(5.1in X 1.81in x 4.13in)

Installation 35 mm DIN or 6 way panel mount

Environmental

Op. Temperature
Standard -10 to 60 C (14 to 140 F)
Wide Temp (-T model) -40 to 75 C (-40 to 167 F)

Storage Temperature -40 to 80 C (-40 to 176 F)
Humidity

MTBF 200,000 hours
MTBF Calculation Parts count reliability prediction

Regulatory Approvals

CE, FCC,
RoHS

Hazardous Locations

NEW UL/cUL Class I Div 2 Groups A,B,C, and D

Specifications - EN 61000-6-2: 2006 Generic Standards for (Heavy) Industrial environments

Test	Description	Test Level		Level
EN 55022: 2006 + A1:2007	Class B Emissions			
EN 61000-4-2: 2009	Electro-Static Discharge (ESD)	Enclosure Contact	6kV	3
		Enclosure Air	8kV	3
EN61000-4-3:2006+A1:2008	Radiated Field Immunity (RFI)	Enclosure Ports	10V/m	3
		Signal Ports	1kV@2.5Khz	3
EN61000-4-4:2004	Burst (Fast Transient)	DC Ports	2kV	3
		Signal Ports	1kV	3
EN61000-4-5:2006	Surge	DC Power Ports	2kV	3
		Signal Ports	10 V RMS	3
EN61000-4-6: 2009	Induced (Conductive) RFI	DC Power Ports	10 V RMS	3

Environmental Specifications

Test	Description	Test Level		Level
IEC60068-2-6	Vibration	Test Fc	2G	-----
IEC60068-2-27	Shock	Test Ea	30G	-----
IEC60068-2-32	Free Fall			-----
Operating Temperature	Standard	-10 to 60C	14 to 140F	
	Wide Operating Temperature (- T models)	-40 to 75C	-40 to 167F	
Storage Temperature		-40 to 80C	-40 to 176F	
Humidity		10 to 95% Non-condensing		



www.bb-elec.com orders@bb-elec.com support@bb-elec.com

International Office: 707 Dayton Road PO Box 1040 Ottawa, IL 61350 USA 815-433-5100 Fax 433-5104
European Office: Westlink Commercial Park Oranmore Co. Galway Ireland +353 91 792444 Fax +353 91 792445



