

Surface Mount Ultrafast Plastic Rectifier


DO-214AA (SMB)

| PRIMARY CHARACTERISTICS | |
|-------------------------|--------------|
| $I_{F(AV)}$ | 2.0 A |
| V_{RRM} | 300 V, 400 V |
| I_{FSM} | 50 A |
| t_{rr} | 35 ns |
| V_F | 1.1 V |
| $T_J \text{ max.}$ | 150 °C |

FEATURES

- Glass passivated chip junction
- Ideal for automated placement
- Ultrafast reverse recovery time
- Low switching losses, high efficiency
- High forward surge capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C
- Solder dip 260 °C, 40 s
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



TYPICAL APPLICATIONS

For use in high frequency rectification and freewheeling application in switching mode converters and inverters for consumer, computer and telecommunication.

MECHANICAL DATA

Case: DO-214AA (SMB)

Epoxy meets UL 94V-0 flammability rating

Terminals: Matte tin plated leads, solderable per J-STD-002 and JESD22-B102

E3 suffix for commercial grade, meets JESD 201 class 1A whisker test, HE3 suffix for high reliability grade (AEC Q101 qualified), meets JESD 201 class 2 whisker test

Polarity: Color band denotes cathode end

| MAXIMUM RATINGS ($T_A = 25\text{ °C}$ unless otherwise noted) | | | | |
|--|----------------|---------------|------|------|
| PARAMETER | SYMBOL | ES2F | ES2G | UNIT |
| Device marking code | | EF | EG | |
| Maximum repetitive peak reverse voltage | V_{RRM} | 300 | 400 | V |
| Working peak reverse voltage | V_{RWM} | 225 | 300 | V |
| Maximum RMS voltage | V_{RMS} | 210 | 280 | V |
| Maximum average forward rectified current at $T_L = 110\text{ °C}$ | $I_{F(AV)}$ | 2.0 | | A |
| Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load | I_{FSM} | 50 | | A |
| Operating junction and storage temperature range | T_J, T_{STG} | - 55 to + 150 | | °C |

| ELECTRICAL CHARACTERISTICS ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted) | | | | | |
|--|--|----------|-----------|------|---------------|
| PARAMETER | TEST CONDITIONS | SYMBOL | ES2F | ES2G | UNIT |
| Maximum instantaneous forward voltage ⁽¹⁾ | 2.0 A | V_F | 1.1 | | V |
| Maximum reverse current at V_{RRM} | $T_A = 25\text{ }^\circ\text{C}$ $T_A = 100\text{ }^\circ\text{C}$ | I_R | 10 200 | | μA |
| Maximum reverse recovery time | $I_F = 0.5\text{ A}$, $I_R = 1.0\text{ A}$, $I_{rr} = 0.25\text{ A}$ | t_{rr} | 35 | | ns |
| Maximum reverse recovery time | $I_F = 1.0\text{ A}$, $dI/dt = 100\text{ A}/\mu\text{s}$, $V_R = 30\text{ V}$, $I_{rr} = 0.1 I_{RM}$ | t_{rr} | 50 | | ns |
| Maximum reverse recovery current | $I_F = 1.0\text{ A}$, $dI/dt = 100\text{ A}/\mu\text{s}$, $V_R = 30\text{ V}$, $I_{rr} = 0.1 I_{RM}$ | I_{RM} | 3.0 | | A |
| Maximum stored charge | $I_F = 1.0\text{ A}$, $dI/dt = 100\text{ A}/\mu\text{s}$, $V_R = 30\text{ V}$, $I_{rr} = 0.1 I_{RM}$ | Q_{rr} | 50 | | nC |
| Typical junction capacitance | 4.0 V, 1 MHz | C_J | 15 | | pF |

Note:

(1) Pulse test: 300 μs pulse width, 1 % duty cycle

| THERMAL CHARACTERISTICS ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted) | | | | |
|---|------------------------------------|----------|------|---------------------------|
| PARAMETER | SYMBOL | ES2F | ES2G | UNIT |
| Maximum thermal resistance ⁽¹⁾ | $R_{\theta JA}$ $R_{\theta JL}$ | 75 25 | | $^\circ\text{C}/\text{W}$ |

Note:

(1) Units mounted on P.C.B. 5.0 x 5.0 mm (0.013 mm thick) land areas

| ORDERING INFORMATION (Example) | | | | |
|---------------------------------------|-----------------|------------------------|---------------|------------------------------------|
| PREFERRED P/N | UNIT WEIGHT (g) | PREFERRED PACKAGE CODE | BASE QUANTITY | DELIVERY MODE |
| ES2G-E3/52T | 0.096 | 52T | 750 | 7" diameter plastic tape and reel |
| ES2G-E3/5BT | 0.096 | 5BT | 3200 | 13" diameter plastic tape and reel |
| ES2GHE3/52T ⁽¹⁾ | 0.096 | 52T | 750 | 7" diameter plastic tape and reel |
| ES2GHE3/5BT ⁽¹⁾ | 0.096 | 5BT | 3200 | 13" diameter plastic tape and reel |

Note:

(1) Automotive grade AEC Q101 qualified

RATINGS AND CHARACTERISTICS CURVES

($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)




Figure 1. Maximum Forward Current Derating Curve




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current




Figure 3. Typical Instantaneous Forward Characteristics




Figure 5. Reverse Switching Characteristics




Figure 4. Typical Reverse Leakage Characteristics






Figure 6. Typical Junction Capacitance

PACKAGE OUTLINE DIMENSIONS in inches (millimeters)



Mounting Pad Layout





Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.