


# ReadyBoard™ 910

EPIC Single Board Computer with  
Intel® Core™ i7/i5/i3 Processor



## Features

- 2<sup>nd</sup>/3<sup>rd</sup> Generation Intel® Core™ i7/i5/i3 Processor
- Dual Gigabit Ethernet
- USB 3.0 with SuperSpeed 5Gb/s Data Transfer Rate
- Analog VGA, LVDS and DVI-D display
- PCI Express Mini Card socket; PCI-104 expansion
- Onboard SSD

## Specifications

### Core System

CPU – Intel® Core™ i7-3610QE, 2.3GHz, 6M L3 Cache, 45W TDP  
Intel® Core™ i5-3610ME, 2.7GHz, 3M L3 Cache, 35W TDP  
Intel® Core™ i3-3120ME, 2.4GHz, 3M L3 Cache, 35W TDP  
Intel® Core™ i7-2710QE, 2.1GHz, 6M LLC, 45W TDP  
Intel® Core™ i5-2510E, 2.5GHz, 3M LLC, 35W TDP  
Intel® Core™ i3-2330E, 2.2GHz, 3M LLC, 35W TDP  
Intel® Celeron® B810, 1.6GHz, 2M LLC, 35W TDP

Memory – Up to 16GB dual channel DDR3 1066/1333MHz SODIMM

Chipset – Intel® HM65 Platform Controller Hub

BIOS – AMI with CMOS backup in 32 Mbit SPI flash with ACPI 2.0

Hardware Monitor – Supply voltages and CPU temperature

### Bus Interfaces

PCI-104, PCIe Mini Card

### Multi I/O and Storage

SATA – 2 devices

USB – 2x USB 3.0 with 5Gb/s data transfer rate (faceplate)

2x USB 2.0 (onboard pin header)

Serial – 2 configurable ports for RS-232/422/485

LED & reset – Power, SATA active, reset button

Keyboard/Mouse – PS/2 interface

GPIO – 4x GPI and 4x GPO

Audio – High Definition Audio; S/PDIF

Storage – Onboard SSD (default 4GB)

### Ethernet

Dual Gigabit Ethernet (Intel® 82574IT controller)

### Video

Integrated Intel® HD Graphics 4000 supporting dual independent displays

Intel® Dynamic Video Memory Technology (DVMT 5.0)

DirectX 10 and OpenGL 2.1

3 display ports:

DVI-D - Resolution up to 1920 x 1200 @ 60Hz (WUXGA)

VGA - Resolution up to 2048 x 1536 @ 60 Hz (QXGA)

LVDS - Dual-channel 24-bit LVDS; resolution up to 1920 x 1080 @ 60Hz

### Power

Input Power – AT mode (12 V +/- 5%), ATX mode (12 V and 5 Vsb +/- 5%)

Power States – Supports S0, S1, S3, S4, S5

### Mechanical and Environmental

Size – 165.1 x 114.3 mm (6.5 x 4.5"); EPIC form factor

Board Thickness – 0.093" (2.36 mm)

Operating Temperature

- Standard: 0°C to +60°C
- Extended: -20°C to +70°C

Storage Temperature – -20°C to +75°C

Humidity – 90% at 60°C

### Operating Systems

Standard Support - Win 7, Windows XP, Linux

Extended Support (BSP) - Win XPe, WES 2009, WES 7, WEC 7, VxWorks 6.9, QNX 6.5

## Ordering Information

### Modules

Model Number	Description/Configuration
RB-910-S	ReadyBoard 910, PCI-104, HM65, Socket G2, 4GB on board SSD
RB-910-L-2710	Quick Start Kit (Intel® Core™ i7-2710QE Processor, cable kit, 2GB RAM, QuickDrive, Fansink thermal module)

### Accessories

Model Number	Description/Configuration
DDR3 memory	Verified industrial grade 1GB, 2GB, 4GB DDR3 SODIMM memory available