

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth

CA 91311

Phone: (818) 701-4933 (818) 701-4939 Fax:

TIP31/31A/31B/31C

- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)
 The complementary PNP types are the TIP32 respectively
 Epoxy meets UL 94 V-0 flammability rating

Moisure Sensitivity Level 1 Marking: Part Number Mounting Torque: 5 in-lbs Maximum Absolute Maximum Ratings @ T. = 25 C (unless otherwise noted)


| Symbol | Parameter | Value | Unit |
|---|---------------------------------------|-----------------------|----------------------|
| V _{CBO} TIP31 TIP31A TIP31B TIP31C | Collector-base voltage (Open emitter) | 40 60 80 100 | ٧ |
| V _{CEO} TIP31 TIP31A TIP31B TIP31C | Collector-emitter voltage (Open base) | 40 60 80 100 | V |
| V_{EBO} | Emitter-base Voltage (Open collector) | 5 | V |
| Ic | Collector Current | 3 | Α |
| I _{CM} | Collector Current Pulse | 5 | Α |
| Ι _Β | Base Current | 1 | Α |
| Pc | Total Device Dissipation(Ta=25℃) | 2 | W |
| | Total Device Dissipation(Tc=25℃) | 40 | W |
| TJ | Junction Temperature | 150 | $^{\circ}\mathbb{C}$ |
| T _{STG} | Storage Temperature Range | -65 to +150 | $^{\circ}\mathbb{C}$ |

Electrical Characteristics @ 25°C Unless Otherwise Specified

| Symbol | Parameter | Min | Max | Units |
|--|--|-----------------------|-----|-------|
| V _{CEO(SUS)} TIP31 TIP31A TIP31B TIP31C | Collector-emitter sustaining voltage (I_C =30mA; I_B =0) | 40 60 80 100 | | V |
| V _{CE(sat)} | Collector-emitter Saturation Voltage (I _C =3A I _B =0.375A) | | 1.2 | V |
| V_{BE} | Base-emitter Voltage (I _C =3A ; V _{CE} =4V) | | 1.8 | V |
| I _{CES} TIP31 TIP31A TIP31B TIP31C | Collector cut-off current $(V_{CE}=40V; V_{EB}=0)$ $(V_{CE}=60V; V_{EB}=0)$ $(V_{CE}=80V; V_{EB}=0)$ $(V_{CE}=100V; V_{EB}=0)$ | | 0.2 | mA |
| I _{CEO} TIP31/31A TIP31B/C | Collector cut-off current $(V_{CE}=30V; V_{EB}=0)$ $(V_{CE}=60V; V_{EB}=0)$ | | 0.3 | mA |
| I _{EBO} | Emitter cut-off current (V _{EB} =5V; I _C =0) | | 1.0 | mA |
| Hfe | DC current gain ($I_c=1A$; $V_{cE}=4V$) ($I_c=3A$; $V_{cE}=4V$) | 25 10 | 50 | |
| fT | Transition frequency ($I_C=0.5A$; $V_{CE}=10V$) | 3 | | MHZ |

Notes:1.High Temperature Solder Exemption Applied, see EU Directive Annex 7.

Silicon NPN **Power Transistors**



| | DIMENSIONS | | | | |
|-----|------------|------|-------|-------|------|
| | INCHES MM | | ИM | | |
| DIM | MIN | MAX | MIN | MAX | NOTE |
| Α | .560 | .625 | 14.22 | 15.88 | |
| В | .380 | .420 | 9.65 | 10.67 | |
| С | .140 | .190 | 3.56 | 4.82 | |
| D | .020 | .045 | 0.51 | 1.14 | |
| F | .139 | .161 | 3.53 | 4.09 | Ø |
| G | .190 | .110 | 2.29 | 2.79 | |
| Н | | .250 | | 6.35 | |
| J | .012 | .025 | 0.30 | 0.64 | |
| K | .500 | .580 | 12.70 | 14.73 | |
| L | .045 | .060 | 1.14 | 1.52 | |
| N | .190 | .210 | 4.83 | 5.33 | |
| Q | .100 | .135 | 2.54 | 3.43 | |
| R | .080 | .115 | 2.04 | 2.92 | |
| S | .045 | .055 | 1.14 | 1.39 | |
| Т | .230 | .270 | 5.84 | 6.86 | |
| U | | .050 | | 1.27 | |
| V | .045 | | 1.15 | | |



Ordering Information:

| Device | Packing |
|----------------|-----------------|
| Part Number-BP | Bulk; 1Kpcs/Box |

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.