

SEARCH

PART # | DOC | SITE

Display Overview

Product Lineup

3.5" Lineup

5.5" Lineup

6.3" Lineup

6.5" Lineup

7.0" Lineup

8.4" Lineup

9.0" Lineup

10.4" Lineup

NL10276BC20 -04

NL10276BC20 -08

NL6448BC33 -50

NL6448BC33 -53

NL6448BC33 -54

NL6448BC33 -63C

NL6448BC33 -63D

NL6448BC33 -64

NL6448BC33 -64C

NL8060BC26 -27

NL8060BC26 -28

12.1" Lineup

15.0" Lineup

15.3" Lineup

19.0" Lineup

20.1" Lineup

21.3" Lineup

Industrial TFT

Transflective TFT

Markets

Support

LCD Product Brief

NL6448BC33 -64C

10.4 inches (26 cm) VGA for industrial applications
ST - NLT

Characteristics

Model number	NL6448BC33 -64C
Drive method	a-Si TFT active matrix
Screen size	10.4 inches (26 cm diagonal)
Number of pixels	640 x 480
Effective display area	211.2 (H) x 158.4 (V) mm
Backlight	One side 2 CCFL
Luminance	450 cd/m2
Contrast	600:1
Display colors	262k colors
Viewing angle	Up: 80°, down: 60°, right: 80°, left: 80° [1]
Response time (t_{on})	25 ms [2]
Outline dimension	243.0 (W) x 185.1 (H) x 10.5 (D) mm
Weight	475 g
Operating temperature	-20°C to +70°C
Storage temperature	-30°C to +80°C
Power supply voltage	3.3 V (5 V)
Power consumption	6.2 W [3]
Input signal	CMOS (RGB 6 bits each)
Remark	ST-NLT

Note:

[1] Contrast of 10:1 or higher

[2] Value of Ton+Toff (0% ? 90%)

[3] Value does not include power consumption of recommended inverter

All values are typical values.

All specifications shown on this web site are subject to change without notice.

SITE MAP

CONTACT US

PRINT

FEATURE

[FFF-Compatibility](#)

[Super Fine Technology](#)