



Recommended P.C. Board Layout

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ON-SHORE TECHNOLOGY, INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ON-SHORE TECHNOLOGY, INC.

SIGN	DATE	DESCRIPTION	APPROVER
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			

- Material**
- Insulator: Glass Filled Polyester
 - Flammability: UL94V-0
 - Contacts: Phosphor Bronze
 - Contact Plating: See options
 - Shell: Brass
 - Shell Plating: 80u" Min. Tin over 50u" Cu

- Ratings**
- Current: 1A
 - Voltage: 30V AC(r.m.s.)
 - Contact Resistance: $\leq 30\text{m}\Omega$
 - Insulation Resistance: >1,000 MU
 - Dielectric Strength: 750V AC
 - Operating Temp: -55° - +85°
 - Storage Temp: -40° - +70°

RoHS Compliant

PART NUMBER:

USB-A1SSXX

- COLOR:**
 B: Black
 W: White
- PLATING:**
 6: Selective Gold Flash (Std.)
 8: Selective 30u" Gold



TITLE		USB - A type, Side type, thru hole			
PART NO.		USB-A1SSXX		DWG NO. USB-A1SSXX.DWG	
APPROVED		CHECKED	DESIGNED	DRAWN	4050
		Marvin 2006.11.12	Marvin 2006.11.12	Marvin 2006.11.12	
		SHEET: 01/01		REV: A	Tolerance X* ±1" XX ±0.30/012 XXX ±0.20/008 XXXX ±0.10/004