

# Spezifikation für Freigabe / specification for release


Kunde / customer :  
 Artikelnummer / part number : **744711015**  
 Bezeichnung : **Stabkerndrossel WE-SD**  
 description : **Rod Core Inductor WE-SD**

LF



DATUM / DATE : 2005-08-23

## A Mechanische Abmessungen / dimensions :



A	<b>30,8 max.</b>	mm
B	<b>29,2 ± 0,5</b>	mm
C	<b>12,0 typ</b>	mm
D	<b>14,0 ± 0,5</b>	mm
E	<b>16,0 max</b>	mm
F	<b>1,0 min</b>	mm
G	<b>3,0 ± 0,5</b>	mm
H	<b>∅ 1,7 ref</b>	mm

## B Elektrische Eigenschaften / electrical properties :

Eigenschaften / properties	Testbedingungen / test conditions		Wert / value	Einheit / unit	tol.
Leerlaufinduktivität / OC-Inductance	10 kHz / 5 mA	L <sub>0</sub>	<b>10,0</b>	μH	±25%
Nenninduktivität / nominal inductance	10 kHz / 5 mA / I <sub>N</sub>	L <sub>N</sub>	<b>10,0</b>	μH	typ.
DC-Widerstand / DC-resistance	@ 20°C	R <sub>DC</sub>	<b>5,7</b>	mΩ	±20%
Nennstrom / rated current	ΔT=40K	I <sub>N</sub>	<b>15,0</b>	A	typ.
Eigenres.-Frequenz / self-res.-frequency		SRF	<b>37,0</b>	MHz	typ.

## C Lötpad / soldering spec. :

## D Prüfgeräte / test equipment :

Wayne Kerr 3260 B für/for L und/and R<sub>DC</sub>  
 HP 4396 B für/for SRF

## E Testbedingungen / test conditions :

Luftfeuchtigkeit / humidity: 33%  
 Umgebungstemperatur / temperature: +20°C

## F Werkstoffe & Zulassungen / material & approvals :

Basismaterial / base material: Ferrit / ferrite  
 Draht/ wire : DIN EN 60317-13

## G Eigenschaften / general specifications :

Betriebstemp. / operating temperature: -40°C - + 150°C  
 Umgebungstemp. / ambient temperature: -40°C - + 110°C  
 It is recommended that the temperature of the part does not exceed 150°C under worst case operating conditions.

Freigabe erteilt / general release:	Kunde / customer			
Datum / date	Unterschrift / signature			
	Würth Elektronik			
	RSt	Rdc-Korrektur	06-11-23	
	MST	Version 1	05-08-23	
Geprüft / checked	Kontrolliert / approved		Name	Änderung / modification Datum / date

Würth Elektronik eiSos GmbH & Co.KG

D-74638 Waldenburg · Max-Eyth-Straße 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400  
<http://www.we-online.com>

# Spezifikation für Freigabe / specification for release

Kunde / customer :

Artikelnummer / part number :

744711015



Bezeichnung :


Stabkerninduktoren WE-SD

description :

Rod Core Inductor WE-SD

DATUM / DATE : 2005-08-23

## H Impedanzkurve / Impedance curve :



Freigabe erteilt / general release:	<b>Kunde / customer</b>		
Datum / date	Unterschrift / signature		
	<b>Würth Elektronik</b>		
Geprüft / checked	Kontrolliert / approved	RSt	Rdc-Korrektur
		MST	Version 1
		Name	Änderung / modification
			Datum / date
			06-11-23
			05-08-23

This electronic component has been designed and developed for usage in general electronic equipment. Before incorporating this component into any equipment where higher safety and reliability is especially required or if there is the possibility of direct damage or injury to human body, for example in the range of aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc, Würth Elektronik eiSos GmbH must be informed before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

### Würth Elektronik eiSos GmbH & Co.KG

D-74638 Waldenburg · Max-Eyth-Straße 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400  
http://www.we-online.com