

8-, 16- and 32-bit Microcontrollers/Microprocessors

# Freescale Tower System

# Modular development platform

#### Overview

The Freescale Tower System is a modular development platform for 8-, 16- and 32-bit microcontrollers and microprocessors that enables advanced development through rapid prototyping. Featuring multiple development boards or modules, the Tower System provides designers with building blocks for entry-level to advanced microcontroller development.

### Modular and Expandable

- Controller modules provide easy-to-use, reconfigurable hardware
- Interchangeable peripheral modules (including serial, memory and graphical LCD) make customization easy
- Open-source hardware and standardized specifications promote the development of additional modules for added functionality and customization

#### The Freescale Tower System

#### **Controller Module**

- Tower MCU/MPU board
- Works stand-alone or in Tower System
- Features integrated debugging interface for easy programming and run control via standard USB cable

#### Secondary Elevator

- Additional and secondary serial and expansion bus signals
- Standardized signal assignments
- Mounting holes and expansion connectors for side-mounting peripheral boards

# Primary Elevator

- Common serial and expansion bus signals
- Two 2x80 connectors on backside for easy signal access and side-mounting board (LCD module)
- Power regulation circuitry
- Standardized signal assignments
- Mounting holes

#### **Board Connectors**

- Four card-edge connectors
- Uses PCI Express<sup>®</sup> connectors (x16, 90 mm/ 3.5" long, 164 pins)

#### Size

 Tower is approx. 3.5" H x 3.5" W x 3.5" D when fully assembled

# Peripheral Module

 Examples include serial interface module, memory expansion module and Wi-Fi<sup>®</sup>



#### **Speeds Development Time**

- Open source hardware and software allows quick development with proven designs
- Integrated debugging interface allows for easy programming and run-control via standard USB cable

#### **Cost Effective**

- Peripheral modules can be re-used with all Tower System controller modules, eliminating the need to purchase redundant hardware for future designs
- Enabling technologies like LCD, serial and memory interfacing are offered off-the-shelf at a low cost to provide a customized enablement solution

## Software Enablement and Support

The increasing complexity of industrial applications and expanding functionality of semiconductors are driving embedded developers toward solutions that require the integration of proven hardware and software platforms. Freescale, along with a strong alliance network, offers comprehensive solutions, including development tools, debuggers, programmers and software.

# Complimentary Software and Tools

- Freescale MQX<sup>™</sup> RTOS, Ethernet,
   FileSystem, USB stacks and more\*
- Freescale Linux® BSP\*
- CodeWarrior Development Studio
- Processor Expert software:
   A rapid application development tool in the CodeWarrior tool suite
- Digital signal processing library: Provides algorithms optimized for the ColdFire architecture
- \* Visit freescale.com/software for a list of supported devices

### Take Your Design to the Next Level

For a complete list of development kits and modules offered as part of the Freescale Tower System, please visit freescale.com/Tower.

Tower System Modules		
Features	Benefits	
Controller Modules (8-, 16-, 32-bit)		
Works stand-alone or as part of Tower System	Allows rapid prototyping	
Features open source debugging interface	Provides easy programming and run-control via standard USB cable	
Peripheral Modules		
Can be re-used with all Tower System controller modules	Eliminates the need to buy/develop redundant hardware	
Interchangeable peripheral modules—serial, memory, graphical LCD, prototyping, sensor	Enables advanced development and broad functionality	
Elevator Boards		
Two 2x80 connectors	Provides easy signal access and side-mounting board (i.e. LCD module)	
Power regulation circuitry	Provides power to all boards	
Standardized signal assignments	Allows for customized peripheral module development	
Four card-edge connectors available	Allows easy expansion using PCI Express® connectors (x16, 90 mm/3.5" long, 164 pins)	


#### **Build Your System in Three Steps or Less**



1. Choose a controller module



2. Choose peripheral modules (up to three standard modules plus side-mounting module(s))







**TWR-SER** 

TOWER

TWR-ELEV



Ultimate
Connectivity
Solution











Connectivity Solution with Sensors

TWR-MCF5225x

TWR-SER

TWR-SENSOR-PAK

TWR-ELEV

Tower Sensor Solution











Connectivity
Solution
with Graphical
LCD

TWR-MCF5225x

**TWR-SER** 

TWR-LCD

**TWR-ELEV** 

**Tower LCD Solution** 

# **Example Configurations**

#### **Partner Modules**

Tap into a powerful ecosystem of Freescale technology alliances for building smarter, better connected solutions. Designed to help you shorten your design cycle and get your products to market faster, these technology alliances provide you with access to rich design tools, peripherals and world-class support and training.

A number of partners have developed modules for the Tower System. Some examples include the i.MX515 ARM® Cortex<sup>TM</sup>-A8 Tower Computer Module and StackableUSB<sup>TM</sup> I/O Device Carrier module from Micro/sys, as well as the Rapid Prototyping System (RPS) AM1 and FM1 modules from iMN MicroControl.

A complete list of partner-developed modules is available at **freescale.com/Tower**.

### **Multiple Power Options**


The Freescale Tower System can be powered entirely over a USB cable via a host PC or USB wall power adaptor. Alternatively, power can be supplied to the Tower via a screw terminal on the primary elevator.

Protection circuitry is built into all Tower System modules to avoid contention on the power rails. Although power can be supplied through any module, power supplied through the elevator modules takes precedence.

Processor module
 via debugger connection

2. Tower elevator

3. Peripheral module



All power connectors are standard USB connectors that can be powered by a USB host/hub or an AC-to-DC adapter with a USB cable.



# **Tower Geeks Online Community**

TowerGeeks.org is an online design engineer community that allows members to interact, develop designs and share ideas. Offering a direct path to explore and interact with other engineers designing with the Tower System, TowerGeeks.org is a great way to discuss your projects, post videos of your progress, ask questions through the forum and upload software. With updates through Twitter and Facebook, it's easy to get involved.



Follow Tower Geeks on Twitter twitter.com/towergeeks



Visit Freescale on Facebook facebook.com/freescale

Price	Features
\$39	MCF51CN ColdFire V1 Ethernet module
\$49	MCF5225X ColdFire V2 connectivity module
\$69	MC9S08LL64 8-bit segment LCD module
\$69	MC9S08LH64 8-bit segment LCD module with integrated 16-bit ADC
\$119	MPC5125 e300c4 module built on Power Architecture® technology
\$59	MCF51MM ColdFire V1 microcontroller module designed for medical applications
\$59	MC9S08MM128 8-bit microcontroller module designed for medical applications
\$69	MCF51JE ColdFire V1 USB microcontroller module
\$139	MCF5441X ColdFire V4 connectivity module with dual Ethernet
\$79	MC56F8257 DSC module
\$69	K40X256 Kinetis module (based on ARM® Cortex™-M4 core) with full-speed USB 2.0 On-The-Go and segment LCD controller
\$109	K53N512 Kinetis module (based on ARM Cortex-M4 core) with Integrated Measurement Engine, Ethernet full-speed USB 2.0 On-The-Go and segment LCD controller
\$69	K60N512 Kinetis module (based on ARM Cortex-M4 core) with IEEE® 1588 Ethernet, full- and High-Speed USB 2.0 On-the-Go, hardware encryption and tamper detection
Price	Features
\$29	Elevator modules: Primary and secondary
\$49	Serial module with RS232/RS485, Ethernet, CAN, USB
\$99	Enhanced serial module featuring dual Ethernet and High-Speed USB
\$14.99	Prototyping module
\$99	Graphical LCD module with 3.2" QVGA display
\$89	Memory module with serial flash, MRAM, SD card and compact flash interfaces
\$149	Swappable sensor module with accelerometer, barometer and touch-sensing controller
\$69	802.11n Wi-Fi® board featuring Redpine Signals' RS9110-N-11-21 Connect-io-n™ Wi-Fi module on board
\$69	802.11b Wi-Fi board featuring GainSpan's GS1011MIP Wi-Fi module on board
\$NA	Sold as part of a complete kit, electrocardiograph sensor for medical applications
\$119	Linear Technology analog module featuring high-precision ADCs and DACs
1	Wireless mesh networking featuring Synapse Wireless' SM700 802.25.4 RF engine
	Analog audio module featuring SGTL5000 low-power stereo codec
	Includes
	TWR-MCF51CN, TWR-SER and TWR-ELEV modules
+	TWR-MCF5225X, TWR-SER and TWR-ELEV modules
	TWR-S08LL64, TWR-PROTO and TWR-ELEV modules
+	TWR-S08LH64, TWR-PROTO and TWR-ELEV modules  TWR-MPC5125 TWR-SER and TWR-ELEV modules
	TWR-MPC5125, TWR-SER and TWR-ELEV modules  TWR-MCF51MM, TWR-SER, TWR-ELEV and MED-EKG modules
+ .	TWR-MCPSTMM, TWR-SER, TWR-ELEV and MED-EKG modules  TWR-S08MM128, TWR-SER, TWR-ELEV and MED-EKG modules
	TWR-MCF51JE-KIT, TWR-SER and TWR-ELEV modules
+	TWR-MCF313E-N1, TWR-SER2 and TWR-ELEV Indules
	TWR-K40X256, TWR-SER and TWR-ELEV modules
	TWR-K53N512, TWR-SER and TWR-ELEV modules
+	TWR-K60N512, TWR-SER and TWR-ELEV modules  TWR-K60N512-KIT, TWR-PROTO, IAR J-Link (Lite) Debug Probe
	\$69 \$119 \$59 \$59 \$69 \$139 \$79 \$69 \$109 \$69 <b>Price</b> \$29 \$49 \$99 \$14.99 \$99 \$14.99 \$69 \$14.99 \$89 \$14.99

Note: All prices indicated are MSRP.

**Learn More:** 

For more information about the Freescale Tower System, please visit **freescale.com/Tower**.

Freescale, the Freescale logo, CodeWarrior, ColdFire and Processor Expert are trademarks or registered trademarks of Freescale Semiconductor, Inc. Reg. U.S. Pat. & Tm. Off. The Power Architecture and Power.org word marks and the Power and Power.org logos and related marks are trademarks and service marks licensed by Power.org. ARM is a registered trademark of ARM Limited. Cortex-A8 and Cortex M-4 are trademarks of ARM Limited. All other product or service names are the property of their respective owners. © 2010, 2011 Freescale Semiconductor, Inc.

Document Number: TWRFS / Rev 9

