



- ▲ FOR MINI-APPLICATOR AND STRIPPER CRIMPER.
- ▲ FOR HAND TOOL USE ONLY.
- ▲ FOR STANDARD APPLICATOR PART #566184 ONLY.
- 4. WIRE RANGE OF 24-28. INSULATION RANGE OF .030-.040.
- 5. GOLD PLATING MAY NOT APPEAR ON CARRIER STRIP.
- ▲ GOLD PLATING PER MIL-G-45204, NICKEL PLATING PER QQ-N-290.
- ▲ TIN PLATING PER MIL-T-10727, COPPER PLATING PER MIL-C-14550.
- ▲ PLATED, 1.27μm [.000050] GOLD OVER 1.27μm [.000050] NICKEL.
- ▲ GOLD PLATED IN LOCALIZED GOLD PLATED AREA, 0.76μm [.000030] GOLD IN MATED AREA, GOLD FLASH ON REMAINDER, OVER 1.27μm [.000050] NICKEL.
- ▲ PLATED WITH GOLD FLASH OVER 0.76μm [.000030] NICKEL.
- ▲ PLATED WITH 2.54μm-5.08μm [.00100-.00200] TIN.
- ▲ PLATED WITH 1.27μm [.000050] GOLD IN LOCALIZED GOLD PLATE AREA, GOLD FLASH ON REMAINDER, OVER 1.27μm [.000050] NICKEL.
- ▲ GOLD PLATED IN LOCALIZED GOLD PLATED AREA, 0.76μm [.000030] GOLD IN MATED AREA, TIN PLATED WIRE BARRELS, OVER 1.27μm [.000050] NICKEL.
- ▲ TIN PLATED WIRE BARRELS, OVER 0.76μm [.000030] NICKEL.
- ▲ GOLD PLATED IN LOCALIZED GOLD PLATED AREA, 0.38μm [.000015] GOLD IN MATED AREA, GOLD FLASH ON REMAINDER, OVER 1.27μm [.000050] NICKEL.
- ▲ AMP ITALY PART NUMBER ONLY.
- ▲ GOLD PLATED IN LOCALIZED GOLD PLATED AREA, 0.03μm [.000001] GOLD IN MATED AREA, 0.76μm [.000030] MIN TIN OR TIN-LEAD ON WIRE BARRELS, ALL OVER 0.76μm [.000030] MIN NICKEL.

OBSOLETE	STANDARD	▲	▲	STRIP	6-66507-3
OBSOLETE	STANDARD	▲	▲	STRIP	6-66507-2
OBSOLETE	STANDARD	▲	▲	LOOSE PIECE	5-66507-9
	STANDARD	▲	▲	LOOSE PIECE	5-66507-7
OBSOLETE	STANDARD	▲	▲	STRIP	3-66507-1
	STANDARD	▲	▲	STRIP	3-66507-0
	STANDARD	▲	▲	STRIP	2-66507-8
	STANDARD	▲	▲	STRIP	2-66507-7
OBSOLETE	STANDARD	▲	▲	STRIP	1-66507-4
	STANDARD	▲	▲	LOOSE PIECE	1-66507-0
	STANDARD	▲	▲	LOOSE PIECE	66507-9
SUPERSEDED BY 66507-9	STANDARD	▲	▲	LOOSE PIECE	66507-8
	STANDARD	▲	▲	STRIP	66507-4
	STANDARD	▲	▲	STRIP	66507-3
	STANDARD	▲	▲	STRIP	66507-2

THIS DRAWING IS A CONTROLLED DOCUMENT.		BY: WELDON	DATE: 9-2-81	BY: RICHARD	DATE: 9-15-81
DRAWING NO. 114-10000		REV. 1		PIN CONTACT, SIZE 20 DF, 24-28 AWG, AMPLITE	
MATERIAL: BRASS		QUANTITY: 10000		REVISED TO: 100779 (G) 66507	
CUSTOMER DRAWING		DATE: 10-1		REVISED BY: AN2	