



Quick Reference Guide

LCD Coaxial Embedded Display Interface (LCEDI / LCEDI SR)

TE Connectivity introduces the next generation LCD Coaxial Embedded Display Interface (LCEDI) family of connectors designed to provide exceptional electrical performance in both low voltage, differential signaling (LVDS) and embedded DisplayPort (eDP) applications. This family of connectors was recently selected by VESA (Video Electronics Standard Association) as the global standard connector for a LED backlight wide (16x9) panel interface. Its ultra-low profile mating configuration (1.1mm height) makes it ideal for the slim LED backlight LCD panel of advanced notebook personal computers.

TE Connectivity's LCEDI connector family accommodates consistent digital data transmission through one, two or four DisplayPort standard lanes at a reduced bit rate of 1.62 Gbps or a high bit rate of 2.7 Gbps through each lane, and even faster data rates over different wiring schemes. The product family offers high density for notebook PC applications, minimizing space and accommodating future pin out for LED backlight technology.

FEATURES

- Twin leaf contact structure
- Mixed cable use
 - Micro coax (twin coax AWG#40 or smaller)
 - Discrete wire (AWG #32 or smaller)
- Friction lock mechanism at shell when mated

BENEFITS



- Fully intermateable with I-PEX CABLINE®-VS series. (same appearance and performance)
- User friendly design
- Full lock mechanism with pull bar (optional)

APPLICATIONS

- DVD/Blu-ray players
- Render massive 3D imaging
- Slim LED backlight LCD panel


Application

LCEDI




- For a complete LCEDI mated pair you will need:
- Receptacle-With or Without Datum Mark (2069716)
 - MATES WITH-- *
 - Plug Housing Assembly (2023344)
 - Upper Shell-With or Without Datum Mark (2023347)
 - Pull Bar-Optional (2023348)
- *TE Connectivity supports both 30 and 40 position versions

- For a complete LCEDI SR mated pair you will need:
- Interface Receptacle (2023308)
 - MATES WITH-- *
 - Interface Plug (2023314)
 - Upper Shell (2023317) (2023351)
 - Lower Shell (2023318) (2023352)
- *The height of a mated LCEDI SR pair is 4.3mm(30P and 40P) or 9.35mm (44P)



LCEDI SR



| LCEDI / LCEDI SR | | | | | | | |
|------------------|-------------|----------|------------|-----|---------------------------------------|---------------------------------------|---------------|
| | PN | Category | Commodity | POs | Description | Components Required For Mated Pair | Mating Height |
| | 8-2069716-3 | LCEDI | Receptacle | 40 | Receptacle Without Datum Mark (Y ver) | Required - With or Without Datum Mark | 1.1 mm |
| | 5-2069716-3 | LCEDI | Receptacle | 40 | Receptacle With Datum Mark | | |
| | 2023344-3 | LCEDI | Plug | 40 | Plug Housing Assembly | Required | |
| | 2023347-3 | LCEDI | Plug | 40 | Upper Shell Without Datum Mark | Required - With or Without Datum Mark | |
| | 5-2023347-3 | LCEDI | Plug | 40 | Upper Shell With Datum Mark | | |
| | 2023348-3 | LCEDI | Plug | 40 | Pull Bar | Optional | |
| | 8-2069716-2 | LCEDI | Receptacle | 30 | Receptacle Without Datum Mark | Required - With or Without Datum Mark | |
| | 5-2069716-2 | LCEDI | Receptacle | 30 | Receptacle With Datum Mark | | |
| | 2023344-2 | LCEDI | Plug | 30 | Plug Housing Assembly | Required | |
| | 2023347-2 | LCEDI | Plug | 30 | Upper Shell Without Datum Mark | Required - With or Without Datum Mark | |
| | 5-2023347-2 | LCEDI | Plug | 30 | Upper Shell With Datum Mark | | |
| | 2023348-2 | LCEDI | Plug | 30 | Pull Bar | Optional | |
| | 2023488-1 | LCEDI SR | Receptacle | 44 | Board Side Receptacle 9.35H | Required | 9.35 mm |
| | 2023489-1 | LCEDI SR | Plug | 44 | Cable Side Plug | Required | |
| | 2023517-1 | LCEDI SR | Plug | 44 | Upper Shell | Required | |
| | 2023308-3 | LCEDI SR | Receptacle | 40 | Interface Receptacle 4.3H | Required | 4.3 mm |
| | 2023314-3 | LCEDI SR | Plug | 40 | Interface Plug 4.3H | Required | |
| | 2023317-1 | LCEDI SR | Plug | 40 | Upper Shell | Required | |
| | 2023318-1 | LCEDI SR | Plug | 40 | Lower Shell | Required | |
| | 2023308-2 | LCEDI SR | Receptacle | 30 | Interface Receptacle 4.3H | Required | |
| | 2023314-2 | LCEDI SR | Plug | 30 | Interface Plug 4.3H | Required | 4.3 mm |
| | 2023351-1 | LCEDI SR | Plug | 30 | Upper Shell | Required | |
| | 2023352-1 | LCEDI SR | Plug | 30 | Lower Shell | Required | |

Frequently asked questions

Question 1

How can I find supporting documentation?

Answer 1

You can find product information, presentations, electrical models, and product and application specifications at: www.te.com/products/lcedi

Question 2

What components do I need to make up a complete LCEDI or LCEDI SR mated pair?

Answer 2

The charts to the left of the tablet PC on Page 2 feature the necessary components required for a complete LCEDI or LCEDI SR mated pair. The components mentioned in the charts are color-coded, and correspond to their appropriate component in the table on Page 3.

Question 3

What is the difference between LCEDI and LCEDI SR?

Answer 3

Both LCEDI and LCEDI SR support embedded DisplayPort (eDP) applications.

LCEDI is designed to be used on the LCD interface driver board (TCON). Its very low profile height makes it suitable for notebook display panels which are getting slimmer from generation to generation. It is also possible to use LCEDI in tablet PCs because LCEDI has a side mating operation as well as a very low profile height of 1.1mm. This low profile height also has a mated height of 1.1mm.

LCEDI SR is designed to be used on notebook PC system boards and allows top-down or vertical mating operation. Currently LCEDI SR offers a 4.3mm mating height with 30 or 40 position size options. It also has a 9.35mm mating height option available in 44 position with screw locks.

Question 4

What is the advantage of choosing a receptacle or an upper shell with a datum mark?

Answer 4

The datum mark is a small triangle shaped indicator marked on the receptacle's top shell as well as on the upper shell of the plug side assembly. These indicators allow the operator to align the plug and the receptacle connectors accurately during the PCB mounting process or mating.

Question 5

What wire or cable types are acceptable for use with LCEDI / LCEDI SR connectors?

Answer 5

LCEDI and LCEDI SR plugs are compatible with Micro-Coax, Micro-TwinAx (AWG#40 or smaller) and discrete wire (AWG#32 or smaller)

FOR MORE INFORMATION

TE Technical Support Center

USA: +1 (800) 522-6752
Canada: +1 (905) 475-6222
Mexico: +52 (0) 55-1106-0800
Latin/South America: +54 (0) 11-4733-2200
Germany: +49 (0) 6251-133-1999
UK: +44 (0) 800-267666
France: +33 (0) 1-3420-8686
Netherlands: +31 (0) 73-6246-999
China: +86 (0) 400-820-6015

For other country number go to te.com/supportcenter

Part numbers in this brochure are RoHS Compliant*, unless marked otherwise.

*as defined www.te.com/leadfree

te.com

© 2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company. All Rights Reserved.
7-1773457-2 CIS FP 3M 03/2011

I-PEX CABLINE®-VS is a trademark of I-PEX CO., LTD. VESA®, DisplayPort, and Embedded DisplayPort are trademarks of the Video Electronics Standards Association. Blu-ray™ is a trademark of the Blu-ray Disc Association. DVI is a trademark of Digital Display Working Group (DDWG).
TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks. Other logos, product and/or company names might be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

