



[About Us](#)

[Products](#)

[Services](#)

[Support](#)

[Projects](#)

[Web Shop](#)

Products

- > [Board Comparison Chart](#)
- » [Developer's Kits](#)
- » [OEM Boards](#)
- » [QuickStart Boards](#)
- » [Education Boards](#)

↓ **LPCXpresso & mbed**

- > [LPCXpresso LPC1114](#)
- > [LPCXpresso LPC11U14](#)
- > [LPCXpresso LPC11C24](#)
- > [LPCXpresso LPC1227](#)
- > [LPCXpresso LPC1343](#)
- > [LPCXpresso LPC1769](#)
- > [LPCXpresso Prototype](#)
- > [LPCXpresso Base](#)
- > [LPCXpresso Value Pack](#)
- > [LPCXpresso Motor Control](#)
- > [mbed](#)
- » [Displays](#)
- » [Tools](#)
- » [Accessories](#)

LPC11U14 LPCXpresso Board



Picture not showing correct version of LPCXpresso board.

The LPC11U14 LPCXpresso board with NXP's ARM Cortex-M0 microcontroller has been designed to make it as easy as possible to get started with Cortex-M0. The LPCXpresso comprises a target board combined with a JTAG debugger. A free Eclipse-based IDE from Code Red is also included.

The LPC11U14 has 6 kB SRAM, 32 kB Flash, USB 2.0 Full-Speed Device, SSP, I2C, UART, ADC, etc. Embedded Artists also provides a [Prototype board](#) and a [Base board](#) that makes it possible to make experiments and prototyping with many peripherals.

Discount

Embedded Artists and Code Red offer LPCXpresso customers valuable discounts. Embedded Artists gives **15 EUR** discount on the regular [Developer's kits](#) and **7 EUR** off the LPCXpresso Base board. Code Red has an offer to upgrade to full-blown suites. For more information see [LPCXpresso discount](#).

Price Information

EUR

Art.no: **EA-XPR-007** [Buy](#)

Currently out-of-stock

Expected delivery date:
2011-07-30

Price Information

EUR

LPCXpresso Kit containing LPC11U14 and [Base Board](#)

Art.no: **EA-XPR-107** [Buy](#)

Currently out-of-stock

Expected delivery date:
2011-07-30

- Overview
- Specification**
- MCU
- Related Products
- Resources
- FAQ

LPC11U14 LPCXpresso Board

<i>Processor</i>	NXP's Cortex-M0 LPC11U14 microcontroller in LQFP48 package
<i>Flash</i>	32 kB
<i>Data Memory</i>	6 kB
<i>Clock Crystals</i>	12.000 MHz crystal for CPU
<i>Dimensions</i>	35 x 140 mm
<i>Power</i>	3.15V-3.3V external powering, or from USB via JTAG probe (LPC-LINK)
<i>Connectors</i>	<ul style="list-style-type: none"> • mini-B USB connector for LPC11U14 USB interface • All LPC11U14 pins available on expansion connector (2x27 pin rows, 100 mil pitch, 900 mil between rows)
<i>Other</i>	<ul style="list-style-type: none"> • Embedded JTAG (LPC-LINK) functionality via LPCXpresso toolchain • LPC-LINK can be connected to external target processor after modifications to the LPCXpresso board • LED on P100_7