



LOC		DIST		REVISIONS			
P	LY	DESCRIPTION	DATE	OWN	APPROV		
1		PROPOSED	24JAN2011	CD	BC		

- △ MATERIALS AND FINISH:
-HOUSING: GF PBT, COLOR: NATURAL
-CONTACTS: COPPER ALLOY, FINISH: Sn OVER Ni
- MUST COMPLY WITH DIRECTIVE 2002/95/EC (ROHS)
 - THIS PRODUCT HAS NOT COMPLETED VALIDATION TESTING
 - WIRE TYPES AND SIZES ACCEPTED
18, 20 AND 22 AWG SOLID WIRE
18 AND 20 AWG PREBOND STRANDED WIRE
18 AWG STRANDED WIRE (16 STRAND COUNT)
MAX INSULATION OD: 2.10 MM (.083")
STRIP LENGTH: 7.0±1.0 (.276")
 - USE (4) M3 SIZE SCREWS, TORQUE TO 2.5-4.0 IN-LBF
 - DESIGNED TO BE USED WITH BRIDGELUX RS SERIES LED

TYCO ELECTRONICS
CONFIDENTIAL
AND PROPRIETARY

PROPOSED DESIGN
NOT PRODUCTION TOOLED

DESIGN IS SUBJECT TO
CHANGE WITHOUT NOTICE

2154455-1	
PART NO.	
Tyco Electronics Corporation Harrisburg, PA 17105-3608	
SOCKET ASSEMBLY, SOLDERLESS RS LED	
SIZE CASE CODE DRAWING NO A200779C-2154455	
RESTRICTED TO	
CUSTOMER DRAWING	
SCALE 3:1 SHEET 1 OF 2 REV 1	

